

0009



State of Utah  
DEPARTMENT OF NATURAL RESOURCES  
DIVISION OF OIL, GAS AND MINING

Michael O. Leavitt  
Governor

Ted Stewart  
Executive Director

James W. Carter  
Division Director

355 West North Temple  
3 Triad Center, Suite 350  
Salt Lake City, Utah 84180-1203  
801-538-5340  
801-359-3940 (Fax)  
801-538-5319 (TDD)

October 23, 1996

TO: Daron Haddock, Permit Supervisor

FROM: Steven M. Johnson, Reclamation Hydrologist *SMT*

RE: Sowbelly As-Builts, Castle Gate Mine, Amax Coal Company, ACT/007/004 Phase I, Folder #2, Carbon County, Utah

### SYNOPSIS

Amax Coal Company completed regrading and seeding reclamation in the fall of 1995 for the Sowbelly Canyon permit area. They have requested Phase I bond release and have submitted as-builts for the regrading, sediment control and diversion in the canyon.

On October 22, 1996, the Division and a representative from OSM joined Johnny Pappas in a Phase I inspection of Sowbelly Canyon. This inspection began at 10:00 a.m. and lasted until 12:00 noon. Grading and establishment of the drainage and sediment control systems were the major components of the inspection.

This memorandum provides the analysis of hydrology from the as-builts and the inspection in determining if release of Phase I bond is appropriate.

### ANALYSIS

#### RECLAMATION PLAN

#### HYDROLOGIC INFORMATION

Regulatory Reference: R645-301-760

#### **Analysis:**

Section 3.2-5(4) covers the reclamation alternate sediment control measures that will be implemented in the reclamation of this canyon. This section was permitted prior to reclamation activities in 1995. Section 3.2-5(4) refers to Appendix 3.2I for sediment control as-builts. Appendix 3.2I shows USLE calculations that demonstrate that the alternate sediment control measures are adequate to treat reclaimed areas. First, Amax Coal says that the amount of sediment from the undisturbed area is greater than the disturbed areas; therefore, the

sediment is controlled on the reclaimed areas. Second, Amax Coal says that an analysis which uses predisturbed assumptions on the disturbed areas results in only a slightly lower sediment production. Finally, the data shows that sediment production per acre is less from the reclaimed areas than the sediment production from undisturbed areas.

Section 3.2-10 discusses the reclamation as-builts. This section discusses the reclamation activities performed in 1995. This section also describes the use of mulch as sediment in the reclaimed areas.

Appendix 3.2G is the reclamation as-built, hydrology calculations. In this section the channel configurations are shown. All channels are shown to be built to design and certified by a professional engineer, except SBRD-8. This channel was only slightly modified in order to leave a more natural, stable channel; therefore the engineer certified that the channel was stable and capable of conveying the required storm runoff, rather than certifying the designs.

During the summer of 1996, the reclamation channels withstood several thunderstorms including one storm that produced nearly one inch of rainfall. There is some evidence that flow was conveyed in some of the channels but there were no signs of channel destabilization. Flow was minimal in the channels to the point that two automated samplers in the main channel (one upstream portions of the reclamation area, one downstream of the reclamation area) collected no data.

Sediment control is currently met by surface roughening and vegetation. Vegetation is not at a level that is in itself adequate for sediment control but when combined with the surface roughening sediment control and runoff control is adequate. Further, the roughening has enhanced the potential for vegetation which will continue to act as long term sediment control.

#### **Findings:**

The reclamation hydrologic designs for Sowbelly Canyon are complete and field inspection shows that the ditches are stable. Sediment control is adequate in surface roughening and vegetation.

#### **RECOMMENDATION**

The hydrologic design and construction in Sowbelly Canyon have produced stable channels. Sediment control will be met in the short through roughening and vegetation, and long terms by vegetation.