


State of Utah
Division of Oil, Gas and Mining
Utah Coal Regulatory Program



Willow Creek Mine
Analysis and Findings
April 22, 1996

TABLE OF CONTENTS

ADMINISTRATIVE FINDINGS	1
IDENTIFICATION OF INTERESTS, VIOLATION INFORMATION, AND RIGHT OF ENTRY INFORMATION	1
Identification of Interests	1
Violation Information	2
Right of Entry	2
UNSUITABILITY CLAIMS	3
PERMIT TERM, INSURANCE, PROOF OF PUBLICATION, FACILITIES OR STRUCTURES USED IN COMMON, FILING FEE, NOTARIZED SIGNATURE	4
Permit Term	4
Insurance	4
Proof of Publication	5
Facilities or Structures Used in Common	5
Filing Fee	5
Notarized Signature	5
TECHNICAL ANALYSIS	7
INTRODUCTION	7
SUMMARY OF PERMIT STIPULATIONS	7
ENVIRONMENTAL RESOURCE INFORMATION	9
GENERAL	9
HISTORIC AND ARCHEOLOGICAL RESOURCE INFORMATION	10
CLIMATOLOGICAL RESOURCE INFORMATION	12
VEGETATION RESOURCE INFORMATION	12
FISH AND WILDLIFE RESOURCE INFORMATION	14
Fish and Wildlife	14
Threatened and Endangered Species	16
SOILS RESOURCE INFORMATION	18
LAND-USE RESOURCE INFORMATION	20
Current Uses	20
Previous Mining Activity	22
ALLUVIAL VALLEY FLOORS	22
GEOLOGIC RESOURCE INFORMATION	23
HYDROLOGIC RESOURCE INFORMATION	26
Sampling and analysis.	26
Baseline information -- Ground Water	27
Baseline information -- Surface Water	29
Baseline cumulative impact area information	31
Survey of Renewable Resource Lands	31
Alluvial Valley Floors	31
Modeling	31
Alternative Water Source Information	31
Probable Hydrologic Consequences	31
Ground Water Consequences	32
Surface water consequences	35

MAPS, PLANS, AND CROSS SECTIONS OF RESOURCE INFORMATION	37
Subsurface Water Resource Maps	37
Surface Water Resource Maps	37
Monitoring Station Map	38
Well Maps	38
Contour Maps	38
Coal Resource and Geologic Information Maps	38
Water Quality	38
Subsurface Water Resource Maps	38
Affected Area Boundary Maps	39
Existing Structures and Facilities Maps	39
Mine Workings Maps	39
Permit Area boundary Maps	39
Surface and Subsurface Manmade Features Maps	39
OPERATION PLAN	41
GENERAL REQUIREMENTS	41
EXISTING STRUCTURES	41
RELOCATION OR USE OF PUBLIC ROADS	41
AIR POLLUTION CONTROL PLAN	42
COAL RECOVERY	42
SUBSIDENCE CONTROL PLAN	43
Renewable Resources Survey	43
Subsidence Control Plan	44
Performance standards for subsidence control	49
Notification	49
SLIDES AND OTHER DAMAGE	51
OPERATIONAL TOPSOIL AND SUBSOIL	52
INTERIM STABILIZATION	53
FISH AND WILDLIFE PROTECTION	54
Potential Effects and General Comments	54
Protection Measures	55
Enhancement	58
ROAD SYSTEMS AND OTHER TRANSPORTATION FACILITIES	58
Road classification system	59
Plans and drawings	60
Performance Standards	62
SPOIL AND WASTE MATERIALS	62
Disposal of noncoal mine wastes	62
Coal Mine Waste	63
Refuse Piles	64
Impounding Structures	64
Burning and Burned Waste Utilization	65
Return of Coal Processing Waste to Abandoned Underground Workings	65
Excess Spoil	65
Excess Spoil: Valley Fills/Head-of-Hollow Fills	65
Excess Spoil: Durable Rock Fills	66
Excess Spoil: Preexisting Benches	66
OPERATIONAL HYDROLOGIC INFORMATION	66
Surface-water Protection	66
Groundwater Monitoring	67
Surface-Water Monitoring	69
Acid- and Toxic-forming Materials	69

Water Rights	70
Transfer of Wells	70
Discharges into an Underground Mine	71
Gravity Discharges	72
Water-Quality Standards and Effluent Limitations	72
Diversions	72
Stream Buffer Zones	73
Sediment Control Measures	73
Siltation Structures	73
Sediment Ponds	73
Other Treatment Facilities	73
Exempt Areas	74
Discharge Structures	74
Impoundments	74
Casing and Sealing of Wells	74
SUPPORT FACILITIES AND UTILITY INSTALLATIONS	75
UTILITY INSTALLATIONS	77
SIGNS AND MARKERS	77
USE OF EXPLOSIVES	78
General Requirements	78
Preblasting Survey	79
General Performance Standards	79
Blasting Signs, Warnings, and Access Control	80
Control of Adverse Effects	80
Records of Blasting Operations	80
MAPS, PLANS, AND CROSS SECTIONS OF MINING OPERATIONS	81
Certification Requirements	81
RECLAMATION PLAN	83
GENERAL REQUIREMENTS	83
POSTMINING LAND USES	83
APPROXIMATE ORIGINAL CONTOUR RESTORATION	85
BACKFILLING AND GRADING	85
Previously Mined Areas	87
MINE OPENINGS	87
RECLAMATION TOPSOIL AND SUBSOIL	88
ROAD SYSTEMS AND OTHER TRANSPORTATION FACILITIES	89
RECLAMATION HYDROLOGIC INFORMATION	90
Surface-Water Protection	90
Ground Water Monitoring	90
Surface-Water Monitoring	91
Water Rights	91
Acid- and Toxic-forming Materials	91
Transfer of Wells	92
Discharges into an Underground Mine	92
Gravity Discharges	93
Water quality standards and effluent limitations	93
Diversions	93
Stream buffer zones	93
Sediment control measures	94
Siltation structures	94
Sedimentation ponds	94
Other treatment facilities	94

Exemptions for siltation structures	94
Discharge structures	94
Impoundments	95
Structure Removal	95
Casing and Sealing of Wells	95
Revegetation Methods	97
Success Standards	100
Fish and Wildlife Plan	101
MAPS, PLANS, AND CROSS SECTIONS OF RECLAMATION OPERATIONS . .	102
Reclamation facilities maps	102
Final surface configuration maps	102
Reclamation monitoring and sampling location maps	103
BONDING AND INSURANCE REQUIREMENTS	103

ADMINISTRATIVE FINDINGS

Last revised - April 22, 1996

ADMINISTRATIVE FINDINGS

IDENTIFICATION OF INTERESTS, VIOLATION INFORMATION, AND RIGHT OF ENTRY INFORMATION

Regulatory Reference: UCA R645-301-112; R645-301-113; R645-301-114

Analysis:

Identification of Interests

Cyprus Plateau Mining Corporation (hereafter referred to as "Cyprus") submitted this mining and reclamation permit application. Cyprus is a wholly-owned subsidiary of, in ascending order, Cyprus Western Coal Company, Cyprus Amax Coal Holding Company, Cyprus AMAX Coal Company, Amax Energy, Inc., and Cyprus Amax Minerals Company. Cyprus, as the Applicant, is authorized to do business in Utah. All of the corporations were incorporated under the laws of the State of Delaware.

The application shows the Applicant's address, telephone number, and employer identification number. Cyprus will be responsible for payment of the abandoned mine land reclamation fees. The resident agent is CT Corporation System of Salt Lake City, Utah. The main MSHA number will be 42-02113; some facilities will have separate MSHA numbers.

Figure 2.1-1 is an organizational chart for Cyprus Amax Minerals Company. Exhibit 1 contains lists of operations affiliated with the Applicant and with G. R. Spindler, an officer or director of Cyprus and companies that own or control Cyprus. The information in this section of the application is complete.

Table 2.1-1 is a summary of corporate information and shows addresses, telephone numbers, and employer identification numbers for Cyprus Amax Minerals Company, Amax Energy Company, Cyprus AMAX Coal Company, Cyprus Amax Coal Holding Company, Cyprus Western Coal Company, and Cyprus Plateau Mining Corporation. This table also shows the names, most social security numbers, titles, and dates positions were assumed for the officers and directors of these companies.

Surface and mineral ownership information is presented in Section 2.1.2.4 and on Maps 1 and 2. The surface of the disturbed area at the proposed mine site is owned by Cyprus, and the surface of the preparation plant, Gravel Canyon, and Crandall Canyon is owned by Blackhawk Coal Company and leased to AMAX Coal Company. Cyprus will manage the lands for mining use under operating agreements with Cyprus Western Coal Company and AMAX Coal Company.

According to Map 1 and the text, Harry C. and Alda M. Edwards own land contiguous to the proposed permit area, but the application does not include their address. It says the address is not in Carbon County records. It should be provided if it becomes available.

ADMINISTRATIVE FINDINGS

The list of surface and mineral owners in Section 2.1.2.4 indicates Carbon County owns surface land both within and contiguous to the proposed permit area. The area contiguous to the proposed permit area is apparently in the southwest quarter of Section 6, Township 13 South, Range 10 East. In the most recent version of this map, there is no ownership symbol in this piece of land.

Map 2 shows regional coal ownership. The text has a list of legal and equitable owners of record of the coal to be mined within the proposed permit area. These are Cyprus Western Coal Company, Blackhawk Coal Company, Carbon County, the Bureau of Land Management, and the Utah Department of Natural Resources Division of State Lands and Forestry. Owners of coal rights contiguous to the proposed permit area are the Bureau of Land Management, Blackhawk Coal Company, Carbon County, the State of Utah, PacifiCorp, Dennis Bettino et al., Mathis Land, Inc., and Harry and Alda Edwards.

Violation Information

Compliance information is presented in Section 2.1.4 and Exhibit 2. Neither the Applicant nor any affiliate, subsidiary or persons controlled by or under common control with the Applicant has had a federal or state mining permit suspended or revoked in the five years prior to the date of the application, and these entities have not forfeited a mining bond or similar security deposited in lieu of bond.

R645-301-113.300 requires a list of all unabated cessation orders and air and water quality violation notices received by the Applicant or any operation owned or controlled by either the Applicant or any person that owns or controls the Applicant. The status of some violation notices in Exhibit 2 is listed as "pending." It is believed that the various operations are working within required schedules to complete abatement of any outstanding enforcement action.

Right of Entry

Cyprus's application says right of entry for surface lands and coal extraction is based on operating agreements with Cyprus Western Coal Company and AMAX Coal Company. AMAX Coal Company holds leases for the Castle Gate Preparation Plant, Gravel Canyon, and Crandall Canyon areas from Blackhawk Coal Company. In addition, Cyprus Western Coal Company has purchased surface entry and coal extraction rights for mining areas and the Willow Creek surface facilities area from Blackhawk under the terms of a sales agreement dated December 14, 1995.

Section 2.1.5.1 has legal descriptions for fee surface and coal and for coal leases held by Cyprus Western Coal Company.

The description of Federal Consolidated Lease SL-048442-050115 includes an exception for a partial assignment to Amca Coal Leasing. The exception is for the SW $\frac{1}{4}$ of Section 1, Township 13 South, Range 10 East. Since Amca Coal Leasing has acquired rights to mine all coal seams in this area, the partial assignment is interpreted to mean that a portion of the lease was assigned to them. This parcel is outside the proposed permit area.

ADMINISTRATIVE FINDINGS

Last revised - April 22, 1996

Right of entry information is considered complete and accurate with one exception. Cyprus has applied with the Bureau of Land Management for leases in the northern part of the proposed permit area. Right of entry for these areas is contingent on approvals which the application says are anticipated in the first quarter of 1996. The Division cannot allow mining in these areas without right of entry information. The Division will need to require Cyprus to restrict mining to those areas for which Cyprus has right of entry.

For all other parts of the permit area, Cyprus presents information describing the specific lands where they claim right of entry. The application also describes the documents granting the rights to enter and begin mining and reclamation operations.

There are also a few anomalies in the legal descriptions that Cyprus should correct. Under the heading "Fee Surface - CWCC," the application gives a description for portions of Township 13 South, Range 9 East, Section 1. The first exception under this description indicates Cyprus does not have right of entry for a portion of the NE/4 SW/4. The NE/4 SW/4 is not within the portion of Section 1 described.

The same section of the application mentions an exception for the Castle Gate Cemetery. The exceptions would be better listed following descriptions of the sections in both Township 12 South, Range 10 East, and Township 13 South, Range 10 East.

Not all land described in the application is within the proposed permit area. Some of it is in the Castle Gate permit area. The reason for including these descriptions in this application is unknown.

Findings:

The application is complete and accurate. However, the following stipulation must be met:

1. **Stipulation:** There are two proposed federal leases in the northern part of the proposed permit area. Cyprus states in the application that they are in the process of obtaining rights to mine these leases, but, until they obtain the right to enter and begin mining and reclamation operations, the Division cannot approve mining in these areas.

UNSUITABILITY CLAIMS

Regulatory Reference: UCA R645-301-115

Analysis:

To the best of the Applicant's knowledge, the permit area is not within and does not include any area designated or under current study for designation as unsuitable for mining. No operations are proposed within 300 feet of an occupied dwelling, but portions of the mine surface

ADMINISTRATIVE FINDINGS

facilities would be within 100 feet of a public road. The application says this road is State Highway 191, but it is a U. S. Highway.

In compliance with R645-103-234.100 through 400, Cyprus has obtained approval from the Utah Department of Transportation for an encroachment on the highway. On May 11, 1995, a public hearing was held in the Carbon County Courthouse concerning the operations within 100 feet of the public road. The application includes a copy of a letter requesting that the Division hold a public hearing and a copy of the Division's notice. The hearing was attended by Lowell Braxton of the Division who documented it in a Division memorandum. No comments were made concerning conduct of mining within 100 feet of Highway 191. Based on appropriate notice and lack of adverse public comment, the Division found on July 6, 1995, that the interests of the public and affected landowners will be protected from the mining activities proposed for within 100 feet of the highway right-of-way.

The Division is unaware of any designation of the area as unsuitable for mining.

Findings:

This portion of the application is complete and accurate.

PERMIT TERM, INSURANCE, PROOF OF PUBLICATION, FACILITIES OR STRUCTURES USED IN COMMON, FILING FEE, NOTARIZED SIGNATURE

Regulatory Reference: UCA R645-301-116; R645-301-117; R645-301-118; R645-301-123

Analysis:

Permit Term

The application is for an initial permit term of five years beginning from the date of permit approval and issuance. It says Cyprus has submitted complete information for the entire anticipated life of the Willow Creek Mine to support future permit renewals.

In meetings with the Division, Cyprus and its consultant's personnel have indicated that, depending on market and mining conditions, they intend to eventually reopen the Crandall Canyon shafts and mine in this area. Although the plans are tentative, the blanket statement that this application is for the entire anticipated life of the mine is not entirely correct. It would be more accurate to qualify this statement with a comment that Cyprus may seek to add additional areas to the permit area in the future.

ADMINISTRATIVE FINDINGS

Last revised - April 22, 1996

Insurance

A copy of the certificate of insurance is in Exhibit 12 and in the Division's files. The policy number is GL1212703. The company affording coverage is the National Union Fire Insurance Company of Pittsburgh PA, and the policy expires July 1, 1996.

American Electric Power Company ("AEP") has also submitted an insurance policy for the area which they formerly permitted, the Willow Creek Mine, INA/007/002. The policy is retroactive to July 1, 1990, and expires July 1, 1996. Companies affording coverage are the United State Fire Insurance Company and Energy Insurance (Bermuda) Ltd. The policy includes general aggregate coverage for \$1,000,000 and \$250,000 for each occurrence. This policy does not meet requirements for a coal mining and reclamation operation, but AEP is not proposing any operations.

Proof of Publication

A copy of the proof of publication has been included for insertion in Exhibit 3. The legal description in the advertisement is correct, and it includes other information required by R645-300-121.100.

Facilities or Structures Used in Common

Cyprus plans to use the Castle Gate Preparation Plant, associated loadout, and may use the Crandall and Gravel Canyon areas to meet potential ventilation and reclamation needs. These areas are included in the approved Castle Gate mining and reclamation plan. Plans for these facilities are included in the Willow Creek application. The application says that, during an interim period following review and approval of the Willow Creek application and during development of the Willow Creek Mine, the shared facilities may be included in and bonded under both the Willow Creek and Castle Gate permits. Cyprus anticipates that a permit revision will be submitted to eliminate the shared facilities from the Castle Gate permit.

These commitments satisfy the requirements of R645-301-117.300.

Filing Fee

The Division has on file a copy of the check paid for the filing fee.

Notarized Signature

The application says the required notarized signature of a responsible Cyprus official that the information in the application is true and correct to the best of the official's information and belief was included in the transmittal which accompanied the permit application submittal. The required statement was included with the transmittal letter and is in the application before the table of contents.

ADMINISTRATIVE FINDINGS

Findings:

These sections of the application are complete and accurate.

TECHNICAL ANALYSIS

Last revised - April 22, 1996

TECHNICAL ANALYSIS

INTRODUCTION

The Division has conducted a thorough review of the Willow Creek permit application plan (PAP). The first round of the review was completed in November 1995 and resulted in a list of plan deficiencies. These deficiencies were responded to by Cyprus Plateau Mining Company (Cyprus) in February 1996. This Technical Analysis (TA) provides information derived from the Division's review of the February 1996 submittal, and resulted in a finding of technical inadequacy. No permit will be issued at this time because of the outstanding technical deficiencies listed below. Cyprus may submit information that properly answers these deficiencies to complete the application process.

This TA is written as part of the permit review process. It documents the Findings that the Division has made to date regarding the application for a permit and is the basis for permitting decisions with regard to the application. The TA is broken down into logical section headings which comprise the necessary components of an application. Each section is analyzed and specific findings are then provided which indicate whether or not the application is in compliance with the requirements.

Often the first technical review of an application finds that the application contains some deficiencies. The deficiencies are discussed in the body of the TA and are identified by a regulatory reference which describes the minimum requirements. In this Technical Analysis we have summarized the deficiencies at the beginning of the document to aid you in responding to them. Once all of the deficiencies have been adequately addressed, the TA will be made final.

Some sections of the PAP are currently approved under the Castle Gate Mine permit. These sections were thoroughly reviewed when they were approved under that permit and the technical analysis is included within the Castle Gate Mine TA.

SUMMARY OF PERMIT STIPULATIONS

The following are stipulations to the Willow Creek permit.

1. There are two proposed federal leases in the northern part of the proposed permit area. Cyprus states in the application that they are in the process of obtaining rights to mine these leases, but, until they obtain the right to enter and begin mining and reclamation operations, the Division cannot approve mining in these areas.
2. Features 5, 10, 20, 61, and 65 of cultural resource site 42Cb 1000 must not be disturbed until the Applicant has completed mitigation required by the Division of State History, and until the Division and State History have accepted the results.

TECHNICAL ANALYSIS

3. CPMC will amend the MRP, both section 3.1 SOILS INFORMATION and Exhibit 5 SOILS INFORMATION, with the chemical and physical analysis results from the 1996 Order-I soil survey.

TECHNICAL ANALYSIS

Last revised - April 22, 1996

ENVIRONMENTAL RESOURCE INFORMATION

Regulatory Reference: Pub. L 95-87 Sections 507(b), 508(a), and 516(b); 30 CFR Sec. 783., et. al.

GENERAL

Regulatory Reference: 30 CFR Sec. 783.12; R645-301-411, -301-521, -301-721.

Analysis:

The Permit Application Package (PAP) uses text along with maps, cross sections, and plans to describe the lands in the proposed permit area and adjacent areas that may be affected or impacted by the proposed coal mining and reclamation operations; the existing or premining land uses; the baseline ground and surface water resources; and the geologic and climatological information.

Rugged terrain; low precipitation and seasonally harsh weather conditions; thin, marginal soils; limited vegetative cover; restricted water resources; and significant reserves of high quality coal have determined land use in the permit and adjacent areas. Underground coal mining and related activities, the railroad in Price Canyon, PacifiCorp's Carbon Generating Station at the mouth of Willow Creek, scattered oil and gas production, and limited timber harvesting are historic and current commercial uses of land in the permit and adjacent areas. Highways and utilities follow Willow Creek and Price Canyons through the rugged terrain. Undeveloped lands are used for low-intensity grazing, wildlife habitat, and dispersed recreation such as hunting, fishing, and hiking.

The Castle Gate (Willow Creek) cemetery is located within the permit area. There are abandoned townsite but no occupied residential land in the permit area. The nearest residences are in Helper and the adjacent community of Martin, located approximately two miles down Price Canyon from the Carbon Generating Station.

Regional and premining land-use information in Section 3.4, Exhibit 8, and on Maps 9, 10, and 11 includes: land use capability and condition; locations of structures and facilities and surface disturbances from previous mining activities; location and extent of underground workings; existing land uses; land use designations, classifications and zoning restrictions; land use constraints due to environmental factors; and locations of the Castle Gate cemetery and other identified cultural, historic, and paleontological resources.

Section 4.5 contains information on the affected areas and timing of disturbance for the Castle Gate preparation plant, Schoolhouse Canyon refuse disposal area, Castle Gate loadout area, Gravel Canyon soil stockpile area, Crandall Canyon shaft area, and Willow Creek Mine surface facilities. Information on Maps 1, 2, 9, and 18 includes surface and mineral ownership; right of entry; and previous mining and related disturbances.

Existing configuration, conditions, structures, and surface and subsurface facilities are shown on Maps 11, 18A, and 18B and Exhibit 20. The pipes carrying water through the

TECHNICAL ANALYSIS

proposed permit area from the Price water treatment plant to Price are shown on Maps 18A and 18B. Map 11 shows both existing and projected surface facilities, contours, etc. on one map to highlight potential conflicts between existing resources and proposed disturbance. Map 18A shows the Mine Surface Facilities - Premining Configuration and Map 18B shows the Mine Surface Facilities - Proposed Configuration and Facilities.

The baseline hydrologic monitoring plan is in Exhibit 12. Baseline data collected to date (05/02/95) and a description of the hydrogeology of the area are in Section 3.7 of the PAP.

Findings:

The Permit Application Package contains descriptions, or refers to locations where the descriptions may be found, of the existing premining environmental resources within the proposed permit area and adjacent areas that may be affected or impacted by the proposed coal mining operation.

HISTORIC AND ARCHEOLOGICAL RESOURCE INFORMATION

Regulatory Reference: 30 CFR Sec. 783.12; R645-301-411.

Analysis:

Section 3.4.3 contains limited cultural and historic resource information. Abbreviated and full reports about cultural resources in the area are in Volume 15 and are considered confidential. Map 11, also in the confidential file, shows facilities area cultural resources.

Three cultural resource areas were previously identified, and these were reclaimed as part of the Abandoned Mines Reclamation Program work in the area in 1990. Three additional sites were located as part of the work done for the Willow Creek Mine. Site 42Cb1027 is in Castle Canyon and consists of a series of six historic features. It was not considered eligible for listing in the National Register of Historic Places. Site 42Cb1001 is a series of three pictograph panels. Site 42Cb1000 includes 65 features associated with the Castle Gate Mines and the Castle Gate townsite. Both of these latter sites were considered potentially eligible for listing in the National Register of Historic Places.

Four new paleontological sites were found, each consisting of one or more trace fossils. These were not considered unique or unusual. However, the consultant recommended that any unusual fossil remains, especially fossil bone materials, encountered during mining be evaluated if possible.

The application also includes a cultural resources survey for a turn lane on the highway. The Applicant no longer intends to build the turn lane.

Following the field investigations, site listing forms were prepared and submitted to the State Historic Preservation Office (SHPO). The Applicant met with the SHPO to review cultural resource considerations and potential mitigation requirements. The application says the results of

TECHNICAL ANALYSIS

Last revised - April 22, 1996

this meeting and subsequent discussions were incorporated in the mining and reclamation planning process in order to minimize or mitigate potential mining related impact.

Exhibit 8 contains a letter from the Division of State History dated October 24, 1995. It says the background information material is accurate and well done and that their office concurs with the accuracy of the material. It also says a determination of no adverse effect can be reached if sensitive treatment of the mine property is considered during the opening of the mine and that the Castle Gate explosion would be a focus of their concern. This was confirmed in a telephone conversation with Mr. James Dykman. He said the areas about which State History is most concerned are the Castle Gate Cemetery and the Castle Gate No. 2 Mine portal.

Most potential effects are being avoided simply by not proposing disturbance in critical areas. The mine portal and cemetery would not be disturbed under the current proposal. In addition, the Applicant commits in Section 4.5.2.1 to mitigate any known significant cultural or historic resource sites prior to site disturbance.

On April 17 and 22, 1996, the Division received correspondence from State History concerning the various sites that might be affected by the mine. They concurred that there would be no effect for sites 42Cb 1001 and 1027. Site 42Cb 1027 is not significant, and 42Cb 1001 would not be disturbed.

Site 42Cb1001 is within the proposed disturbed area, and the closest proposed disturbance is the conveyor and a steep cut adjacent to the conveyor. It appears the cut slope forms about a 20-foot difference in elevation between the conveyor and the site. For this reason, there would probably be no damage to the pictographs from coal fines originating on the conveyor. It is important that the site not be disturbed without specific consent from the Division and State History.

Several features associated with site 42Cb 1000 would be affected by the proposed mine. Five important features of this site would be affected, but the effects would be mitigated in accordance with a plan submitted to the Division and State History.

Until the data recovery discussed in State History's April 22, 1996, letter is completed and the Division and State History have reviewed and accepted the results, the sites must not be disturbed.

Findings:

This portion of the application is considered complete and accurate. The Division should make the following stipulations:

1. **Stipulation:** Features 5, 10, 20, 61, and 65 of cultural resource site 42Cb 1000 must not be disturbed until the Applicant has completed mitigation required by the Division of State History, and until the Division and State History have accepted the results.

CLIMATOLOGICAL RESOURCE INFORMATION

Regulatory Reference: 30 CFR Sec. 783.18; R645-301-724.

Analysis:

Climatological information is found in Sections 3.7.1.4, and 3.7.4. Information specific to temperatures, precipitation and wind is located in Sections 3.7.4.1, 3.7.4.2, and 3.7.4.3, respectively. More climatological information is found on Page 3.7-28, Section 3.7.3.1. Table 3.7-7 is the summary of climatological data.

Average monthly temperatures are listed in Table 3.7-7. The frost free period ranges from 60 to 120 days, depending on elevation and exposure. Temperatures can change rapidly when fast moving storm fronts pass. Annual precipitation is 14.8 inches. Rainfall frequently comes in brief, high-intensity storms. Average monthly precipitation is lowest in June, 0.65-inches, and highest in September, 1.86-inches.

Table EXDS-5 and Table 3.7-13 provide return periods for short duration storms at three stations near the permit area. The final duration-frequency values for the permit area were derived by taking the simple mean of the three stations with record.

Prevailing summer wind are from the West and Northwest, usually blowing less than 20 mile per hour. Winter wind tend to be more variable, blowing frequently from the Northeast. Diurnal flow tend to be upslope in the daytime and downslope at night.

Findings:

Cyprus has included sufficient climatological information to make the necessary determinations about hydrologic designs and air quality.

VEGETATION RESOURCE INFORMATION

Regulatory Reference: 30 CFR Sec. 783.19; R645-301-320.

Analysis:

Section 3-2 contains the results of vegetation surveys done for the proposed Willow Creek Mine. The application says three plant community types were surveyed for this study: 1) Disturbed Plant Community; 2) Reclaimed Plant Community; and 3) Riparian Plant Community. This classification is also mentioned in Section 3.2.2.2. This is inconsistent with information provided later in the application which shows previously undisturbed, non-riparian areas that would be disturbed. In addition, under the heading "Vegetation Mapping," the application says data for the water tank and fan area disturbances will be collected in 1995. This data has been collected and the commitment is no longer appropriate.

TECHNICAL ANALYSIS

Last revised - April 22, 1996

The application gives general summaries of vegetation information for vegetation types found in the proposed permit area. This information is from a 1981 study by Mariah Associates. According to their classification, there were six vegetation types within the proposed permit area.

In this section under the heading "Mixed Brush Vegetation Type," the application says more "xeric" sites frequently support wolfberry and other species. In this sentence, "xeric" should probably be "mesic."

In Section 3.2.2.3, the application indicates only generalized summaries of the original Mariah Associates data could be found. The Division's files contain complete copies of raw data for the Mariah Associates report.

Vegetation sampling was done in 1994 for disturbed, reclaimed, and riparian areas. Sampling was done in 1995 for the reclaimed Royal Refuse Pile, areas not previously disturbed by mining, and for the pinyon-juniper reference area. 1994 had below average precipitation, but precipitation in 1995 was much above average with an unusually wet spring.

Total vegetation cover in the disturbed plant community was 26.72%. Ground cover, including vegetation cover and litter, was 46.92%. Dominant plants included Indian ricegrass, downy brome, Salina wild rye, and rubber rabbitbrush. Relative cover by species commonly classified as weeds was 15.4%. Production was estimated at 472 pounds of air dry forage per acre based on 22 transects.

The Reclaimed Plant Community had 28.73% vegetation cover and 48.13% ground cover. Dominant species included pubescent wheatgrass, western wheatgrass, kochia, yellow sweet clover, prostrate summer cyprus, rubber rabbitbrush, and fourwing saltbush. Relative cover from plants usually classified as weeds was 19.2%. Production was estimated at 926 pounds per acre. Fifty transects were sampled for cover. The application indicates a maximum sample size was used, but the regulations do not have a maximum sample size. For final bond release, this would be important, but for initial information, the application contains the data the Division needs.

The Royal Refuse Pile was sampled as a site similar to reclaimed areas at Willow Creek. Total plant cover averaged 31.0%. Fourwing saltbush was the dominant plant in this area comprising 45% of the relative cover. Crested wheatgrass was next at 30% followed by downy brome at 12% and rubber rabbitbrush at 6%. Seven samples were taken in this area, and the minimum sample size was calculated at 5.5 samples. While this is adequate for initial vegetation information, it is not adequate for a baseline revegetation success standard since the "Vegetation Information Guidelines" Appendix B, referenced in the regulations, requires a minimum of 15 samples for the sampling method used. Production was estimated at 926 pounds per acre based on 50 samples. The minimum sample size should have been 66 samples. As with production information for the reclaimed plant community, this suffices for initial information but would not be adequate as a final bond release success standard.

About six acres of undisturbed native vegetation would be affected by the mine. The application says comparison of disturbance area and vegetation mapping and field evaluation of

TECHNICAL ANALYSIS

the areas of native vegetation to be disturbed resulted in a determination that all of the new disturbance corresponds to the pinyon-juniper community.

The pinyon-juniper reference area is located near the mouth of Eagle Canyon and is shown on Map 5. The reference area boundaries have been marked in the field with steel fence posts. Total plant cover averaged 20.08%. Salina wild rye comprised 67% of the total cover followed by basin big sage. Fourteen cover transects were sampled.

Woody plant density in the reference area was 1482 per acre. Basin big sagebrush, broom snakeweed, and fourwing saltbush were the most common woody plants. Forage production was estimated at between 450 and 600 pounds per acre for 1994 and 1995.

Range condition of the reference area was judged as being fair according to methods used by the Natural Resources Conservation Service. It received an ecological rating of 38. The corresponding range site is the Upland Very Steep Shallow Loam (Pinyon-Juniper) ecological site.

The undisturbed area that compares to the pinyon-juniper reference area had 22.33% cover, and a t-test indicates this is not significantly different than the reference area. There was also no significant difference in woody plant density.

Sampling methods used for the riparian area were different from those used for the other areas. These methods allow the percentage to be greater than 100%. Four layers of the canopy were measured separately. The total cover from these layers was 70.43%. Nearly half of this total was from coyote willow and redtop. Other important species included Fremont cottonwood, narrowleaf cottonwood, and yellow sweet clover.

For the requirements of R645-301-321, the application's vegetation information is considered adequate. However, the Applicant is proposing to use some of the baseline information as a revegetation success standard. As discussed under "Revegetation," the information is not adequate for this purpose with the exception of the vegetation data for the riparian area.

Findings:

The baseline vegetation information meets the requirements of R645-301-321.

TECHNICAL ANALYSIS

Last revised - April 22, 1996

FISH AND WILDLIFE RESOURCE INFORMATION

Regulatory Reference: 30 CFR Sec. 784.21; R645-301-322.

Analysis:

Fish and Wildlife

About 312 species of vertebrate wildlife could exist within the proposed permit area. Of these, 60 are known to live in the area, 23 are likely inhabitants, 95 could occur in the area but may be just transients, and 134 are unlikely to be in the permit area based on known range or habitat preference.

Three amphibian species are considered potential residents of the mine plan area. Of these, the tiger salamander is the only species classified as having high interest to the State.

Three species of reptiles are known, based on observations, to exist in the proposed permit area, but eleven species are considered potential inhabitants. Two high interest species may be in the proposed permit area, the milk snake and the collared lizard. The application discusses habitat where these species are normally found.

Site reconnaissance surveys in 1994 found 40 bird species although 104 species are considered potential inhabitants of the proposed permit area. Several raptor species are known or believed to nest in the area, and raptor surveys have been done in various parts of the proposed permit area intermittently since 1979. Map 7 shows known nest sites. At least six golden eagle nests are within one-half mile of the proposed surface facilities. Future verification of nesting activity will occur prior to construction in 1996/1997, and appropriate mitigation measures will be implemented in consultation with the Division and Wildlife Resources.

The application discusses habitat requirements for thirteen other bird species. The reasons for singling out some of these species is unknown. Some of the thirteen are not known to occur in the West Tavaputs Plateau and are unlikely to inhabit the mine plan area.

In Section 4.3.3.4, the application says that where full extraction mining is conducted beneath exposed cliff faces or potential habitat for tree-nesting raptors, field reconnaissance will be completed for mining areas at least two years prior to mining to evaluate the presence of any sensitive species such as canyon sweetvetch, golden eagle nests, or goshawk nests. If sensitive species are found in areas having the potential for significant subsidence-related impacts, a mitigation plan will be formulated in consultation with appropriate State and federal agencies. The plans may include leaving buffer zones of coal, obtaining take permits for golden eagle nests, or other plans.

It is extremely unlikely subsidence would affect canyon sweetvetch. This species does not normally grow on cliffs such as could potentially fail during subsidence. Even in the unlikely event there were subsidence cracks in the area of some plants, they would probably not be damaged.

TECHNICAL ANALYSIS

In other areas eagle nests have been lost as a result of subsidence, and the plans to check potential habitat for nesting activity in advance of mining are appropriate. Where the application only gives the examples of golden eagles, goshawks and canyon sweetvetch, it is assumed there will be checks for other cliff- and tree-dwelling species.

The application uses the term "sensitive species" in referring to canyon sweetvetch and golden eagles. This term is used by the Bureau of Land Management and Forest Service to refer to specific groups of uncommon species, often candidate threatened or endangered species. Canyon sweetvetch is actually on the list for these agencies, but golden eagles are not. The Applicant should consider using a different term.

Fifty mammal species are classified as potential residents of the proposed permit area. Of these, ten have been observed in the area. Seventeen species of high interest to the State are known, likely, or possible residents of the area.

According to the application, nearly all of the proposed permit area contains critical elk winter range. Most of the proposed permit area also has either high priority or critical deer winter range. Several other mammal species are known or suspected to inhabit the area, but the application does not show important habitat for these species.

The Division of Wildlife Resources considers the proposed surface facilities area to be marginal critical deer winter range. The area may not produce as much forage as adjacent undisturbed areas, but because of the terrain, water availability, and other factors, deer tend to congregate there. Correspondence from Wildlife Resources indicates the habitat would be of better quality if the area was properly reclaimed.

Fish surveys were conducted in Willow Creek in October 1994 and June 1995. Willow Creek is considered a class 4 fishery with low recreational fishing potential. The application says the portion of Willow Creek in the proposed mine area has poor spawning habitat and that this section of the stream is used more as a migration route for spawning fish. The only game species found in the electroshocking surveys was rainbow trout.

The Price River has a greater diversity of fish, but it is still considered a class 4 fishery. Most game fish found in a 1987 electroshocking study in Helper in 1987 were rainbow trout, but there were some cutthroat and brown trout,

Non-game fish species in Willow Creek are speckled dace and mountain sucker. Section 3.3.3.1 and Table 3.3-2 show results from 1994 and 1995 surveys including numbers of each species found. Wildlife Resources has collected nine species of fish from the Price River downstream of its confluence with Willow Creek.

Tables 3.3-3 through 3.3-9 have results of October 1994 macroinvertebrate sampling in Willow Creek. According to the application both the numbers of individuals and the numbers of taxa found at each sampling site were considered relatively low. Diversity values ranged from 1.15 to 1.66 at lower sites and 1.78 to 2.31 at upper sites. The application says values less than two are considered to indicate a possible stressed macroinvertebrate community.

TECHNICAL ANALYSIS

Last revised - April 22, 1996

Threatened and Endangered Species

The application describes the Applicant's and others' efforts to locate threatened, endangered, and candidate species. In 1989, the AMR program requested information about what species could be affected by their project in the area of the proposed mine, and they were given a list of six listed and three candidate species. The application says Cedar Creek Associates will request from the Fish and Wildlife Service an updated list of species potentially occurring the proposed permit area. This list has not been submitted.

The application says, based on current listings and information from Wildlife Resources, there is potential for thirteen candidate and five listed terrestrial wildlife species to occur in the proposed permit area. Of the five listed species, only two, the peregrine falcon and bald eagle, have much likelihood of being the area. No peregrine falcon nests or resident falcons are known to exist in the vicinity of the proposed permit area.

Bald eagle critical wintering areas exist a few miles southwest of the proposed permit area, but there are no known high priority concentration areas or critical roost trees actually in the area. The application says in Section 3.3.2.2 there is minimal potential for incidental use of the permit area by bald eagles and peregrines falcons. Wildlife Resources commented that there would be much greater potential for bald eagle roosting sites if Willow Creek supported a healthy riparian area with large cottonwood trees.

There is potential habitat for two candidate fish species in Willow Creek. These are the roundtail chub and the leatherside chub. The application says these species occurred historically in the Price River and its tributaries, but neither has been observed recently in Willow Creek. However, leatherside chub has been collected recently in the Price River upstream of the Willow Creek confluence.

Six other listed or candidate species could potentially occur in the Price River below the confluence with Willow Creek, but most of these live primarily in the Green River.

Threatened, endangered, and sensitive plant species are discussed in Section 3.2.3. In 1989 correspondence with AMR, the Fish and Wildlife Service mentioned two sensitive plant species that could occur in the area. These are canyon sweetvetch (*Hedysarum occidentale* var. *canone*) and Creutzfeldt catseye (*Cryptantha creutzfeldtii*). Neither species was found by AMR biologists.

The Applicant spent several days in August 1994 looking for canyon sweetvetch, but no plants were found in the project area. Two populations were found in the mouth of Cordingly Canyon about one-half mile south of the proposed permit area. The application says it is possible that additional plants occur in the proposed permit area but not in areas currently proposed for disturbance.

According to the *Utah Endangered, Threatened and Sensitive Plant Field Guide*, Creutzfeldt catseye grows in shadscale and mat atriplex communities on the Mancos Shale Formation between 5250 and 6495 feet elevation. Portions of the proposed disturbed area are

TECHNICAL ANALYSIS

barely within this elevational range; however, the area does not have the right kind of habitat for this species. Also, Bob Thompson of the U. S. Forest Service said he has seen no plants even in what he considers potential habitat in the Helper area. He has searched and found no plants west of Price.

The Division needs to request a list of potentially-affected species from the Fish and Wildlife Service. The Office of Surface Mining, Reclamation and Enforcement will need to consult with the Fish and Wildlife Service about any species of concern.

Findings:

This portion of the application is considered complete and accurate. However, the application says in Section 3.3.4.2 that Cedar Creek Associates will request from the Fish and Wildlife Service an updated listing of threatened, endangered, or candidate species potentially occurring within the proposed permit area. This list could not be found within the application and should be submitted if it is available.

Although the Applicant has committed to obtain a list of threatened, endangered, and candidate species from the Fish and Wildlife Service, the Division should do the same. Based on recent conversations with the Fish and Wildlife Service, the only list they may provide is of species that may occur within the county. It is believed the Applicant and the Division have considered all species with potential habitat in the area or that could be affected by the operation. The only effects the Division believes could occur are with threatened and endangered fish of the Upper Colorado River as discussed under "Fish and Wildlife Protection."

SOILS RESOURCE INFORMATION

Regulatory Reference: 30 CFR Sec. 783.21, 817.200(c); R645-301-411, -301-233.

Analysis:

Section 3.1, SOILS INFORMATION, discusses in detail the existing types and characteristics of soil, refuse and roof/floor materials. The information is collected and condensed from various published resources, Castle Gate Mine area operation records and current soil surveys. Adequate soil survey information is provided for those portions of the Willow Creek Mine permit area to be affected by surface operations.

Regional soils conservation information is taken from a Order-III soil survey, Soil Survey of Carbon Area, Utah, published by the Soil Conservation Service, United States Department of Agriculture (USDA-SCS) in June 1988. In addition to the published soil conservation data, soils information from previous sampling programs in the immediate Willow Creek and extended Castle Gate areas is extracted and reviewed from past mining activity. These include 1979 Soil Investigations (Price River Coal Co.), 1981 Soil Investigations for Crandall Canyon (Price River Coal Co.), 1988 Soil Sampling and Characterization (Blackhawk Coal Co.), 1989 Soil Sampling (Blackhawk Coal Co.), 1990 Soil Sampling (Castle Gate Coal Co.) and 1991 Soils Mapping (Castle Gate Coal Co.). The 1979

TECHNICAL ANALYSIS

Last revised - April 22, 1996

soil investigations include complete soil profile descriptions for 10 soil pits excavated in Crandall Canyon, Willow Creek and Castle Gate Preparation Plant areas. Finally, 1994, 1995 and 1996 supplemental site-specific soil investigations were conducted by CPMC for the proposed Willow Creek area and includes both disturbed and undisturbed soils.

The 1996, Order-I soil survey for the Willow Creek area supplies the critical information that is necessary for accurately assessing the site-specific soil resources available for salvage. Twelve additional soil pits were evaluated and soil samples collected according to the Division's "Guidelines for Management of Topsoil and Overburden." CPMC accepted the stipulation that the Mine Reclamation Plan (MRP) will be amended when the laboratory soil results from the 1996 Order-I soil survey are completed. Four of the examined soil pits are in undisturbed soils and eight are located in disturbed soils. The undisturbed soils correspond to USDA-SCS soil mapping Unit 107 Shupert-Winetti Complex. Detailed soil profile descriptions include site description, horizon/layer identification, depth, color, texture, structure and fragment/rock descriptions. The 1996 soil survey complies with the standards of the National Cooperative Soil Survey.

Two soil maps are presented for those areas potentially affected by the mining and reclamation activities. These include a Regional Soils Map (Map 3) and a Facilities Area Soils Map (Map 4). The Regional Soils Map shows the USDA-SCS Soil Survey mapping units for the entire mine permit area. This regional map reflects an Order-III soil survey. The Facilities Area Soils Map is a more detailed map which includes the site-specific soil sampling and surveys from the historical Castle Gate preparation plant and the proposed Willow Creek surface facilities.

A total of 6.7 acres of new ground will be impacted by construction in the Willow Creek Mine area with 4.7 acres in Soil Mapping Unit 107 Shupert-Winetti Complex, 1.5 acres in Unit 121 Travessilla-Rock Outcrop-Gerst Complex, and 0.5 acres in Unit 72 Pathead-Curecanti Family Association. According to the USDA-SCS Soil Survey, the Winetti soils correspond to the Loamy Bottom ecological or range site. Forage production of this soil is reported to be 1,000, 1,500 and 2000 pounds of air dry forage per acre for unfavorable, average and favorable precipitation years, respectively. Travessilla-Rock Outcrop soils corresponds to the Upland Very Steep Shallow Loam (Pinyon-Utah Juniper) woodland site. Potential production of wood products for this soil type are reported to be 1 to 2 cords of wood per acre with a potential forage production of 300, 500 and 700 pounds of air dry forage per acre for unfavorable, average and favorable precipitation years, respectively. Pathead soils occupy the undisturbed valley bottom areas along Willow Creek and correspond to the Mountain Valley Steep Loam (Salina Wildrye) range site. The potential forage production of this range site is reported as 1,000, 1,200 and 1,400 pounds of air dry forage per acre for unfavorable, average and favorable precipitation years, respectively.

Past prime farmland investigations for Price River Coal Co. and Castle Gate Coal Co. have concluded that soils within this area are excluded from consideration as important farmland. These conclusions are based upon the excessive amount of rock fragments, high

TECHNICAL ANALYSIS

erodibility and lack of reliable irrigation water within the Castle Gate mining permit area. Exhibit 5, SOILS INFORMATION, includes Prime Farmland Investigation correspondence, soil profile descriptions, soil field notes and soil laboratory data.

An evaluation of soil availability and suitability is made using the Divisions "Guidelines for Management of Topsoil and Overburden Materials." A comparison of the existing surficial soil materials is made for evaluation of reclamation suitability. In addition, the comparison includes the separate evaluations of coal refuse materials and mine development wastes. Since the implication is given that coal refuse materials and mine development waste may be used as substitute topsoil, CPMC has stated the following: "CPMC is not proposing to use coal or coal waste material as substitute topsoil material. Since the Willow Creek Mine area has been extensively disturbed in the past, there is coal waste material in many locations. This material has been covered in many locations by soil materials that are usable as growth medium. The growth medium has been demonstrated in this MRP to be adequate for reclamation. ^{See Section 3.1.2.4} In areas where coal waste material will be covered with growth medium, the ^{this quote} demonstrations made in this MRP show that reclamation can be achieved with less than four feet of cover. The final topsoil depth for reclamation will depend on the final salvaged volume of growth medium."

Selected overburden materials and disturbed soils may be used as supplement or substitute topsoil as referenced by R645-301-224, Substitute Topsoil, and R645-301-233, Topsoil Substitutes and Supplements. The Division recognizes that some contamination by coal materials of disturbed soils has occurred, is inevitable and does not present a reclamation hazard. The Willow Creek disturbed soils are an acceptable substitute topsoil as shown by their physical and chemical analyses, section 3.1.2.4 Soil Availability and Suitability. However, prior to approval of selected disturbed soils and overburden materials containing high amounts of coal, refuse, and/or waste rock, the Division requires the positive demonstration results of field-site trials and/or greenhouse tests (R645-301-233, Topsoil Substitutes and Supplements). In addition, the Division will not allow the use of coal, coal refuse materials and mine development waste as substitute topsoil or as potential growth media materials. Handling and disposal of coal refuse materials and mine development waste is regulated by 30 CFR 817.81, Coal Mine Wastes: General Requirements, and R645-301-528, Handling and Disposal of Coal, Overburden, Excess Spoil, and Coal Mine Waste.

Findings:

This portion of the permit application is considered complete and accurate with the stipulation that CPMC will amend the MRP, both section 3.1 SOILS INFORMATION and Exhibit 5 SOILS INFORMATION, with the chemical and physical analysis results from the 1996 Order-I soil survey.

TECHNICAL ANALYSIS

erodibility and lack of reliable irrigation water within the Castle Gate mining permit area. Exhibit 5, SOILS INFORMATION, includes Prime Farmland Investigation correspondence, soil profile descriptions, soil field notes and soil laboratory data.

An evaluation of soil availability and suitability is made using the Divisions "Guidelines for Management of Topsoil and Overburden Materials." A comparison of the existing surficial soil materials is made for evaluation of reclamation suitability. In addition, the comparison includes the separate evaluations of coal refuse materials and mine development wastes. Since the implication is given that coal refuse materials and mine development waste may be used as substitute topsoil, CPMC has stated the following: "CPMC is not proposing to use coal or coal waste material as substitute topsoil material. Since the Willow Creek Mine area has been extensively disturbed in the past, there is coal waste material in many locations. This material has been covered in many locations by soil materials that are usable as growth medium. The growth medium has been demonstrated in this MRP to be adequate for reclamation. In areas where coal waste material will be covered with growth medium, the demonstrations made in this MRP show that reclamation can be achieved with less than four feet of cover. The final topsoil depth for reclamation will depend on the final salvaged volume of growth medium."

Selected overburden materials and disturbed soils may be used as supplement or substitute topsoil as referenced by R645-301-224, Substitute Topsoil, and R645-301-233, Topsoil Substitutes and Supplements. The Division recognizes that some contamination by coal materials of disturbed soils has occurred, is inevitable and does not present a reclamation hazard. The Willow Creek disturbed soils are an acceptable substitute topsoil as shown by their physical and chemical analyses, section 3.1.2.4 Soil Availability and Suitability. However, prior to approval of selected disturbed soils and overburden materials containing high amounts of coal, refuse, and/or waste rock, the Division requires the positive demonstration results of field-site trials and/or greenhouse tests (R645-301-233, Topsoil Substitutes and Supplements). In addition, the Division will not allow the use of coal, coal refuse materials and mine development waste as substitute topsoil or as potential growth media materials. Handling and disposal of coal refuse materials and mine development waste is regulated by 30 CFR 817.81, Coal Mine Wastes: General Requirements, and R645-301-528, Handling and Disposal of Coal, Overburden, Excess Spoil, and Coal Mine Waste.

Findings:

This portion of the permit application is considered complete and accurate with the stipulation that CPMC will amend the MRP, both section 3.1 SOILS INFORMATION and Exhibit 5 SOILS INFORMATION, with the chemical and physical analysis results from the 1996 Order-I soil survey.

TECHNICAL ANALYSIS

Last revised - April 22, 1996

LAND-USE RESOURCE INFORMATION

Regulatory Reference: 30 CFR Sec. 783.22; R645-301-411.

Analysis:

Current Uses

Land uses of the proposed permit area are discussed in Section 3.4.2. Maps 9 and 10 show regional land use information and previous mining activity.

According to the application, the primary constraints relative to the condition and capability of lands within the proposed permit area and adjacent areas to support various land uses are the rugged terrain of the area, the lack of significant precipitation, and the lack of available water for irrigation or stock on a large portion of the area. The topography is composed primarily of high plateaus intersected by deep drainages with steep-walled canyons and high rocky cliffs.

Topography and resource constraints limit land uses on the plateaus to wildlife habitat, low intensity grazing, undeveloped recreation, and scattered timber production. These areas have limited assess because of the surrounding rugged terrain and harsh climatic conditions during part of the year. Soils on the plateaus are generally more developed than in the canyons, and higher precipitation and lower runoff because of the gentler terrain allow growth of some conifers.

Land use is even more limited in the narrow canyons and on ridge lines. In many areas, assess is extremely difficult except in the very bottoms of some canyons. Reasonably feasible land uses are wildlife habitat, low intensity grazing, and occasional undeveloped recreational use. The potential for alternative postmining land uses is limited by shallow, poorly-developed soils with low water holding capacity, and a lack of surface or ground water sources.

Extensive historical mining and related activities have occurred in the Price River and lower Willow Creek valleys in the permit area. Several other canyons have dirt roads but are otherwise nearly undisturbed. Existing and potential uses in the valley bottom areas include mining, transportation, wildlife habitat, grazing, and undeveloped recreation.

In Section 3.4.2.2, the application describes existing land uses within the proposed permit area. These are divided into the categories in R645-100-200 and further subdivided. The primary uses listed are industrial/commercial, undeveloped lands, and forestry. Under industrial/commercial, the application includes underground coal mining, scattered oil and gas production, transportation and utilities, and electrical power generation. Under undeveloped lands, the application includes low intensity grazing, fish and wildlife habitat, and dispersed recreation. The only forestry use shown is limited timber production. Grazing and wildlife habitat are the dominant uses for undeveloped lands, and mining is the main industrial use.

According to the application, small cattle and sheep grazing operations utilize some of the high plateau areas on a seasonal basis. Typical stocking rates are about eight acres per animal unit month. There will be no surface disturbances on areas used for grazing.

TECHNICAL ANALYSIS

A wide variety of fish and wildlife species use the area. In areas where more recent mining has occurred, such as the proposed surface facilities area, reclamation efforts over portions of the areas have resulted in effective vegetative reestablishment and general restoration of many of the premining habitat values.

The application says wildlife habitat is the primary land use for the proposed permit and adjacent areas. These areas are subject to low-intensity management for wildlife use by the responsible land management agencies.

Although the proposed permit area is used for grazing, information in the plan indicates there is very little grazing use, particularly in the west part of the area. The Division of Wildlife Resources indicates its wildlife section surveys big game populations in the area and works with landowners to issue landowner or depredation permits. The area provides habitat for numerous wildlife species, including deer, elk, bobcat, bear, cougar, passerine birds, red-tailed hawks, and golden eagles.

Most of the area consists of critical elk winter range and critical and high value deer winter range. These habitats are considered vital to maintenance of local elk and deer populations, and, to the degree possible, the Division of Wildlife Resources is concerned about managing these lands for wildlife habitat.

The postmining land use for the formerly permitted Willow Creek site, permit number INA/007/002, was light industrial. This use was terminated with Blackhawk Coal Company's decision to lease the property to Cyprus Western Coal Company.

The permit and adjacent areas are zoned by the Carbon County Planning Department as mining and grazing or critical environmental. The critical environmental designation is for areas above 7000 feet elevation and includes grazing, wildlife habitat, and some recreation activities. The application says the designated land use classifications and related zoning restrictions are consistent with both existing land uses and proposed mining activities.

The proposed permit area includes no public parks, components of either the National River or Trail Systems, renewable resource lands, areas designated unsuitable for mining, or other restricted use areas. It is assumed the application refers to the Wild and Scenic Rivers System where it says there are no components of the National River System in the proposed permit area.

It appears Section 3.4.2.4 is referring to unsuitability criteria when it says there are no renewable resource lands in the proposed permit area or adjacent areas. This needs to be clarified. The proposed permit area does contain renewable resource lands, but it probably does not contain areas that contribute significantly to the long-range productivity of water supply or of food or fiber products including aquifers and aquifer recharge areas. The significance criterion is used to designate areas unsuitable for coal mining and reclamation activities.

TECHNICAL ANALYSIS

Last revised - April 22, 1996

Previous Mining Activity

The earliest recorded mining activity in the area was the development of the Castle Gate No. 1 Mine in 1888. Extensive mine development and operations continued in the area through World War II, but mining gradually decreased until the last of the Castle Gate Mines closed in 1972.

Essentially all of the previous historical mining operations have been conventional room and pillar mines extracting coal reserves from one or more of the known coal seams in the Blackhawk Formation. Table 3.4-1 summarizes available information on previous historical mining operations, including mine names, seams mined, period of mining, and mining methods. Map 10 shows the extent of underground and known surface operations.

Section 5.3.1.2 indicates the mine surface facilities area and the Castle Gate Preparation Plant were in all probability undeveloped lands utilized for wildlife habitat prior to the introduction of mining. This statement is probably correct since it is assumed there was little wildlife management in the area before 1888. There may have been some limited grazing, however.

The information in the portion of the application describing previous mining activity fulfills regulatory requirements.

Findings:

This portion of the application is considered complete and accurate.

ALLUVIAL VALLEY FLOORS

Regulatory Reference: 30 CFR Sec. 785.19; R645-302-320.

Analysis:

The permit application refers to a decision document by the Division of Oil Gas and Mining (DOG M) in 1982. At that time, a multi-disciplinary team studied the vicinity of the Castle Gate Preparation Plant. The team determined that the site was in an alluvial valley, but that there were no effects on the soils or water quality by the adjacent mining activity. This document is reprinted in Exhibit 10.

The Price River is impacted by the power plant; the Dept of Transportation road salt storage facility; highway activity and abandoned coal refuse piles along the river banks. Both the Willow Creek Mine site and the Castle Gate Preparation Plant have remained idle for most of the last decade.

Findings:

The plan is considered technically adequate with regard to the Alluvial Valley discussion.

GEOLOGIC RESOURCE INFORMATION

Regulatory Reference: 30 CFR Sec. 784.22; R645-301-623, -301-724.

Analysis:

Descriptions of the stratigraphy and lithology of strata from the Mancos Shale up to the North Horn Formation are in Section 3.6.1.3. Section 3.6.2.2 contains more detailed descriptions of strata from the Aberdeen Sandstone, the strata/aquifer immediately below the lowest coal seam to be mined, up through the coal bearing strata of the Blackhawk Formation. Characteristics of the overburden, interburden, and coal are described in Section 3.6.3. Regional hydrostratigraphy, including the Flagstaff Limestone, is discussed in Section 3.7.2.1. Structural geology is discussed in Section 3.6.2.1. Alluvial/colluvial, perched, stored mine water, and regional aquifer systems occur in the permit and adjacent areas. These systems and hydraulic characteristics based on aquifer testing are identified and discussed in Section 3.7.2.2. Ground water occurrence is characterized in Section 3.7.2.3. Ground water movement is generally limited by low transmissivities and lack of secondary permeability, and recharge is limited due to low precipitation rates, brief high intensity runoff, and steep outcrop exposures. Ground water occurrences in bore holes and in the mines are discussed in Section 3.6.2.3.

Most of the 179 bore holes drilled on or around the permit area since the beginning of the century and prior to 1994 were cored from near-surface to total depth. Detailed logs from these bore holes were used to construct the cross sections (Maps 13A-13D) and isopachs (Maps 14A-14E). However data from the historical drilling and exploratory programs varied considerably in completeness and uniformity. There are few geophysical logs, incomplete cutting logs, generalized core descriptions, very few coal analyses, and little or no information on material physical characteristics.

The primary purpose of the 1994-1995 drilling program was completion of ground water monitoring wells. Ground water was intercepted in each of these bore holes. In addition, a full data collection and analysis program provided valuable information to address existing data deficiencies. The 1994 program produced eleven coal and forty roof and floor spot core samples with complete core descriptions and photographs plus:

- Collection and description of cuttings during rotary drilling
- Documentation of penetration rates using a geolograph and notation of drilling conditions
- Notation of any water or gas encountered in the drillholes and measurement of discharge flow rates
- Geophysical logging of drillholes
- Laboratory analysis of coal core samples
- Suitability analysis of roof and floor samples for each coal seam.

Exhibit 9 contains well completion reports, cutting logs with information on ground water occurrences, and core logs for W94-5-1 (B51), W94-12-1 (B121), and W94-33-1(B331); well completion reports and core logs for BN251, BN301; analysis reports for the roof and floor cores from W94-5-1, W94-12-1, and W94-33-1 plus W94-31-1 (BW311); and coal analysis reports for

TECHNICAL ANALYSIS

Last revised - April 22, 1996

BN251, BN301, W94-5-1 and W94-33-1. There is no comparable information for, drilled in 1995.

No potentiometric surface map has been made: Cyprus asserts that no consistent, uniform, stable potentiometric surface exists in the permit area because of extensive underground disturbance from historic mining, deeply eroded canyons, discontinuous nature of perched aquifers, relatively low permeability of the rock units overlying the regional aquifer, and slow recharge/discharge capabilities. Hydrographs of available water level elevations for wells B51, B121, BW311, B331, B331A, BN251, BN301, and BW361 (Figure 3.7-1) show short term stability of the potentiometric surface(s), with little seasonal variation. These potentiometric data indicate that Willow Creek Canyon is the principal influence on the potentiometric surface(s) within the proposed permit area. On the Geologic Cross Sections (Maps 13A through 13D), ground water intercepts are indicated in only two bore holes.

In addition to the water monitoring wells, fifteen shallow boreholes were drilled in 1994 for geotechnical investigation of foundation conditions in the alluvial/colluvial aquifers along Willow Creek and the Price River. Locations of are shown on Map 16. Bore hole logs are in Exhibit 11. Bore holes TH-02 and TH-17 were completed as piezometers. An additional four roof and floor samples for smaller non-minable seams were obtained from a geotechnical hole drilled near the proposed portal area, for a total of 44 roof and floor rock samples collected in 1994.

Other information on chemical and physical properties of the coals and adjacent strata comes from a variety of sources dating back to 1979. Chemical characteristics of coal and other materials to be disturbed in the Willow Creek Mine are discussed in Section 3.6.3.2. Cyprus evaluations of all available chemical analyses indicate that the sampled materials are not potentially acid- or toxic-forming.

Of the forty core samples of roof and floor rock collected in 1994, three had acid-base potentials below -5 tons CaCO_3 /1,000 tons of material, the minimum acceptable under the Division's Guidelines for the Management of Topsoil and Overburden, but the average value was 45.91.

Although the average SAR value from the 44 rock and roof core samples was 14.14, numerous samples of soil, mine waste, and coal refuse already at the surface (Soils - Section 3.1.2.3) indicate there is no significant potential for sodium toxicity relative to revegetation.

Boron levels from the forty rock and roof core samples averaged 1.29 mg/kg but two samples exceeded 5 mg/kg and are therefore "unacceptable" under the UDOGM guidelines. Selenium levels from the forty rock and roof core samples averaged 0.04 mg/kg but three samples exceeded 0.1 mg/kg, the UDOGM guideline's suitability limit. The manner in which waste materials are typically handled during mining will most likely result in the smaller volumes of unacceptable materials being mixed with larger volumes of acceptable materials and the resulting buffering or dilution will probably leave material that falls within acceptable values. On page 3.6-27 is a statement that where mine waste rock or coal refuse materials are placed in

TECHNICAL ANALYSIS

surface stockpiles, testing these materials for suitability may be appropriate as part of the reclamation program.

Coal extraction thickness will range from 5 to 13 feet and projected maximum subsidence is therefore 3.5 to 9.1 feet, based on the assumption that the surface will subside up to 70% of the thickness of the extracted coal. Nature, depth, and thickness of the coal seams and overlying strata are described in Section 3.6.2 and physical properties of the coal and roof and floor materials are described in Section 3.6.3. Overburden will be greater than 700 feet in most areas mined and massive sandstone units lie between the coal seams and the surface, so subsidence can be expected to be less than the assumed maximum.

Findings:

The permit application includes geologic information in sufficient detail to assist in determining all potentially acid- or toxic-forming strata down to and including the stratum immediately below the coal seam to be mined; determining whether reclamation as required by R645-301 and R645-302 can be accomplished; and preparing the subsidence control plan.

The application includes geologic information in sufficient detail to assist in determining the probable hydrologic consequences of the operation upon the quality and quantity of surface and ground water in the permit and adjacent areas, including the extent to which surface and ground water monitoring is necessary; and determining whether reclamation as required by the R645 Rules can be accomplished and whether the proposed operation has been designed to prevent material damage to the hydrologic balance outside the permit area.

The Division has not determined it to be necessary to require the collection, analysis, and description of additional geologic information to protect the hydrologic balance, to minimize or prevent subsidence, or to meet the performance standards.

Cyprus has not requested that the Division waive in whole or in part the requirements of the borehole information or analysis required of this section.

HYDROLOGIC RESOURCE INFORMATION

Regulatory Reference: 30 CFR Sec. 701.5, 784.14; R645-100-200, -301-720.

Analysis:

Sampling and Analysis

Cyprus's Baseline Hydrologic Monitoring Plan for the Willow Creek Mine is Exhibit 12 of the PAP. Collection of baseline data began in June 1994.

Sampling and analysis for environmental resource information is covered in Exhibit 12 and Sections 3.7.2.4 and 3.7.3.4. These sections are titled Ground Water Quality and Surface

TECHNICAL ANALYSIS

Last revised - April 22, 1996

Water Quality, respectively. Both sections discuss the type of data that is available from previous sampling projects and the sampling that was undertaken as part of this permitting project. All monitoring locations are shown on Figure 2 of Appendix 12.

Field measure including surface water flow, groundwater depth, temperature, pH, electrical conductivity, and dissolved oxygen will be collected according to methods described in section 3.4 of Exhibit 12. Flow will be measured according to one of several methods, including using weirs and flow meter measurements as described in U.S. Geological Survey, Water Supply Paper 2175.

Over the preparation and mining periods of the mine water samples for chemical analysis will be taken from springs, streams and wells as described in Section 3.5 of Appendix 12. Dip samples will be periodically taken from springs and streams for chemical analysis. Three monitoring wells have been installed to depths of 400 feet, 1000 feet, and 1800 feet which had chemical samples taken when they are drilled. Because of the great depth and associated costs, these wells will only be used to define the water surface elevation after their construction. Sample water taken for analysis of dissolved cations and trace elements will be filtered and preserved in the field. Duplicate samples will be taken and analyzed in the laboratory and field equipment will be decontaminated as part of the quality control/quality assurance plan.

A comprehensive seep and spring survey resulted in the establishment of 11 spring/seep monitoring locations. The occurrence of ground water and hydraulic characteristics of the aquifers are to be determined through testing and monitoring of 8 wells. Flow and quality of all springs and seeps and ground water wells will be monitored. Monitoring stations are listed in Table 3.7-1 and their locations are shown on the Regional Hydrology Map (Map 15). During 1994 and early 1995 four additional springs/seeps were added, and during 1995 two additional groundwater monitoring wells were installed in conjunction with supplemental exploration drilling.

Information characterizing the ground water flow regime and hydraulic parameters of the regional aquifer comes from wells MC-205, MC-206, and MC-207 located in the western coal reserves area and wells B51, B331, B331A, and B121 recently installed in the Willow Creek Mine area as part of the Baseline Hydrologic Monitoring Plan. The locations of wells B51, B331, B331A, and B121 are shown on the Regional Hydrology Map (Map 15).

The purpose of the plan is to collect and evaluate baseline hydrologic data specific to the Willow Creek Mine. Data collected under the plan will be used to characterize existing ground water flows, water quality conditions, and any seasonal variations in these characteristics, and to evaluate potential impacts to these resources from mining and reclamation activities. Additionally, baseline hydrologic data will be compared to regional data and data from adjacent areas to evaluate spatial and temporal relationships.

Applicable ground water quality standards are summarized in Table 3.7-5 for comparison to water quality data from the site. Ground water monitoring locations where average concentrations of an analyte exceed a water quality standard for at least one use category are presented in Table 3.7-6.

TECHNICAL ANALYSIS

Water quality parameters include field measurements for pH, specific conductance, and temperature, and laboratory measurements for general water characteristics such as total dissolved solids, nutrients, major ions, and trace metals. Available water quality information is summarized in Table 3.7-4. Ground water quality data are presented in Exhibit 10, Hydrologic Information. Available ground water quality data for wells B51, B121, B331, and B331A are presented in Figure 3.7-3.

Ground water quality samples will be collected, labeled and transported to a qualified analytical laboratory for analyses. Proper sample collection, preservation, handling, and storage methods will be utilized at all times to preserve the integrity of the samples and ensure validity of analysis results. Water quality samples will be analyzed for the specific parameters listed on Table 3.7-9 and Table 3A of Exhibit 12, and sampling frequency is listed in Table 2 of Exhibit 12. All water monitoring analysis results will be recorded, reviewed to identify potential problems or trends, and filed at the mine so as to be available for future inspection and review. In addition, Cyprus will file copies of both field data and laboratory analysis sheets on a quarterly basis with the UDOGM. At the end of each annual water year, Cyprus will tabulate all water monitoring data for the year, review the data with respect to changes in groundwater hydrology systems, and provide a summary Annual Hydrology Report in compliance with the UDOGM schedule.

Approximately one year of baseline hydrologic data for most stations were available at the time of the draft technical adequacy review of this permit application. Monitoring to establish baseline conditions will continue with updated analyses and discussions submitted to UDOGM before permit approval.

Baseline Information -- Ground Water

A discussion of regional ground water conditions is provided in Section 3.7. Ground water resources are found in shallow alluvial/colluvial valley-fill deposits along drainages; in perched, thin, laterally discontinuous strata in the Blackhawk, Price River, North Horn, and Flagstaff Formations; ground water which has accumulated over time in extensive existing underground mine workings; and in a regional Blackhawk-Star Point-Mancos aquifer.

Ground water rights are held on numerous small springs or seeps, wells in alluvium/colluvium in drainages, shallow wells that intercept perched drainages, and ground water that is discharged into or stored in mines. Water rights are marked on Map 17 and summarized in Exhibit 10. Price River Water Improvement District's pending municipal water rights in Sec's. 23 and 24, T. 12 S., R. 10 E. are marked on Map 17; but similar pending municipal water in nearby areas are not shown on that map. These municipal rights are for water extracted from the Cockrell methane extraction wells. Quality of the water extracted from these wells is poor and it is unlikely this water will ever be appropriated for municipal use. Large volume ground water use in the region is for municipal water, power generation, and irrigation. This water is primarily from the alluvial/colluvial aquifer along the Price River. However, there are several wells in Emma Park, the flatter area north of the permit area, that have rights to large volumes of ground water. These wells probably produce water from the Flagstaff and North Horn Formations. Small volume use from all sources is primarily for stock watering.

TECHNICAL ANALYSIS

Last revised - April 22, 1996

No potentiometric surface map has been made. Cyprus asserts that no consistent, uniform, stable potentiometric surface exists in the permit area because of the extensive underground disturbance from historic mining, the discontinuous nature of the perched aquifers, the relatively low permeability of the rock units overlying the regional aquifer, and slow recharge/discharge capabilities. Because of these factors Cyprus has requested an exemption from any requirement to create a potentiometric surface map and cross sections depicting regional aquifer water levels across the permit area. However, hydrographs of available water level elevations for wells B51, B331, B331A, B121, BN205, and BN301 are shown on Figure 3.7-1 show short term stability of the potentiometric surface(s), with little seasonal variation.

Locations of fifteen shallow boreholes, drilled in 1994 for geotechnical investigation of foundation conditions in the alluvial/colluvial aquifers along Willow Creek and the Price River, are shown on Map 16 and Figure 2 of Exhibit 11.. Bore hole logs are in Exhibit 11. Bore holes TH-02 and TH-17 were completed as piezometers..

Wells completed in the alluvial/colluvial deposits along the Price River can reportedly yield up to 500 gpm at a sustained rate. Ground water movement in the perched and regional aquifers is limited by low transmissivities, lack of secondary permeability, and limited recharge due to arid conditions and limited outcrop exposure of potential recharge zones.

Flows and water levels for seeps, springs, and wells that are monitored by Cyprus for baseline information are summarized in Table 3.7-4 of the PAP. Field data sheets are in Exhibit 10. Locations of seeps, springs, and wells are on Map 15. Spring B321 is identified as "Willow Creek Spring" in Table 3.7-4 and on Map 15 but as "Sulphur Spring" on Map 17 (and perhaps other places in the PAP) , which is confusing, not clear and concise.

Area ground water is typically a weak calcium sulfate or sodium sulfate type. Exhibit 10 contains water analysis reports for September 1994 through March 1995 for the four wells drilled in 1994 and for other ground and surface water sampling sites being monitored by Cyprus. Exhibit 10 also contains summaries of analysis results, some dating back to 1977, for ground water samples collected by PRCC and CGCC from mines, springs and seeps, and various bore holes. Water quality data are summarized in Table 3.7-4.

In ground water samples, field measured pH values range from 7.6 to 9.3 indicating neutral to moderately alkaline conditions typical of the arid western United States.

Electrical conductivity (EC) ranges from 1,200 to 3,350 μ mhos/cm. Total Dissolved Solids (TDS) values range from 1,270 to 2,450 mg/L, and elevated TDS values correlate directly with high EC values. Cyprus relates the observed variability in TDS and EC values to the highly variable lithologic composition of area bedrock. Lower TDS and EC are generally associated with alluvial/colluvial and perched ground water sources and more permeable sandstones with limited cementation and few soluble components. Higher TDS and EC are associated with relatively deep regional sources, permeable marine sediments, or more highly consolidated marine shales and fine-grained siltstones: low permeabilities result in longer residence times, and greater concentrations of salts and other soluble materials result in greater potential for dissolution and salt loading.

TECHNICAL ANALYSIS

Concentrations of dissolved and total iron range from less than 0.01 to 0.39 and 0.17 to 15.7 mg/L, respectively. Cements that bind the sedimentary grains in many lithologic units in this area commonly include iron compounds, so it is reasonably assumed that the observed iron concentrations are related to such natural sources.

Concentrations of magnesium range from 19 to 140 mg/L, which are consistent with natural concentrations in sedimentary sequences in the region.

Oil and grease concentrations for the four 1994 wells range from 1 to 6 mg/L. These values are at or slightly above the detection limit and may indicate residue from the construction and installation of the monitoring wells. However, during the 1992 - 1993 evaluation of the coal reserves, two to three inch thick skims of natural crude oil were found floating on ponded water in both the C Seam works and in the East Mains of the Kenilworth Seam. A sample was collected but no analyses were completed. The oil is apparently seeping up out of the thin interbedded sandstones, siltstones, and mudstones which form the immediate floor in these areas. Oil has been reported to drip from roof strata at other sites in both the K and A Seams, particularly in the eastern extent of the mining. Oil seeps have also been reported from the Castle Gate property west of the Price River. The oil and grease detected in the four wells may therefore represent natural crude oil from the Blackhawk Formation.

There is some potential that ground water and surface water quality in the permit and adjacent areas may be affected by a coalbed methane degassification project located north of the lease and adjacent areas. The Cockrell Oil Company is extracting water from approximately 25 coalbed methane wells in the Blackhawk Formation to desorb methane from the coal matrix. Water removed from the Blackhawk Formation comes primarily from the Aberdeen sandstone. Following extraction from the wells, the methane is removed and the remaining water stream is treated by reverse osmosis and evaporation to reduce TDS and volume, respectively. The remaining water, "concentrate" in Cockrell's terminology, is injected into the Price River Formation. Injected water may increase the discharge rate from springs and seeps down gradient of the degassification project, quality of spring and seep discharges may be degraded by the injected concentrate, and quality of water in the Price River may eventually be affected. Additionally, concentrate injected into the Price River formation may encroach on the permit area and the resulting degradation of ground water quality due to the coalbed methane project could be misinterpreted as being related to Willow Creek mining activities.

Baseline Information -- Surface Water

Surface-water baseline information is found in Section 3.7.3. Section 3.7.3.1 is the description of the in which surface water exist in the permit and surrounding areas. Section 3.7.3.2 is the list and description of the surface water bodies in the permit area including ponds, lakes, perennial streams, etc. Section 3.7.3.3 talks about the quantities and occurrences of surface water and Part 3.7.3.4 is the surface water-quality information. Figures and tables within these two part reveal the data from monitoring in this permitting project and previous water monitoring projects. Water rights information is presented in Section 3.7.3.5, Exhibit 10 and on Map 17. Section 3.7.3.6 describes how surface water and ground water interact.

The surface water environment is formed by an arid to semi-arid climate, rugged topography, predominately sedimentary rock, and soils formed from sedimentary rocks. Surface

TECHNICAL ANALYSIS

Last revised - April 22, 1996

water flow usually results from snowmelt and from thunderstorm runoff. Thunderstorm can be very intense over short periods which, combined with the rugged, rocky topography, can result in very large increases in surface water flows. The Price River and Willow Creek are the major, perennial drainages in the permit area. Other perennial drainages within a 2 mile radius of the permit area are Sulphur Canyon, Mathis Canyon, Deep/Buck Canyon, the main stem of Antone Creek. There are several ephemeral drainages in the two mile radius of the permit area. Drainage specific information for many of the permit area drainages is located in Table 3.7-8, Surface Drainage - Watershed Characteristics found on page 3.7-31.

Many data are available on stream flows in the Price Rive and Willow Creek, but there is very little historical data available for the smaller drainages in the permit area. Available surface water flow records are represented in Figures 3.7-4A through 3.7-4I in graphical form.

Several small man-made sedimentation ponds associated with coal mining activities and several stock watering ponds are the only stationary surface water bodies in the permit area. There are no lakes or reservoir. The stock watering ponds are frequently associate with springs.

General water quality information is found in Section 3.7.3.4, Surface Water Quality. Data show that pH is natural to basic, pervious activities have contributed to increase phenols in some samples, natural sulfur springs result in some water having elevated sulfate levels, TSS tends to be elevated during storm runoff, and elevated iron has been found due to natural sources. Table 3.7-10 shows the type of samples taken in multiple sampling projects and Table 3.7-10 is a summary of sampling. Some data show that water quality standards have been exceed prior to mining by CPMC. These data, located in Table 3.7-12, show that nitrates have exceeded the standard of 0.02 mg/L in Willow Creek, Price River and Mathis Canyon. Phosphate have exceeded the 0.05 mg/L standard in Willow Creek, Price River, and Sulphur Canyon. Copper has exceeded the standard of 0.01 mg/L in Willow Creek, and Crandall Canyon. Phenols have exceeded a 0.01 mg/L standard in Willow Creek, Price River and Sulphur Canyon. Finally, Crandall Canyon sampling has exceeded the zinc standard of 0.05 mg/L. All water quality standards are located in Table 3.7-5. Figures 3.7-6A through 3.7-9I where included in the permit application to show the relationship between stream flow and the concentration of an assortment of water quality constituents. A statement on page 3.7-52 says that "Specific conductivity, total dissolved solids (TDS), and sulfate concentrations all appear to decrease during high-flow conditions and increase during low-flow conditions." They go on to say, "Iron concentrations appear to be flow independent. Concentrations tend to increase with higher flows and decrease under low flow conditions." This statement is inaccurate because, the data show that there is a relationship between flow and iron concentration.

Beneficial uses of water in the permit area are domestic water supply, industrial, and limited agricultural. Price City water treatment plant is located on the Price River just above the permit area, but some of the tributary are within the permit area. Price River water is used in limited irrigation project down stream. Surface water owner ship information is provided in Exhibit 10 and shown on Map 17.

Baseline Cumulative Impact Area Information

A CHIA (Cumulative Hydrologic Impacts Assessment) has been done for the proposed Willow Creek Mine. Hydrologic and geologic information necessary to assess the probable

TECHNICAL ANALYSIS

cumulative hydrologic impacts of the proposed operation and all anticipated mining on surface- and ground-water systems in the cumulative impact area has been obtained from appropriate federal or state agencies and provided by the Applicant. No adverse impacts on surface- and ground-water systems are anticipated from the proposed operations.

Survey of Renewable Resource Lands

Renewable Resource lands information is included in Section 3.7.5. Part 3.7.5.1 on page 3.7-91 identifies the occurrence of aquifers and recharge areas within the permit and adjacent areas. Part 3.7.5.2 on page 3.7-92 defines the potential for disruption of aquifers or changes in recharge due to subsidence. The permit application says, "the area does not provide significant recharge to any regional ground water aquifers and is relatively more important as a watershed area for area surface drainages. There has been no significant historical nor any recent agricultural activity within the permit or adjacent areas and the USDA-SCS has issued a negative determination for prime farmlands for the area as discussed and documented in Section 3.1.3, Prime Farmlands."

Alluvial Valley Floors

Section 3.7.6 on page 3.7-92 addresses the potential impacts to alluvial valley floors. This section cites a study undertaken by the Division in 1982 as part of permitting the Castle Gate mine which found that mining in the study area would not affect the alluvial valley floors that are present. This study is presented in Exhibit 10.

Modeling

Cyprus' plans and methodology for hydrologic modeling are stated in Section 3.7.8 on page 3.7-94. Cyprus will model runoff calculations, Part 3.7.8.1, and precipitation events used for runoff calculations, Part 3.7.8.2. Calculations for these models are located in Exhibit 13. Cyprus does not plan to create any ground water models.

Modeling techniques, interpolation, or statistical techniques have not been used as part of the ground water baseline information in the proposed permit.

Alternative Water Source Information

Alternative water source information is located in Section 3.7.9 beginning on page 3.7.96. Part 3.7.9.1 covers the potential impacts on surface and ground water sources, and Part 3.7.9.2 provides information on alternate water sources.

Probable Hydrologic Consequences

To accurately characterize the existing surface and ground water environments and to assess the probable hydrologic consequences of the planned mining and related activities, Cyprus reviewed and evaluated all available information on baseline hydrologic conditions as presented and described in Section 3.7 of the PAP. Cyprus then considered potential hydrologic impacts that could occur as a result of the planned mining and related activities based on the operation and reclamation plans presented in Sections 4.0 and 5.0. Both direct and indirect mining related impacts were identified and evaluated. The effectiveness of operational protection and control

TECHNICAL ANALYSIS

Last revised - April 22, 1996

measures and reclamation activities in mitigating potential impacts were considered. The following summarizes the probable hydrologic consequences of the planned Willow Creek mining and related activities as determined by Cyprus.

Ground Water Consequences

Cyprus' planned mining, processing, and related activities have the potential to cause localized and temporary impacts to ground water. These probable ground water hydrologic consequences include:

- Alterations of ground water flow patterns
- Drainage of seeps/springs
- Alterations of recharge/storage/discharge relationships
- Increases in concentrations of TDS and certain individual chemical constituents

Mining related probable hydrologic consequences for ground water resources in the Willow Creek permit area will be limited by the lack of significant ground water recharge, a thick sequence of low permeability bedrock between the coal seams to be mined and the ground surface, the general lack of significant regional ground water movement due the absence of well defined regional aquifers, and limited beneficial ground water use in the permit and adjacent areas.

Alterations to Ground Water Flow Patterns - Historic coal mining in the area has produced extensive underground mine workings. In areas where those workings intercept ground water systems or connect to them through fractures the abandoned mine workings serve as sinks in the ground water systems. Seepage into the mines is extremely slow but inflows have gradually accumulated in significant quantities in the underground workings. In the western coal reserves area, mine inflows appear to be greatest where extensive retreat mining has produced substantial subsidence. However, regardless of subsidence conditions or mining method, the overall inflow rate is low, ranging from less than 5 gpm up to a maximum of about 35 gpm. Mine inflow monitoring by Price River Coal Company indicated inflow rates of 2.9, 12, 30, and 30 gpm for the Aberdeen, Utah Fuels No. 1, Royal, and Kenilworth mines, respectively. Similar monitoring by Castle Gate Coal Company for the No. 3 and No. 5 Mines resulted in measured inflow rates of 33 gpm (0.04 gpm/acre) and 3.5 gpm (0.015 gpm/acre).

The total volume of ground water storage in the old mine workings in the eastern coal reserves is unknown, although it is probably substantial. Water accumulates predominantly in the down-dip workings. Most abandoned mine workings in the area have been sealed, and there are few known instances of mine water being discharged from old workings. Generally, the volume of ground water stored in old mine workings increases until the local ground water system establishes equilibrium between inflow and outflow as recharge into the aquifer or as discharge to the surface.

Ground water flow patterns will be altered further as the Willow Creek Mine opens new underground workings. As the new mine workings are dewatered the potentiometric surface in the immediate vicinity will be lowered and a cone of depression created, and additional ground water will be deflected toward the mine workings. Mine inflow rates in the eastern coal reserves are expected to be similar to those observed in the western coal reserves. Based on an average

TECHNICAL ANALYSIS

recharge rate to ground water of 0.44 inches per year and an area of approximately 9 square miles of existing mine workings, the amount of ground water intercepted annually by the mine is estimated to be 131 gpm (0.3 cfs). At the end of operations for the Willow Creek Mine, assuming that the area mined is 19.8 square miles (i.e., old and new mine workings extending beneath approximately 90% of the permit area), the amount of ground water intercepted annually by the mine is estimated to be 183 gpm (0.4 cfs). If average yield per acre of 0.023 gpm per acre is used, the volume is 470 acre-feet per year or approximately 290 gpm. This amount of water is stated as being relatively small compared to the overall flow of the regional ground water system, although the criteria used to make such a determination are not given in the PAP.

Depression of the potentiometric surface near the mine is expected to be both minor and localized due to the relatively low permeability of the stratigraphic units. Additionally, ground water in overlying perched aquifers may leak downward along subsidence fractures, resulting in partial or full drainage of the perched aquifers that may in turn affect the discharge of springs and seeps. However, impacts to perched aquifers and associated springs and seeps are not expected to be significant because the perched aquifers are very limited in areal extent, areas potentially affected by subsidence represent a relatively small portion of the permit area, and beneficial use from perched systems within areas to be subsided is limited to a single spring (B41) in the eastern portion of the permit area.

After operations at the Willow Creek Mine cease, the underground workings will gradually fill with water and a stable potentiometric surface will be reestablished, which should be approximately the same as the potentiometric surface that existed prior to mining. Changes in the potentiometric surface are not expected to be significant because the overall hydrologic balance within the ground water basin will not be affected. Reductions in quantity and availability of ground water are expected to be minor, limited in areal extent, and temporary in nature.

Reductions in ground water flow are not expected to adversely impact ground water use in adjacent areas, such as the municipal water wells of the Price River Water Improvement District in Sec's. 23 and 24, T. 12 S., R. 10 E. because strata that yield water in these areas are hydraulically isolated from the coal seams by a significant thickness of low permeability bedrock and subsidence is not projected to occur near enough to affect these areas.

Drainage of Seeps and Springs - Perched ground water above the Willow Creek mine may drain or seep downward through subsidence fractures. Perched aquifers may be partially or fully dewatered and springs and seeps that discharge from stratigraphic units that contain perched ground water may be affected. Impacts due to subsidence are not expected to be significant because the perched aquifers are limited in areal extent and potential subsidence areas represent a relatively small portion of the total permit area. Subsidence fractures are expected to gradually fill by sloughing, plastic flow, and mineral deposition. Only one identified ground water source, Jack Spring (B41), is within an area where subsidence is projected. Cyprus will attempt to minimize subsidence while maximizing recovery of available coal resources by the use of longwall mining methods, maintenance of barrier pillars, limiting extraction in critical areas, and proper mining and roof control design and operations practices. Effective control of subsidence will limit fracturing of overlying strata and the consequent potential for drainage through subsidence fractures.

TECHNICAL ANALYSIS

Last revised - April 22, 1996

Drainage of perched ground water aquifers is not anticipated to affect the regional potentiometric surface because the perched systems are isolated from the regional aquifer by low permeability interbedded siltstones and shales. Storage volumes in the isolated perched aquifers are minor compared to the regional system.

If discharge from seeps or springs is documented as having decreased below baseline conditions as a result of mining related activities, Cyprus has committed to mitigate those impacts through augmentation of effected water rights, monetary compensation, development of alternative watering facilities such as guzzlers, or other appropriate mitigation measures.

Alterations to Recharge/Storage/Discharge Relationships - Cyprus's planned mining, processing, and related activities are not expected to have any significant long-term effect on recharge, storage, or discharge relationships. Recharge occurs primarily along outcrops by infiltration of direct precipitation and runoff. Cyprus's operations are limited in areal extent and are not located within any major recharge area. Drainage of ground water presently stored in abandoned mine workings and the surrounding rock will be localized and temporary. Upon closure of the Willow Creek Mine, ground water will again accumulate in the mine workings and ground water storage relationships will be reestablished. There will be localized alterations to ground water flow, and discharges down gradient of the mine may be temporarily reduced until the underground mine workings fill. The quantity of ground water discharge which will be effected is a relatively small percentage of the total volume within the ground water basin, but neither volume has been quantified in the PAP.

Increases in Chemical Constituents - Ground water in both the Willow Creek permit and adjacent areas is a weak calcium-sulfate or sodium-sulfate chemical type. As ground water encounters freshly exposed materials in the mine, oxidation and weathering will cause changes in ground water chemistry including increases in TDS and concentrations of individual chemical constituents. Due to the limited volume of ground water drainage relative to total flows within the ground water basin, minor changes in ground water chemistry and in specific constituents are not expected to significantly effect overall ground water quality or use. Over time these increases will stabilize and then decrease as available soluble chemical constituents are depleted and concentrations in mine water and exposed rock reach equilibrium. Gradual flooding of abandoned mine workings will also have a beneficial water quality effect by displacing oxygen and reducing the oxidation potential.

Based on available information, Cyprus does not anticipate that the existing coalbed methane degassification project located down gradient of the planned mine workings and outside of the permit area will have any effect on ground water resources within the permit area. The water used to force methane from the recovery wells is of low quality and is reinjected into the Price River Formation following gas recovery. In the unlikely event that ground water impacts extend further than projected by the environmental analysis for the project, water quality impacts could be locally significant within the permit area.

Page 4.7-25 state that ground water resources are limited to: "1) shallow alluvial/colluvial valley fill deposits in area drainages; 2) perched ground water occurring in thin laterally discontinuous sedimentary units associated with the Price River, North Horn, and Flagstaff Formations; 3) ground water which has accumulated over time in extensive existing underground mine workings; and 4) a regional water table aquifer occurring in the deeper portions of the

TECHNICAL ANALYSIS

Blackhawk Formation and extending into the underlying Star Point and Mancos Formations." Groundwater movement is limited by low transmissivities and other factors. These limitations should result in relatively low mine inflow rates. Groundwater quality is reflective of the different lithologic composition of the area bedrock units. Baseline data shows that "area ground water is typically a weak calcium sulfate or sodium sulfate type with neutral to moderately alkaline pH, relatively high TDS concentrations and slightly elevated levels of iron." Some perched groundwater supplies are used for stock watering, but surface water is more accessible, and, therefore, more often used.

Surface Water Consequences

The Probable Hydrologic Consequences Determination can be found in Section 4.7.4. The baseline conditions are summarized in Section 4.7.4.1. Potential adverse impacts are discussed in Section 4.7.4.2. Presence of acid- and toxic-forming materials is discussed in Section 4.7.4.3. Sediment yield; acidity, total suspended and dissolve solids and individual chemical constituents; changes in stream flow; and ground- and surface-water availability are addressed in Section 4.7.4.2.

There are several perennial drainages located within or adjacent to the permit area listed on page 4.7-25. They are: "1) Price River, the principal drainage in this area; 2) Sulphur Canyon, which is tributary to the Price River near the northern edge of the permit boundary; 3) Willow Creek, which is tributary to the Price River and drains the majority of the permit area; and 4) Summit Creek, which is tributary to Willow Creek upstream of the permit area, but drains the extreme eastern portion of the permit area." Surface water quality is typical of arid regions with chemical characteristics such as "calcium bicarbonate, calcium sulfate, and sodium bicarbonate water types with neutral to moderately alkaline pH, high TDS and TSS values, and elevated sulfate, iron, and phenols."

Cyprus has determined on page 4.7-26 that the potential hydrologic consequences for ground water are: 1) Alterations of ground water flow patterns; 2) Drainage of seeps/springs; 3) Alterations of recharge/storage/discharge relationships; and 4) Increases in concentrations of TDS and certain individual chemical constituents. However, the effect of these consequences "will be limited by the lack of significant ground water recharge in the area, the existence of a thick sequence of low permeability bedrock layers between the coal seams to be mined and the ground surface, the general lack of significant regional ground water movement due the absence of well-defined regional aquifers, and very limited beneficial ground water use in the permit and adjacent areas."

Cyprus has determined on page 4.7-28 that the potential hydrologic consequences for surface water are: 1) Temporary increases in runoff from surface disturbance areas; 2) Minor reductions in surface flows and alteration of surface flow patterns due to operation of sedimentation structures and flow reductions due to mine water supply withdrawals; 3) Changes in surface water chemistry; and 4) Increases in the levels of TDS, TSS, and certain individual chemical constituents. However, the effects of these consequences "will be limited by the relatively small surface disturbance area, and will be effectively mitigated by operation of the drainage and sediment control system and ultimate reclamation of mine disturbance areas."

TECHNICAL ANALYSIS

Last revised - April 22, 1996

Removal of vegetation and other disturbances "will reduce infiltration potential and evapotranspiration due to elimination of vegetation and will increase surface runoff and erosion potential." Cyprus will divert undisturbed drainage around disturbed areas and grade disturbances such that removed vegetation will not greatly increase the amount of erosion. Cyprus will further decrease the effects of increased runoff by minimizing the amount of surface disturbance area and implementing a drainage and sediment control plan (Exhibit 13). Prompt reclamation after completion of mining operation will insure time limited effects of increased runoff rates.

Reductions in surface flows and alteration of surface flow patterns will likely occur due to operations of sediment structures and mine water supply withdrawals. Sedimentation ponds will collect water during periods of runoff resulting from large storm events and snow melt. Cyprus says that retention of water in the ponds followed by slow release "will actually represent a positive impact, potentially extending the period of active flow" in ephemeral and intermitted areas. They go on to say that perennial drainages will only be impacted when runoff is retained in low-flow periods. Any runoff retained will be a small percentage of normal flows. Cyprus does not consider the amount of water lost to evaporation from within the sediment ponds that would not be lost if allowed to flow naturally into their respective drainages; however, the sediment ponds are designed to detain water no longer than 3.4 days.

Cyprus will withdrawal water from the Price River for mine water supply at a rate of 730 acre-feet per year (pages 4.7-10 and 11). Cyprus holds active senior water rights for the water that they will withdrawal; however, they are responsible for and recognize the concern to flow depletion. Plans will be put into place to recycle water used in mining operations to limit the need to withdrawal water from the Price River. Cyprus does not include in this PHC any information about how much water will be withdrawn from the Price River.

Mining activities at the Willow Creek Mine may cause some changes in surface water chemistry by exposing surficial materials to runoff. Cyprus says that "the most probable potential change in runoff water chemistry would be a shift from a strong calcium bicarbonate type toward a sodium sulfate type due to the weathering and leaching of exposed surface materials." The proposed surface drainage and sediment control plan will protect the surface materials by limiting the exposure of these material to surface runoff. Examination of the materials that will be expose show that they are not likely to be acid and toxic forming in nature; therefore, limited exposure with will result in a low potential for significant changes in surface water chemistry. Surficial materials are described on page 4.7-35.

Increased exposure of materials to water is also a potential cause of changes in the levels of TDS and other individual chemical constituents. The potential for erosion to increase in unvegetated disturbed areas will increase the potential for increase sediment load, TSS, in storm and snowmelt runoff. Cyprus predicts that mining activities will not cause changes in pH, but "TDS, TSS, and sulfate levels may increase slightly in the disturbed area runoff."

Willow Creek stream alterations are covered in the PHC on pages 4.7-34 and 36. Section 4.7.2.2 describes how the surface water resources will be preserved during the construction of the alternate flow paths.

Findings:

Sampling and Analysis

The information about the baseline hydrologic monitoring plan is accurate and fulfills the requirements of the regulations. According to R645-301-723, Cyprus must perform all mining activities according the current edition of "Standard Methods for the Examination of Water and Wastewater" or the methodology in 40 CFR Parts 136 and 434.

Groundwater Information

The name, location, and description of streams, existing wells, springs, and other surface and ground water resources are given. Ownership and location for rights to surface and ground water are given. The PAP data on ground water quality and quantity to not indicate seasonal variation and usage. Ground water quality descriptions include baseline information on total dissolved solids or specific conductance corrected to 25 degrees C, pH, total iron, and total manganese and additional water quality parameters. Ground water quantity descriptions include water levels for monitoring wells and flow rates for seeps and springs. Alkalinity has been determined for most water samples. Acidity has not been measured, but the potential for acid drainage from the proposed mining operation is minimal.

Probable Hydrologic Consequences

Probable Hydrologic Consequences ground water baseline information is complete and accurate.

The PHC for surface water is complete and accurate. Cyprus has met all applicable regulations dealing with the probable hydrologic consequences.

MAPS, PLANS, AND CROSS SECTIONS OF RESOURCE INFORMATION

Regulatory Reference: 30 CFR Sec. 783.24, 783.25; R645-301-323, -301-411, -301-521, -301-622, -301-722, -301-731.

Analysis:

The engineering information that needs to be addressed in the environmental resource information is to identify and describe the lands that will be subjected to coal mining and reclamation operations over the estimated life of mine. The specific information required in Sections R645-301-521.111, 112, 121, 122, 123, 124, 132, 141, 150, 151, 152, 190 deals with the types of maps and cross section that must be included in the PAP.

The maps and cross sections in the PAP meet the minimum regulatory requirements as listed under R645-301-521.111, 112, 121, 122, 123, 124, 132, 141, 150, 151, 152, 190. Other regulations apply to maps and cross sections. Those requirements will be addressed in the appropriate sections of this technical analysis.

TECHNICAL ANALYSIS

Last revised - April 22, 1996

Subsurface Water Resource Maps

Occurrences of subsurface water within and adjacent to the permit area are shown on Maps 15 and 16.

Surface Water Resource Maps

Lakes, streams, ponds, and springs within and adjacent to the proposed permit area are shown on Maps 15 and 16.

Monitoring Station Map

Ground-water and surface-water monitoring stations are shown on Figure 2 in Exhibit 12 and Map 15 in Volume 15.

Well Maps

Wells within and near the permit area are shown on Map 15 in Volume 6. Elevations (to the nearest 40 feet) and locations of test borings are also shown on Maps 12 and 16 of the PAP and Map 2 of Exhibit 11. The location of one gas well is shown on Map 15.

There is some potential that ground water and surface water quality in the permit and adjacent areas may be affected by a coalbed methane degassification project located north of the lease and adjacent areas. The Cockrell Oil Company is extracting water from approximately 25 coalbed methane wells in the Blackhawk Formation to desorb methane from the coal matrix. Methane is removed from the water, the water stream is treated to reduce TDS and volume, and the remaining water is injected into the Price River Formation. Injected water may increase the discharge rate from springs and seeps downgradient of the degassification project, quality of spring and seep discharges may be degraded by the injected concentrate, and quality of water in the Price River may eventually be affected. In the unlikely event that ground water impacts extend further than projected by the environmental analysis for the project, water quality impacts could be locally significant within the permit area and the resulting degradation of ground water quality due to the coalbed methane project could be misinterpreted as being related to Willow Creek mining activities. The injection wells are outside the permit and adjacent area. Locations are shown on Figure 3.7-3A.

Contour Maps

Maps 4, 6 and 8 show the premining topography in the facilities areas. Maps 3, 5 and 7 show the regional topography.

Coal Resource and Geologic Information Maps

Surface geology for the region is shown on Map 12, a certified map. Elevations (to the nearest 40 feet) and locations of test borings are also shown on Map 12. The crop lines for the coal seams are shown on Maps 14-A to 14-E. Strike and dip shown on Map 12. Locations of the fifteen test borings of the alluvial/colluvial aquifers associated with Price River and Willow Creek are on Map 16 and Map 2 of Exhibit 11, Geotechnical Investigations.

TECHNICAL ANALYSIS

Water Quality

Elevations (to the nearest forty feet) and locations of monitoring stations used to gather data on water quality and quantity are on certified Map 15, Regional Hydrology Map.

Subsurface Water Resource Maps

Geologic Cross Sections AA' to FF', Drawings (Maps) 13A to 13D, provide one piece of information on the location and extent of subsurface water within the proposed permit or adjacent areas. There is no map of the potentiometric surface for the regional or other aquifers. Figure 3.7-1 indicates there is little seasonal difference of heads.

Affected Area Boundary Maps

Maps 19A to 19D show the boundaries of all areas proposed to be affected over the estimated total life of the underground mining activities. They describe the size, sequence, and timing of the mining activities over the mine life.

Existing Structures and Facilities Maps

The areas where the surface facilities for the Willow Creek Mine will be located have been previously disturbed by coal mining activities. The premining topography and existing surface facilities are shown on Map 18A. The proposed topography and facilities are shown on Map 18B.

Mine Workings Maps

The location of known mine workings in the permit area are shown on Map 10, Previous Mining Activities. The proposed mine workings are shown on Maps 19A to 19D.

Permit Area boundary Maps

The permit boundaries are shown on several maps. They include Maps 1, 2, 3, 5, 7, 9, 10, 12, 15, 17, 19A-19D, and 20.

Surface and Subsurface Manmade Features Maps

The location of the surface and subsurface manmade features are shown on Maps 18A and 18B. While the maps show the locations of these features, they are not labeled.

Findings:

Coal Resource and Geologic Information Maps

Stratigraphy and structure of the proposed permit and adjacent areas are portrayed on maps and cross sections. Cross Sections, maps, and plans show elevations and locations of test borings. Coal crop lines and information on the nature, depth, and thickness of the coal seams and overburden and underburden are shown on maps and cross sections. Strike and dip are shown on Map 12. Locations of the fifteen test borings of the alluvial/colluvial aquifers

TECHNICAL ANALYSIS

Last revised - April 22, 1996

associated with Price River and Willow Creek are on Map 16 and Map 2 of Exhibit 11, Geotechnical Investigations.

Monitoring Sampling Location Maps

Elevations (to the nearest 40 feet) and locations of wells test borings are shown on Maps 12, 15, and 16 and Map 2 of Exhibit 11.

Subsurface Water Resource Maps

The location and extent of subsurface water within the proposed permit and adjacent areas are not portrayed on maps (potentiometric surface). Geologic Cross Sections AA' to FF' (Maps 13A to 13D), provide some information on the location and extent of subsurface water. Hydrographs in Figure 3.7-1 indicates there is little seasonal difference of heads. Maps show elevations and locations of monitoring stations used to gather baseline data on the quality and quantity of ground water, and location of water wells.

Well Maps

Locations of the one gas well within the proposed permit area and water wells in the permit area and adjacent areas are shown on maps and plans in the PAP.

Wells that extract gas from the coal seams and inject waste water from the gas stripping process are located near the proposed permit area. Locations of the injection wells in relation to the proposed permit area is shown on a map in the PAP.

Surface and Subsurface Man-made Features Maps

The Operator did not label the manmade features outside the permit area such as PacifiCorp Carbon Generating Station, State Highway 191 and U.S. Highway 6 & 50. Such features need to be labeled on both the Maps 18A and 18B.

OPERATION PLAN

GENERAL REQUIREMENTS

Regulatory Reference: 30 CFR Sec. 784.2, 784.11, R645-301-523

Analysis:

The Operator provided a general operational plan in the PAP. The specific of the plan will be discussed in the following subsection.

Findings:

The Operator has met the minimum regulatory requirements.

EXISTING STRUCTURES

Regulatory Reference: 30 CFR Sec. 784.12; R645-301-526.

Analysis:

As described in Section 3.4.4, Previous Mining Activity, extensive historic mining activity has occurred throughout the proposed permit area with resulting development of underground mine workings in many areas. Surface disturbance from coal mining consists of mine portals, coal and waste stockpiles, coal handling, processing, and loadout facilities; and mine support facilities. In Castle Gate, surface disturbance included residential and commercial development tied to the historic mining operations. Both mining related underground and surface disturbance are shown and labeled on the Previous Mining Activity Map (Map 10) Table 3.4-1 shows the chronology of the underground mining and surface activities that have occurred in the proposed permit boundaries.

One reason for determining the prior disturbance is to determine what areas are pre-SMCRA sites. If the pre-SMCRA sites are not used in for during mining and reclamation then those areas need not be reclaimed by the Operator. The Operator has not identified any areas within the proposed permit area that will meet the pre-SMCRA reclamation exemption. The Division has determined that the pre-SMCRA exclusion rule will not apply to this site.

Findings:

The Operator has met the minimum regulatory requirements.

TECHNICAL ANALYSIS

Last revised - April 22, 1996

RELOCATION OR USE OF PUBLIC ROADS

Regulatory Reference: 30 CFR Sec. 784.18; R645-301-521, -301-526.

Analysis:

Information on the relocation or use of public roads is listed in Section 2.1.6.2. Disturbance associated with development and operation of the mine surface facilities will, however, occur within 100 feet of State Highway 191 which is a public road. In compliance with the applicable regulatory provisions of Rules R645-103-234.100 through 400, the Operator has contracted and obtained approval from the Utah Department of Transportation and initiated a formal request for public hearing with UDOGM. Copies of public notice and hearing documentation and written findings relative to mining within 100 feet of a public road were submitted to UDOGM on receipt of insertion in Exhibit 3, Public Notice and Proof of Publication, Hearing Notices and Documentation.

Findings:

The Permittee has met the minimum regulatory requirements.

AIR POLLUTION CONTROL PLAN

Regulatory Reference: 30 CFR Sec. 784.26, 817.95; R645-301-244.

Analysis:

Air quality information is presented in Sections 3.5 and 4.4. These sections contain information about air quality in the general area and about methods to be used to control emissions. Exhibit 4 contains a copy of the Notice of Intent submitted to the Division of Air Quality.

The Division of Air Quality is the primary regulatory authority for this regulation and will be responsible for reviewing the Applicant's commitments. The Applicant will need to obtain an approval order before beginning construction. However, for the present, the Applicant has complied with the requirements of these regulations.

Findings:

For the present, the Applicant has complied with the requirements of these regulations. Before beginning construction, the Applicant will need to obtain an approval order from the Division of Air Quality.

TECHNICAL ANALYSIS

COAL RECOVERY

Regulatory Reference: 30 CFR Sec. 817.59; R645-301-522.

Analysis:

Maximum resource recovery has always been and will continue to be one of Cyprus's primary objectives in compliance with applicable USDI-BLM regulations and as a matter of sound resource management and efficient mining and economic practice. Conservation and maximum utilization of the available coal resource will involve mining to the minimum practical seam thickness, maximizing overall coal recovery consistent with sound engineering and mining practices. Resource conservation and protection have been addressed in some detail in the Resource Recovery and Protection Plans (R2P2) previously submitted to and approved by the USDI-BLM as part of the Blackhawk Logical Mining Unit Report in April 1992.

When a proposed permit will include mining federally owned coal, the Division usually relies on the R2P2 in their evaluation. A copy or summary of the R2P2 was not included in the PAP. Lack of the R2P2 will hamper the Division's in determining if maximum coal recovery will occur. The Division recommends that the Operator include a copy of the R2P2 in the PAP. (In the 02/06/96 revisions the Operator states that he is in the process of revising the R2P2. As soon as the R2P2 has been revised, the Operator will submit information from the revised plan.)

The Division has evaluated the coal recovery plan and has determined that the Operator could mine the southwest corner of Section 32 Township 12 South, Range 10 East in the A seam.

Findings:

The Operator failed to meet the requirements of R645-301-522 by excluding coal recovery from the southwest corner of Section 32 Township 12 South Range 10 East in Seam A. The Division will wait until the Operator includes a copy of the R2P2 before evaluating coal recovery on federally controlled lands.

SUBSIDENCE CONTROL PLAN

Regulatory Reference: 30 CFR Sec. 784.20, 817.121, 817.122; R645-301-521, -301-525, -301-724.

Analysis:

Renewable Resources Survey

The Operator identified the following as structures or areas as renewable resource lands that could be affected by mining related subsidence. The structures and renewable resource lands identified in the subsidence survey are:

- High plateau areas and ridge lines that have the potential for low-intensity seasonal grazing
- Limited recharge areas generally associated with the relatively flat high plateaus and exposed ridge lines, and small basins where runoff or snow accumulations may provide supplemental ground water recharge

TECHNICAL ANALYSIS

Last revised - April 22, 1996

- State Highway 191
- Willow Creek
- Several power transmission lines that cross the proposed permit area
- Several unimproved dirt roads
- Several fence lines

The Division agrees with the Operator's findings that subsidence could damage structures and renewable resource lands. According to R645-525.100 if the Division determines that the potential exists for subsidence to damage structures or renewable resource lands then the PAP must have a subsidence control plan. A copy of the subsidence control plan was submitted to the Division in the PAP and will be evaluated in the following section of the technical assessment.

Subsidence Control Plan

Coal Removal Method

Cyprus currently projects an annual production rate of 0.3 to 6.0 million tons of coal from the Willow Creek Mine over the 20 year mine life. Annual production may fluctuate dependent on changes in coal market conditions and other factors. A relatively rapid build-up in production to the full production capacity of 6.0 million tons of coal per year will occur over a period of approximately 4 years.

Mine development involves excavation and construction of the underground openings, or entries, required to access the minable coal reserves, provide for efficient production of those reserves, facilitate haulage of both coal and mine waste, and provide for effective ventilation of the mine workings. Development activities will include development of mine portals, main entries, sub-mains, slopes and rises, and longwall panels. All mine development activities including both development methods and actual physical dimensions of development entries have been designed to provide for long-term stability during active mining operations and to effect full compliance with all applicable regulatory provisions.

Cyprus plans to utilize the longwall mining method as the primary coal production technique. There are, however, certain areas where longwall mining will not be feasible due to limited seam thickness, the configuration of the remaining coal reserves (inadequate width or length to justify the costs associated with longwall development and set-up), geologic conditions, or potential subsidence concerns. In these areas, conventional room and pillar mining methods will be utilized with continuous miners, shuttle cars, and roof bolters as the primary production equipment.

The Division has determined that the Operator described the methods of coal removal, the projected amount of coal mined, and the sequence and timing for the development of underground workings. The minimum regulatory requirements have been met.

Underground Workings Map

Map 19A to Map 19D show the location of the mine workings and projected subsidence for each seam. Map 20, Subsidence Monitoring Plan, shows the areas of planned subsidence for the entire project.

TECHNICAL ANALYSIS

Physical Conditions Description

Coal extraction thickness will range from approximately 5 to 13 feet resulting in potential maximum subsidence of 3.5 to 9.1 feet assuming the projected maximum subsidence rate of 0.7 times extraction thickness. It is important to note that this is the maximum potential subsidence with full extraction. In reality, practical operational limitations on coal extraction, increased mining depth, and the massive sandstones previously discussed will probably result in actual subsidence which is considerably less than this maximum value.

Given that most of the proposed mining will occur at depths of 700 to over 2,000 feet, averaging approximately 1,800 feet and the occurrence of several relatively massive high-strength sandstone units in the overlying stratigraphic sequence which will probably limit vertical deformation, surface subsidence is expected to be minimal. Use of the proposed longwall mining method inherently provides the greatest amount of control over the area and rate of subsidence. Associated subsidence is typically uniform consistent with a relatively uniform coal recovery thickness and occurs progressively with panel extraction minimizing potential differential settlement. Experience indicates that approximately 90 percent of longwall related subsidence occurs within 2 to 3 years following completion of mining.

Exhibit 11 contains a report by Agapito Associates, Inc. entitled "Measures for Controlling Subsidence from Movable Coal Seams in the Willow Creek Area". The study examines the geologic and geotechnical environment, subsidence parameters and stability evaluations.

The Division has examined the information about the lithology, topography and mining activities that will affect subsidence. The Division has determined that there is enough information to support the Operator's claims about subsidence. The Operator's claims about the extent of subsidence are consistent with other subsidence studies in the Utah and Colorado coal fields.

The Operator has met the minimum regulatory requirements physical conditions description.

Monitoring Description

Once development and mining operations begin, Cyprus will implement an ongoing subsidence monitoring program to determine when mining related subsidence commences and the amount of actual surface subsidence. This information will be reviewed and evaluated to determine the accuracy of the original subsidence projections. The subsidence monitoring data will also be the basis for any appropriate modifications in mining plans, mine sequencing, or ground control measures in order to minimize or provide for controlled surface subsidence. By providing for ongoing review and evaluation of actual subsidence response, Cyprus can make any design or operational adjustments necessary to prevent significant subsidence related material damage or diminution of use. The proposed subsidence monitoring plan has been developed in compliance with applicable regulatory provisions of Rules R645-301-525.140 and 632, and will include periodic visual observations, field surveys of permanent subsidence monuments, review and evaluation of monitoring field data, and development of summary tables showing any changes

TECHNICAL ANALYSIS

Last revised - April 22, 1996

in elevation or horizontal position (for sensitive structures only) of the subsidence monuments and subsidence profiles.

The periodic visual observations will be conducted on at least an annual basis and will involve a visual field inspection of potential subsidence areas for any visible evidence of subsidence including surface cracks, slumping, displacement, structural damage, or other observable changes. Any observed evidence of potential subsidence related surface impacts will be noted on a field report form and the location of any documented observations will be tied to existing subsidence monuments to the extent reasonably feasible.

Subsidence monuments will be established in each potential subsidence area before any subsidence actually occurs in that area, normally during the summer prior to initiation of mining. The timing for installation of monitoring points will be determined by projecting the angle of draw from the line of mining advance based on the following formula:

$$\text{Distance} = \text{Overburden} (\tan 22\frac{1}{2}^{\circ})$$

Based on available information, as documented by Exhibit 11 the anticipated maximum angle of draw for the proposed operations is 22.5 degrees. The anticipated subsidence limits and corresponding boundaries for subsidence monitoring activities are based on the projected maximum angle of draw. Given, however maximum draw angles of up to 45 degrees for similar operations, Cyprus will establish an expanded subsidence boundary corresponding to the theoretical maximum draw angle of 45 degrees for initial mining operation in the D Coal Seam to verify the projected angle of draw. Since the D Coal Seam is the uppermost coal seam to be mined, it is associated with the minimal depth of cover and maximum subsidence potential and so represents the worst-case subsidence condition. If initial monitoring indicates an angle of draw greater than the projected maximum of 22.5 degrees, subsidence limits and the subsidence monitoring network will be reevaluated and expanded if necessary to address the maximum area of potential surface subsidence effects.

Detailed Description of the Subsidence Control Measures

Subsidence control for the corridor containing the highway and creek will be provided by a barrier pillar extending under this corridor. The barrier pillar is defined by the angle of draw extending from the limit of any mining areas adjacent to the highway/creek corridor as shown on the Mine Plan Maps (Maps 19A through 19D) and, with the exception of the K Seam main entry crossing, no mining will occur within this defined boundary. The K Seam main entry crossing has been designed based on specific recommendations presented in the Agapito Report which is included in Exhibit 11, Geotechnical Investigations. The K Seam main entries will be developed at a depth of approximately 900 feet beneath Willow Creek as 20 foot wide entries with 70 x 100 foot pillars. This configuration will result in an effective extraction ratio of only 37.5 percent, there will be no retreat mining in this area, and the coal remaining in the support pillars will provide for effective long-term stability to prevent subsidence of overlying areas.

The Operator provided protection to Highway 191 and Willow Creek by excluding those areas from planned subsidence. Mining beneath the structures will be limited to main entry in the K seam. That entry is needed for access to coal east of the highway/road corridor.

TECHNICAL ANALYSIS

Description of the Anticipated Effects of Planned Subsidence

Low-Intensity Seasonal Grazing Areas - Some of the relatively flat high plateau and broad upper ridgeling areas in the northwest portion of the proposed permit area are utilized on a seasonal basis for low-intensity cattle ranching and sheep grazing. Use is limited by the generally rugged terrain, arid conditions, and lack of significant ground water resources for stock watering. Due to the natural dip of the coal seams, these areas are near the effective cover limit for proposed mining operations and correspond to cover thicknesses of 1,800 feet or more. Given effective cover depths and the proposed ground control measures noted above, potential subsidence in these areas should be limited and is not expected to result in any significant diminution of the existing grazing use.

In the unlikely event that subsidence was to result in surface cracks which could pose a hazard to livestock or ground water source Cyprus would take remedial action. If any significant surface cracks were to occur fences or grading would be used to protect the public and livestock. If ongoing monitoring results in a determination that mining has resulted in reduction of changes in the flow or quality of a stock watering source which will significantly diminish potential grazing use, remediation may involve replacement or augmentation of any affected water rights, monetary compensation, development of alternative watering facilities.

Limited Recharge Areas - Ground water recharge in the area is limited by the arid climate, rugged terrain, and relatively low permeability of most of the geologic units. Effective ground water recharge occurs only where potential water bearing members outcrop on the relatively flat high plateau areas, on exposed ridge lines, and in small basins where runoff or snow accumulations may provide a supplemental ground water recharge and in these areas limited outcrop exposures preclude a significant recharge. As discussed in Section 3.7.2.2, Ground Water Aquifers, transmission of the minimal recharge that does occur to either perched aquifers or the regional water table aquifer is effectively limited by the low overall permeability of the overlying stratigraphic units. The regional water table aquifer is not generally utilized for water supply due to its relative depth and low water storage and transmission capacity and perched aquifers are typically of such limited extent that use is limited to occasional small volume stock watering from the few developed springs and seeps that exist in the area as shown on the Regional Hydrology Map (Map 15). There are no ground water supply wells within the area of potential subsidence which would be affected by mining related subsidence.

Unimproved Dirt Roads - Several unimproved dirt roads exist in the area as shown on the Subsidence Control Plan Map (Map 20). These roads have limited access, are not maintained on a regular basis, and are generally used only by private property owners in the area for grazing or other occasional access

Fence Lines - Several fence lines exist within the area of potential subsidence as shown on the Subsidence Monitoring Plan Map (Map 20). The existing fence lines are typically three-wire barbed fences strung on wooden posts which are utilized to delineate and confine livestock use to specific areas. It is anticipated that potential subsidence related impacts on existing fence lines will be minimal and will be limited to isolated instances of fence wire being broken or separated from the supporting posts.

TECHNICAL ANALYSIS

Last revised - April 22, 1996

State Highway 191 and Willow Creek - State Highway 191 parallels Willow Creek, bisecting the proposed permit area along a diagonal corridor running from southwest to northeast. Both the highway, as a major structure, and the creek, as an important resource value, will be protected from potential mining related subsidence effects. Cyprus does not plan to develop either longwall panels or room and pillar sections under the highway and creek, but will drive main entries in the K Seam under the highway/creek corridor to access minable K, C, and A Seam reserves to the south and east.

Subsidence control for the corridor containing the highway and creek will be provided by a barrier pillar extending under this corridor. The barrier pillar is defined by the angle of draw extending from the limit of any mining areas adjacent to the highway/creek corridor as shown on the Mine Plan Maps (Maps 19A through 19D), and with the exception of the K Seam main entry crossing, no mining will occur within this defined boundary. The K Seam main entry crossing has been designed based on specific recommendations presented in the Agapito Report which is included in Exhibit 11, Geotechnical Investigations. The K Seam main entries will be developed at a depth of approximately 900 feet beneath Willow Creek as 20 foot wide entries with 70 x 100 foot pillars. This configuration will result in an effective extraction ratio of only 37.5 percent, there will be no retreat mining in this area, and the coal remaining in the support pillars will provide for effective long-term stability to prevent subsidence of overlying areas.

The power poles in Barn Canyon will not be damaged by subsidence since the Operator will either make arrangements to move the lines outside the subsidence area or not mine the coal under Barn Canyon.

The Operator assumes that State Highway 191, Willow Creek and the powerlines that parallel them are in a protected corridor that will not be affected by subsidence. The assumption is based on the 22.5° angle of draw, which is the average angle of draw for Utah and Colorado. It is possible that the angle could be much larger than 22.5° and subsidence would occur in the corridor. In such an event the stream, highway or powerlines could be damaged. The Operator needs to address this situation.

In the unlikely event that Willow Creek, State Highway 191, or the nearby powerlines are impacted by surface subsidence, Cyprus would immediately notify UDOGM, UDOT, PacifiCorp, and any other appropriate jurisdictional agencies or other entities. In consultation with the effected or responsible parties, Cyprus would develop and implement any necessary and appropriate control and mitigation measures. Control and mitigation measures would focus first on any immediate safety or environmental concerns and then address repair and mitigation of any related subsidence damage.

The Operator has committed to mitigate all damages caused to manmade structures. Since specific remediation plans cannot be developed until after the event the Division considers this commitment adequate.

Measure for Mitigation or Remedy of Any Subsidence-related Material Damage

In the unlikely event that subsidence damage was to occur in the low-intensity seasonal grazing areas, it would most likely be in the form of surface cracks which could pose a hazard to livestock or in interruption of any perched ground water sources supplying water for stock

TECHNICAL ANALYSIS

watering purposes. If this occurred, Cyprus would implement appropriate remedial measures. Generally, the areas which are grazed are not susceptible to surface cracking since developed soils exist in these areas which would inherently buffer any tensile stresses; however, if any significant surface cracking were to occur remediation would involve fencing any areas that pose a potential hazard to livestock, limited surface grading or plowing, and reseeded to fill the cracks, minimize erosion and reestablish vegetation. As appropriate and with documentation of any actual loss, Cyprus will compensate the surface land owner/grazing lessee for any direct livestock losses and any significant loss of use resulting from mining related subsidence. Cyprus currently, and will continue to, monitors all known springs and seeps in the area during the period of active mining operations. If ongoing monitoring results in a determination that mining has resulted in reduction or changes in the flow or quality of a stock watering source which will significantly diminish potential grazing use, remediation may involve replacement or augmentation of any affected water rights, monetary compensation, development of alternative watering facilities such as guzzlers, or a negotiated agreement with the affected surface owner/grazing lessee providing for substitution or replacement of grazing areas.

The potential subsidence effects on the unimproved roads should be limited, and are not expected to result in any significant diminution of existing road conditions or access. In the unlikely event that subsidence was to result in surface cracks which could affect road conditions or use, remediation would involve limited surface grading to fill and eliminate the cracks and to provide a smooth, passable road surface.

If Willow Creek, State Highway 191, or the nearby powerlines are impacted by surface subsidence, Cyprus would immediately notify UDOGM, UDOT, PacifiCorp, and any other appropriate jurisdictional agencies or other entities. In consultation with the effected or responsible parties, Cyprus would develop and implement any necessary and appropriate control and mitigation measures. Control and mitigation measures would focus first on any immediate safety or environmental concerns and then address repair and mitigation of any related subsidence damage.

Other Subsidence Control Information Specified by the Division

The Operator must obtain an agreement with the Utah Department of Transportation (UDOT) to mine beneath State Highway 191. The agreement is needed to insure that the public is protected from the potential effects of subsidence on a public road. The Operator must also agree to notify UDOT six months prior to any mining under state highways.

In the February 2, 1996 submittal, the Operator stated that an agreement with PacifiCorp and Boyd Marsing are pending and copies will be provided to UDOGM on receipt. The Division cannot approve the subsidence plan until they have obtained documentation that UDOT has approved the mine plan.

Performance Standards for Subsidence Control

The Operator has committed to repair or replace any material damage caused by subsidence. The Operator does not show any public buildings and facilities, churches, schools, and hospitals; or impoundments with a storage capacity of 20 acre-feet or more or bodies of water with a volume of 20 acre-feet or more within the area of planned subsidence. When the

TECHNICAL ANALYSIS

Last revised - April 22, 1996

Operator determined the areas planned subsidence he assumed that the angle of draw would be 22.5° and no subsidence will occur in the corridor beneath Willow Creek. The angle of draw is based on the average angle of draw in Utah and Colorado. While that assumption may be the best estimate for the angle of draw it is possible the angle of draw could be much larger and affect Willow Creek, the powerlines and the state highway.

The Division usually accepts the 22.5° angle of draw until field measurements demonstrate that another angle should be used. There is no reason for the Division to reject the 22.5° at this time. However, if subsidence monitoring data indicates that subsidence could occur outside of the approved subsidence control areas then the Operator must modify the mining plans so that subsidence only occurs in the approved areas. Should subsidence cause damage to State Highway 191, powerlines, or Willow Creek the Operator must commit to repair the damage.

Notification

Prior to initiation of mine development or other mining activities which could result in potential surface subsidence, Cyprus will notify the affected surface landowners as well as the owners or Operator's of any potentially affected utilities or structures. Notification will occur at least 6 months prior to initiation of the mining activities and will consist of a written notice identifying the area(s) of proposed mining, the schedule for when mining will occur, and the location(s) where a copy of the subsidence control plan is available for public review. In order to protect the rights of the owners or Operator's of specific structures and lands which could potentially be affected by mining related subsidence, Cyprus is either proceeding with, or has obtained, subsidence agreements giving Cyprus the right to undermine the subject lands or structures provided that any subsidence related impacts are properly mitigated. Where appropriate, subsidence agreements will be secured prior to initiation of any mining related activities which may potentially affect the structure or lands covered by the agreements. Existing subsidence agreements are included in Exhibit 16, Subsidence Information, and copies of any agreements obtained in the future will be provided to UDOGM for insertion in this exhibit. The following summarizes the need for, and status of, any subsidence agreements for mining and related operations:

Surface Landowners - Subsidence agreements have been obtained from the private property owners of surface lands within potential subsidence areas as indicated by comparison of the Surface Ownership Map (Map 1), and the Subsidence Monitoring Plan Map (Map 20). These agreements document Cyprus's right to undermine the private property holdings addressed by the agreements provided that any subsidence related material damage is effectively mitigated. Mitigation may include, but is not limited to purchase of affected lands, substitution or replacement of grazing areas, monetary compensation, or repair of any surface damage.

Water Rights

Subsidence agreements have been obtained from owners of water rights that lie within potential subsidence areas as indicated by comparison of the Water Rights Map (Map 17), and the Subsidence Monitoring Plan Map (Map 20). The agreements document Cyprus's right to mine beneath the surface or ground water sources associated with the water right(s) and Cyprus's commitment to mitigate any subsidence related impacts. Mitigation may include, but is not limited to purchasing the water right, replacement or augmentation of any affected water rights, monetary compensation, development of alternative watering

TECHNICAL ANALYSIS

facilities such as guzzlers, construction of retention ponds, and substitution or replacement of grazing areas. There are no domestic drinking water sources within the proposed mining and potential associated subsidence areas.

Highway 191 and Willow Creek

Areas beneath State Highway 191 and Willow Creek were extensively mined in Sections 31 and 32, T12S, R10E, as shown on the Previous Mining Activities Map (Map 10). The historic mining in this area consisted of extensive development mining with retention of support pillars in most areas, although retreat mining with pillar recovery is known to have occurred in two areas, one area directly beneath and the other very close to the highway and creek. There is no evidence that the historic mining resulted in any significant surface subsidence impacts to either the highway or the creek. Given this directly applicable historic mining precedent and Cyprus's plans to retain a barrier pillar beneath the highway/creek corridor and limit extraction in the K Seam main entry crossing, no significant subsidence is anticipated and subsidence agreements with UDOT for the highway are not considered necessary.

Powerlines

Although no subsidence impacts to electrical transmission lines are anticipated, in order to protect PacifiCorp's interests Cyprus is also proceeding with negotiation of a subsidence agreement which will be secured before initiating any mining activity which could affect the existing power lines. The agreement will give Cyprus the right to undermine in the vicinity of the power lines provided that any subsidence related impacts are appropriately mitigated.

The Operator has committed to notify all surface owners at east six months prior to mining under their property.

Findings:

The Operator has met the minimum regulatory requirements for renewable resources survey.

The Operator has met the minimum regulatory requirements for describing the coal removal method. The minimum regulatory requirements have been met for the underground workings map. The Operator has met the minimum regulatory requirements physical conditions description. The Operator has met the minimum regulatory requirements for a monitoring description. The Operator has met the minimum regulatory requirements for a detailed description of the subsidence control measures. The Operator has met the minimum regulatory requirements for a description of the anticipated effects of planned subsidence. The Operator has met the minimum regulatory requirements for Measure for mitigation or remedy of any subsidence-related material damage.

The Operator has met the minimum regulatory performance standards for subsidence.

The Operator has met the minimum regulatory requirements for subsidence notifications.

TECHNICAL ANALYSIS

Last revised - April 22, 1996

SLIDES AND OTHER DAMAGE

Regulatory Reference: 30 CFR Sec. 817.99; R645-301-515.

Analysis:

Certain situations involving accidents, emergencies, or unforeseen circumstances may require immediate or timely reporting to provide for appropriate coordination of required control and mitigation measures. Under applicable regulatory requirements, these situations are specifically identified as including the following:

- Slides which may have potential adverse effects on public health and safety, property, or the environment
- Impoundment hazards
- Accidental release of potentially hazardous or toxic materials including petroleum products
- Temporary cessation of mining operations

Reporting and emergency measures for potential slides are specifically addressed in Section 4.6, Geologic Protection; for impoundment hazards and accidental releases of potentially hazardous or toxic materials in Section 4.7, Hydrologic Resource Protection; and for temporary cessation of mining operations in Section 4.5.2.5, Temporary Cessation.

In Section 4.6, Geologic Protection, the Operator states:

At any time that a slide or similar earth movement occurs and is identified by mine personnel which poses an immediate hazard or may have potential adverse effects on health, safety, property or the environment it will be immediately reported to UDOGM. Notification would typically involve a telephone call with follow-up written documentation. Based on an assessment of site-specific conditions and circumstances, Cyprus will then coordinate with UDOGM to develop and implement appropriate remedial measures.

Findings:

The Operator has met the minimum regulatory requirements.

OPERATIONAL TOPSOIL AND SUBSOIL

Regulatory Reference: 30 CFR Sec. 817.22; R645-301-232, -301-233, -301-234, -301-242, -301-243.

Analysis:

Section 4.2, SOIL HANDLING PLANS, describes the soil handling practices, related environmental control and environmental mitigation measures associated with the Willow Creek Mine Facilities. Soil materials will be recovered from any disturbance area where natural soils exist and from previously disturbed areas where suitable disturbed soils exist. The majority of the existing Willow Creek area's surface materials represent disturbed soils which are intermixed with overburden and coal waste. Potential disturbance areas where

TECHNICAL ANALYSIS

natural undisturbed soils remain will generally be very small, typically occurring on the perimeter of previous disturbance areas where steep slopes and shallow soils limit practical soil availability.

Soil recovery will focus on removal and salvage of all reasonably recoverable soils to a maximum depth of 3 feet or until highly consolidated, coarse fragment content or clayey materials are encountered at a shallower depth. No effort will be made to segregate individual soil horizons. Where disturbed soils are to be recovered, recovery depths will range from a minimum of 12 inches to a projected maximum of 30 inches. To the extent operationally feasible, significant coal or coal refuse zones will be avoided during recovery. Any significant coal or coal waste deposits and accumulation will be excavated and disposed in the Schoolhouse Canyon Refuse Pile.

Table 4.2-1, Soil Recovery and Storage Plans, summarize soil material recovery areas and volumes for proposed mining and related surface disturbances. Table 4.2-1A, Justification for Soil Salvage Assumptions, provides supportive documentation for soil recovery. Existing topsoil stockpile volumes include Gravel Canyon at 87000 cy, Crandall Canyon at 18000 cy and Willow Creek Mine Facilities at 21200 cy. An additional 106270 cy of topsoil removal is projected at the Willow Creek Mine Facilities. Total surface disturbance at the Willow Creek Mine Facilities is approximately 55.8 acres. With a grand total of 127470 cy of salvaged topsoil over the 55.8 acres of surface disturbance, an average of 17 inches of soil removal is projected for the Willow Creek Mine Facilities. Willow Creek Mine Facilities disturbance subtotals include 31 acres previously disturbed areas, 6.7 acres undisturbed soils, 1.6 acres riparian soils and 16.5 acres reclaimed sites.

Soil removal volumes and quality are estimates based on extensive field sampling of both disturbed and undisturbed soils in the proposed surface disturbance areas. However, actual recovery and resulting soil quality will be dependent on site-specific conditions and practical operating limitations. CPMC commits to the following:

- CPMC plans to sample soil materials prior to removal and placement in temporary stockpiles to verify suitability and optimize reclamation success. Samples will be analyzed for all suitability parameters defined by the Division's Topsoil and Overburden Guidelines. Sampling results will be reviewed, summarized, and provided to DOGM.
- Soil recovery operations will be supervised and monitored by a qualified and experienced reclamation specialist/soil scientist. Actual soil recovery depths, surface area and resulting volumes will be documented and any site-specific limitations on soil recovery will be noted. Following completion of soil removal operations, a narrative description of soil recovery operations along with appropriate supporting documentation will be prepared and incorporated into the next Annual Reclamation Monitoring Report for submittal to DOGM. Any variations between actual and projected soil recovery as outlined by Table 4.2-1 will be identified and explained.

Soil and substitute topsoil will be salvaged and placed in stockpiles for storage. Existing soil stockpiles include one located in Gravel Canyon and two in the Crandall

TECHNICAL ANALYSIS

Last revised - April 22, 1996

Canyon area. One new soil stockpile is located in the Willow Creek area on the west side of an existing rock outcrop known as "Devil's Slide." Soil stockpiles will be protected from erosion, contamination, and soil loss by establishing sideslopes at 3H:1V or less, providing roughened surface conditions, seeding with vegetative cover, posting, and using appropriate drainage control measures. Seeding will normally occur as soon as reasonably feasible once active soil stockpiling operations cease for a given stockpile area. Stockpile areas will be inspected periodically and any significant erosion or other problems will be noted and repaired.

Findings:

This portion of the permit application is complete and accurate.

INTERIM STABILIZATION

Regulatory Reference: R645-301-331

Analysis:

Requirements of this regulation are addressed primarily in Section 5.3.2.3. Table 5.3-1 is a temporary seed mixture comprised of four introduced and two native species. Most of these species are rhizomatous or spread above ground to effectively protect soil from erosion.

The amount of seed the Applicant plans to use is adequate but minimal. The *Interagency Forage and Conservation Planting Guide for Utah* recommends drill seeding at a rate of 25 to 75 seeds per square foot and broadcast seeding at a rate of 50-100 seeds per square feet. If the Applicant uses the mix as shown, they would drill seed at the rate of 31 seeds per square foot or broadcast at the rate of 62 per square foot. While these are within the recommended rates, a 50% increase in the amount of seed would better assure interim revegetation.

The application says the planting time for most areas is in the fall, but prompt revegetation of small disturbances may be desirable to minimize erosion potential. In these cases, revegetation could occur at any time if site and climatic conditions are reasonable. Fall is recognized as the best time to seed in this area of Utah, but spring and early August planting may also be successful depending on the weather. If the Applicant seeds at times other than the fall, there is a risk of needing to prepare the surface again and to reseed.

The application does not specifically say what other revegetation methods will be used on interim revegetation sites. However, because it does not differentiate, it is assumed the Applicant will use the same methods for both final and interim revegetation. These techniques are discussed under "Revegetation." Seedbed preparation techniques discussed in this section apply to both interim and final revegetation. In particular, gouging is highly recommended and has been used with very good success at several sites in Utah. Gouging is where a trackhoe or similar equipment makes pits in the soil about one to two feet deep and about two to four feet across. These pits are not conducive to drill seeding, but they are very effective at trapping moisture, reducing erosion, and increasing plant establishment.

Findings:

TECHNICAL ANALYSIS

The Applicant has complied with the requirements of this section.

It is recommended the Applicant increase the amount of seed for interim revegetation by 50%. Revegetation techniques other than the species mixture and timing of planting are discussed under "Revegetation," and the Division makes recommendations to improve these methods.

FISH AND WILDLIFE PROTECTION

Regulatory Reference: R645-301-333.

Analysis:

Potential Effects and General Comments

Section 4.3.2.1 of the application includes a list of potential effects on fish and wildlife. These include disturbance of 55.8 acres of land together with displacement of wildlife from the mine area, direct mortality of non-mobile wildlife, indirect disturbance from increased human activity, a potential for losses from electrocution and traffic-related mortality, the potential for altering vegetation in subsided areas, and possible disruption of water sources due to interruption of ground water flow.

While revegetation efforts have been largely successful in establishing potential wildlife habitat, actual use is limited by the surrounding terrain and nearby disturbances. The application indicates these factors preclude significant long-term use by large mammals, raptors, and many other terrestrial wildlife species.

The application's characterizations of the significance of the site for wildlife are questionable. Although the amount of vegetative cover in the proposed disturbed area is not as great as in undisturbed areas, the vegetation in reclaimed areas is generally more palatable and has greater nutritional value for wildlife than vegetation in undisturbed areas. Division of Wildlife Resources personnel indicate the area proposed for disturbance is suitable deer habitat although use has been limited by previous disturbances. Division personnel have observed numerous deer in the AMR areas. The area has good structural diversity. Many of the rocks have whitewash indicating they are used as perches by raptors.

While opinions differ as to how important the site is for local wildlife populations, it does not appear there are any factors which would preclude granting a permit to conduct mining and reclamation operations. The Applicant will still be responsible to use the best technology currently available to protect fish and wildlife and to enhance related values, such as wildlife habitat.

According to the application, the greatest potential for significant territorial impacts would be associated with displacement of large raptors during the nesting season. At least six golden eagle nests are within one-half mile of the proposed surface facilities area, and some have been tended or used within the past few years. Construction during crucial periods could disrupt nesting activities.

TECHNICAL ANALYSIS

Last revised - April 22, 1996

Potential effects to aquatic species include increased sedimentation, especially during construction, temporary loss of habitat during realignment of the stream, and possible changes in water quality and flow rates. The length of the creek, and thus the length of the riparian area, would be shortened from about 1210 to 1100 feet.

Although the Applicant considered prevailing wind directions when locating the coal stockpiles, some windborn coal fines will probably enter the creek.

On page 4.3-5 is the statement, "The use of construction equipment near the Willow Creek stream channel represents a minor potential risk since a petroleum spill or leak could result in stream contamination and potential toxic effects from petroleum products, on fish and macroinvertebrates." The latter part of this sentence does not explain why using construction equipment near the stream constitutes a minor risk for oil spill contamination.

Maximum anticipated water withdrawals from the Price River will be limited to 730-acre feet annually. These withdrawals would be based on existing water rights, and the application indicates the Applicant does not believe this should be considered a new depletion subject to mitigation requirements for threatened and endangered fish of the Upper Colorado River. This determination will be made by the Fish and Wildlife Service after consulting with the Office of Surface Mining, Reclamation and Enforcement.

No areas were identified as potential jurisdictional wetland areas during the baseline field surveys of surface disturbance areas.

Protection Measures

The Applicant intends to minimize disturbance through the use of existing facilities at the Castle Gate Preparation Plant and by using conveyors instead of trucking coal to the preparation plant. Little of the proposed disturbed area is on undisturbed land. All facilities are consolidated in a limited area near existing transportation routes.

The application says disturbances to the creek, including removal of a series of five man-made pools below the culvert crossing, would be mitigated by building designed channel segments and revegetation with riparian and other suitable vegetation species. The realigned sections will incorporate specific designs resulting in overall enhancement of aquatic habitat values and increases in the extent of riparian vegetation. The application gives some details of the designs, including approximate pool and riffle locations, meander locations along with placement of large rocks on the outsides of meanders, and revegetation plans.

Work in the stream will be done during low flows and will include alternative sediment control to keep excavated material out of the creek and to control runoff from the disturbed areas. A series of silt fences will be installed to catch sediment in the new channel after it is first opened. New stream crossings will be seeded with a quick-growing temporary seed mix and mulched or protected with synthetic slope stabilization materials.

The conveyor system will be covered to minimize dispersion of coal fines, and all transfer points will be partially or fully enclosed to minimize fugitive coal fines. Most sections of the conveyor will be at least 200 feet from the stream, but a few will be within 150-180 feet.

TECHNICAL ANALYSIS

Accumulations of coal fines will be cleaned up and disposed of when they reach a depth of one inch or greater.

Section 4.3.3.7 says the Applicant does not plan to use, store, or generate potentially hazardous or toxic materials. This is apparently in reference to materials defined in these categories by regulations which exclude most petroleum products. The next sentence says materials potentially hazardous to wildlife, such as petroleum products, will be within closed areas or containers.

Fueling and maintenance of construction equipment will not occur in the immediate vicinity of Willow Creek, and no fuel or lubricants will be stored within the stream buffer zone. Decant structures on the sedimentation ponds have oil skimmers to minimize the potential of discharge of oil products from the ponds.

Longwall equipment will be operated, inspected, and maintained to minimize potential fluid loss. Longwall fluids that leak or spill will mix with mine drainage within the underground mine workings. The mine water handling system will be a closed loop that will not discharge to surface systems or drainages. Any mine water that needs to be discharged to the surface will be first sampled and will be routed to sediment control structures to ensure it meets effluent limitations.

Major pollution events have occurred at other mines in the area that use longwall miners. The procedures included in the application should protect the stream from potential environmental damage from longwall fluids. If a petroleum event was to reach Willow Creek, it would be reported immediately. The Spill Prevention, Control, and Countermeasure (SPCC) plan should contain specific provisions for preventing, cleaning up, and reporting spills.

Equipment use and operations in stream buffer zones will be restricted to the construction activities required for placement of bridge abutments, replacement of the culvert crossing, and stream channel realignment. No fuel or lubricants will be stored within the buffer zone, and fueling and lubrication of equipment will not occur in the immediate vicinity of Willow Creek. A full length berm will separate operating areas from the stream channel.

Aquatic monitoring will continue for two years after construction of the realigned portion of Willow Creek. Benthic macroinvertebrates and fish will be sampled in one location in each relocated portion, and this will be compared to data from a reference location. If the results of sampling during the first year after construction indicate effective recovery of aquatic communities, no additional sampling will be required in the second year. However, if the initial monitoring indicates significant continuing adverse effects, the Applicant will provide the Division with recommendations about continued monitoring and mitigation. The commitments to monitor macroinvertebrate populations in the creek satisfy regulatory requirements. However, unforeseen effects of the mine may necessitate additional monitoring in the future.

The Applicant commits to design and construct mine-related power transmission lines to protect raptors from electrocution hazards in accordance with applicable guidelines.

The application says in Section 4.3.3.6 that site-specific evaluation of the facilities area by a professional biologist resulted in the conclusion that the proposed conveyor location at the base

TECHNICAL ANALYSIS

Last revised - April 22, 1996

of the natural canyon walls does not represent a barrier to large animal movements since such movements would typically involve more favorable access routes. Although sides of the canyons are not generally used for major migrations, big game use them for foraging and for daily movements, such as to the creek. The conveyor is a potential obstacle. However, the conveyor was designed with a minimum clearance of 40 inches. Several sections of the conveyor will be elevated more than 40 inches. Literature sources indicate most deer and elk have no problem going under conveyors elevated at least one meter. Portions of the conveyor will be elevated more than this and should allow large bucks and bulls to pass.

The application says in Section 4.3.4.2 that the permit area does not provide suitable nesting habitat for bald eagles but that there is some potential for golden eagle nesting. The Applicant will either not initiate new activities within one-half mile of active golden eagle nests during the spring breeding season, or it will, in consultation with the Division and Wildlife Resources, initiate appropriate mitigation measures. Observed golden eagle nesting activity within the permit area will be reported to Wildlife Resources. The Applicant will conduct periodic raptor surveys in areas of concern if proposed mining activities have significant potential to adversely affect raptor breeding.

Three golden eagle nests are in Eagle Canyon, and at least three are in Castle Canyon. Construction activities within one-half mile of nest sites, particularly when the nests are within line of site of the activities, are normally restricted to a period outside the nesting season, approximately February 15 to July 15. The Applicant intends to install water tanks near the mouth of Castle Canyon and does not anticipate having a conflict with the nesting season. However, fans would be installed near the mouth of Eagle Canyon, and it is anticipated this will take about six months. This construction schedule could conflict with the nesting season for any birds nesting in Eagle Canyon.

To resolve this problem, the Applicant's officials met with the Fish and Wildlife Service. They agreed the Applicant would evaluate visibility of the proposed facilities from the nests, check the elevation difference, evaluate the possibility of scheduling some construction outside the nesting periods, look at the potential for obtaining take permits and using nesting deterrents, and propose a plan for addressing the nests in the mining and reclamation plan application. In addition, after a firm construction schedule is established, mitigation plans will be developed in consultation with the Division, Wildlife Resources, and the Fish and Wildlife Service before beginning construction. These commitments satisfy regulatory requirements. Wildlife Resources has concurred that the Applicant's monitoring and protective measures will be adequate.

During operations, significant wildlife observations from the permit area will be reported to Wildlife Resources. Personnel will be instructed to report accidental wildlife mortality or eagle sightings to the mine environmental coordinator. If mining activities have significant potential to adversely affect raptor breeding, the Applicant will perform periodic raptor monitoring surveys.

Enhancement

Habitat enhancement plans are contained in Section 5.3.3. In correspondence dated November 9, 1995, the Division of Wildlife Resources recommended that lost habitat be mitigated by an enhancement project that will encourage deer and elk to use areas other than the

TECHNICAL ANALYSIS

canyon bottom. The application lists four potential habitat enhancement alternatives. These include retreatment of chained areas on Bureau of Land Management land, seeding one or two areas on Division of Wildlife Resources' land in the Gordon Creek area, placing sources of water for wildlife on the Applicant's land near the mine, and enhancing portions of Willow Creek. The first and last of these proposals have problems that may be difficult to overcome, but the Applicant commits to select and implement one or more of the projects.

The measures discussed in the application are the types of measures the Division seeks. While details of these projects still need to be decided, and while some may not be feasible, the commitments in the application satisfy the requirements of this regulation. The projects appear to have the potential of being useful and actually achieving an increase in habitat quality.

Findings:

This portion of the application is considered complete and accurate.

The Applicant has committed to several wildlife protection and habitat enhancement measures that constitute the best technology that is now available. Four potential wildlife habitat enhancement measures have been included. Any of these should achieve the objective of improved habitat conditions.

Although the proposed disturbed area is not on federal property, portions of the proposed permit area have Bureau of Land Management land. Therefore, the Division will need to receive concurrence from the Fish and Wildlife Service. Although the Division does not anticipate adverse effects to threatened, endangered or sensitive species in the immediate area, the Fish and Wildlife Service may determine water depletions from the mine to have potential adverse effects on threatened and endangered fish of the Upper Colorado River. If so, the Applicant will need to pay a mitigation fee.

ROAD SYSTEMS AND OTHER TRANSPORTATION FACILITIES

Regulatory Reference: 30 CFR Sec. 784.24, 817.150, 817.151; R645-301-521, -301-527, -301-534, -301-732.

Analysis:

Road Classification System

In conjunction with the proposed mining and related operations Cyprus will construct, operate and maintain a number of new roads and will operate and maintain several existing roads. Both new and existing roads will be utilized to access existing and proposed facilities and for transportation of personnel, equipment, and supplies. All roads were classified as primary on or before April 4, 1996. Given that both coal and mine development waste will be transported by conveyor, the only road to be utilized for transportation of mine waste or coal processing waste will be Road PR-4 from the Castle Gate Preparation Plant to the Schoolhouse Canyon coal refuse stockpile. There are, however, several other roads which will be utilized on a frequent, long-term basis to support the proposed mining and related operations. Existing and proposed roads which will be used in conjunction with the proposed mining and related operations include the following:

TECHNICAL ANALYSIS

Last revised - April 22, 1996

Proposed Roads in Willow Creek Facilities Area

- PR-1 Primary mine access road for the proposed surface facilities area
- PR-2 Primary mine access road to the Willow Creek run-of-mine coal stockpile area
- AR-1 Ancillary access road to the mine water and firefighting reserve tank installation
- AR-2 Ancillary access road to the mine ventilation fan area
- AR-3 Ancillary access road to Sedimentation Pond 001 and Conveyor SC-4
- AR-4 Ancillary access road to the Willow Creek soil/substitute stockpile and explosive storage area

Existing Roads in Castle Gate Preparation Plant and Loadout Areas

- PR-3 Primary access road for the preparation plant and loadout areas
- PR-4 Primary access road to the Schoolhouse canyon coal refuse facility
- AR-5 Ancillary access road to the west end of Rock Tunnel No. 2 and the transfer point between Conveyors SC-5 and SC-6
- AR-6 Ancillary access road to the truck dump grizzly

Existing Road in Gravel Canyon Soil Stockpile Area

- AR-7 Ancillary access road to the Gravel Canyon soil stockpile

Existing Road in Crandall Canyon Facilities Area

- AR-8 Ancillary access road to Crandall Canyon facilities area

All existing and proposed roads are shown on the Mine Surface Facilities Map (Map 18) and in Exhibit 20, Crandall Canyon Operations Plans.

The Operator has listed and classified all the proposed and existing roads as primary.

Plans and Drawings

Road Maps, Appropriate Cross Sections, Design Drawings

Map 18, Mine Surface Facilities, shows the location of the primary and ancillary roads in the Willow Creek area. Cross sections for the primary roads are shown in Figure 4.5-9. The cross sections show the road widths, gradients and surfacing materials.

The Operator has stated in the PAP that:

Primary roads have been or will be located and constructed to the extent operationally feasible in the most stable areas available and outside of the channel of intermittent or perennial streams. Road design and construction plans will prevent damage to public or private property; minimize the potential for downstream flooding or sedimentation; reflect consideration of the size of vehicles which will be using the road, traffic volume, and normal speeds; and to the extent possible, using the best technology currently available, minimize adverse impacts on fish, wildlife and related environmental values. All roads have been designed to provide for effective drainage, long-term stability, and safe vehicle operations

TECHNICAL ANALYSIS

under varying weather conditions. Design and construction of all primary roads will be certified by a qualified Registered Professional Engineer as meeting these criteria.

Design and construction practices for specific roads will be dependent primarily on site conditions and the nature and frequency of anticipated use. The primary mine access road (PR-1) will provide access to most of the mine surface facilities and will be utilized for transportation of personnel, equipment, and supplies. Because it will handle a relatively heavy traffic volume and must provide safe operating conditions year-round, Road PR-1 will be a paved asphalt road with an all-weather travel surface. The other primary roads will also be utilized on a year-round basis but the associated traffic levels will be significantly lower so these roads have been designed and either are or will be constructed with an adequate compacted road base and gravel or similar durable granular surfacing.

Road construction will involve cut and fill earthwork operations using tractor scrapers, tracked dozers, and motor graders. Cut and fill slopes will be established at maximum grades of 2.5H:1V except in rock where slopes may be as steep as 0.5H:1V dependent on the characteristics of the rock. Typical road construction practices, road configuration, and dimensions for the two road classifications are illustrated by Figures 4.5-9 and 4.5-10, Typical Primary Road Configuration, and Typical Ancillary Road Configuration, respectively. Road gradients will vary from flat to a maximum of approximately 10 percent and any required road embankments will be constructed and compacted in a controlled manner to provide a minimum static factor of safety of 1.3. All roads cut and fill slopes will be revegetated as soon as reasonably practical following construction using the temporary revegetation seed mixture to stabilize the slopes and minimize erosion potential. Road surfaces will be graded or crowned to prevent accumulations of water on the road surface and adequately sized ditches and culverts will be installed and maintained to effectively carry road and other disturbed area drainage. Adequate cover will be provided over all culvert crossings to prevent damage or collapse of the culverts and culverts have been designed and will be installed to prevent plugging, erosion at the culvert inlet or outlet, and any drainage over the road surface. The locations of all proposed ditches are shown on the Drainage and Sediment Control Plan Maps, (Maps 23A through 23F) and ditch designs are included in Exhibit 13, Drainage and Sediment Control Plan.

Alteration or Relocation of a Natural Stream Channel

Road PR-1, Willow Creek Stream Buffer Area and Stream Protection Berm, Main Road Culvert Crossing, and Main Access Road Bridge - The main mine access road (Road PR-1) will cross Willow Creek in two locations and will parallel the creek for almost the entire length of the proposed surface facilities area. Because construction of this road will involve crossing, alteration, and relocation of portions of a natural drainage way, specific UDOGM approvals under applicable provisions of Rules R645-301-527.220 and 742.412. It should be noted that much of the Willow Creek channel through the proposed mine surface facilities area has

TECHNICAL ANALYSIS

Last revised - April 22, 1996

previously been relocated and modified and so does not represent a natural undisturbed stream channel. Where Road PR-1 parallels Willow Creek, a stream protection berm approximately three feet high with 3H:1V side slopes will be constructed along the edge of the road or any associated roadside ditch on the side nearest the stream. This berm will provide a means of physically separating the proposed mining and related activities from the stream and will serve as one edge of a restricted access stream buffer zone.

The Division has given tentative approval for the stream alteration. There are no outstanding engineering issues involved with the stream relocation.

Removal and Reclamation of Roads Not Retained under an Approved Postmining Land Use

Certain roads within the mine facilities area will continue to provide access to specific areas during both reclamation and the extended liability period, although most roads will be removed and reclaimed during final site reclamation. Generally, the primary access roads will be removed and reclaimed in two phases. The first phase will involve ripping of these roads and removal of the associated road surfacing materials. This phase will occur in conjunction with facility demolition and removal and the surfacing materials removed will be placed in the designated solid waste disposal areas as previously discussed. The second phase of road removal for primary roads and removal and reclamation of all other roads will be sequenced to coincide with backfilling and grading of the areas that the roads either provide access to or pass through. When roads are no longer needed, they will be removed and the associated disturbance areas will be regraded and reclaimed.

Road reclamation will generally involve the use of tracked dozers to rip the road surface and grade any surfacing material into piles which will normally be recovered by wheel loader and either hauled directly or loaded into trucks for haulage to one of the designated disposal areas. Road surfaces will then be ripped to alleviate any compaction and the road area will be graded to blend with surrounding reclaimed areas. During final grading, any culverts will be removed and transported to a temporary steel debris storage site for either salvage or disposal off-site. Cut/fill areas will be reclaimed by pulling the fill material up slope into the cut and grading any remaining cut slope, the fill material, and disturbed down slope areas to a stable configuration consistent with natural drainage patterns and blending with the surrounding terrain. Any major road cuts will be reclaimed by partially backfilling the cut and grading any remaining cut slope exposures so that they are stable as described in the backfilling and grading plan discussion. Any major road fills which would interfere with postmining drainage will be removed and the associated disturbance areas regraded in conjunction with overall site grading activities.

Performance Standards

In the PAP the Operator states:

Operation and maintenance procedures for all mine roads are designed to provide a smooth operating surface, assure safety, and minimize dust emissions. Road maintenance will involve periodic grading to provide a smooth surface, remove rocks or debris, and maintain effective drainage; repair and resurfacing as necessary; inspection, clean-out; and repair of ditches and drainage structures; and watering or application of surfactants to control dust during dry periods.

TECHNICAL ANALYSIS

Generally, speeds on roads and in active operating areas will be limited to 25 miles per hour by posted speed limits both as a safety consideration and to minimize dust emissions from unpaved roads. In the unlikely event that any road is damaged by a catastrophic event such as an earthquake or flood, Cyprus will make appropriate repairs as soon as reasonably practicable and will limit the use of the road or provide an alternate access if unsafe conditions exist.

Findings:

The Permittee has met the minimum regulatory requirements.

SPOIL AND WASTE MATERIALS

Regulatory Reference: 30 CFR Sec. 701.5, 784.19, 784.25, 817.71, 817.72, 817.73, 817.74, 817.81, 817.83, 817.84, 817.87, 817.89; R645-100-200, -301-210, -301-211, -301-212, -301-412, -301-512, -301-513, -301-514, -301-521, -301-526, -301-528, -301-535, -301-536, -301-542, -301-553, -301-745, -301-746, -301-747.

Analysis:

Disposal of Noncoal Mine Wastes

Noncoal wastes generated in conjunction with mining and related activities will include, but not be limited to, waste oil and lubricants, garbage, paper waste, machinery parts, tires, cable, wood waste, and other miscellaneous debris. All smaller noncoal solid wastes will be collected and stored in dumpsters or similar closed containers. Larger solid waste materials including such items as used equipment, machinery parts, tires, and cable will be temporarily stored in a designated scrap yard located in the equipment storage area as shown on the Mine Surface Facilities Map (Map 18). Most of the waste oil from the maintenance shop facility will be collected in a waste oil sump and recycled to one of two waste oil storage tanks for use in the shop facility waste oil heater. The waste oil will be mixed with fuel oil only after sampling and analysis to verify that the waste oil meets strict EPA requirements. Waste oil and fuel oil feed rate and mixture will be adjusted as necessary based on waste oil availability and shop heating requirements. Any waste other waste oil and lubricants and any waste oil not meeting the applicable EPA requirements will be collected and stored in either closed drums or in the waste oil storage tank located in the maintenance shop building. Temporary storage areas for waste oil and lubricants will provide full containment to prevent accidental release of petroleum products to the surface drainage system.

A contract disposal service will regularly collect and haul the noncoal solid wastes from the dumpsters to the permitted Carbon County municipal landfill. Dependent on the market for scrap materials, the larger noncoal solid waste and scrap will be collected periodically either by a salvage contractor for salvage and recycling or by a contract disposal firm which will haul these material off-site and dispose of it in a suitable disposal site. Any waste oil, lubricants, or other potentially combustible materials will be collected and either recycled or disposed of by a licensed disposal contractor in accordance with all applicable Utah and EPA regulations. No noncoal wastes will be disposed of on site during active operations except for mining waste generated in the mining process. As described in the previous section, this material will be disposed of in the Schoolhouse Canyon coal refuse stockpile.

TECHNICAL ANALYSIS

Last revised - April 22, 1996

Cyprus does not currently plan or anticipate that any materials classified as "hazardous waste" will be utilized or generated in conjunction with the proposed mining and related operations. In the unlikely event that hazardous material's storage or disposal becomes necessary, Cyprus will comply with all applicable storage, labeling, and documentation requirements, and disposal will occur off-site at a licensed hazardous waste disposal facility.

Coal Mine Waste

Mine development, ongoing mining operations, and ancillary operations such as development of overcasts for mine ventilation and coal haulage will result in production of mine waste including waste rock, carbonaceous shale, weathered coal, floor clay, and parting material. Where it is operationally feasible to separate these material from the coal during development and mining, the mine waste will be removed and handled separately from the coal. Where separation is not operationally feasible, mine waste will be handled with the coal and will be removed in the coal preparation plant.

Generally, the same mining equipment and haulage systems used for coal production will be used to remove and handle mine waste. Continuous miners, electric shuttle cars, and LHD scoops will be used to load and haul mine waste to the mine conveyor system. Normally waste haulage will occur on a scheduled waste handling shift when the conveyor belt system will be cleared of coal. Typically, any waste produced during periods other than on a scheduled waste handling shift will be temporarily stockpiled in an inactive area underground for later handling and haulage from the mine. Once the mine waste is placed on a belt at the loading point, it will be transferred to the main haulage belt running from the mine. From the main haulage belt, the mine waste will transfer to the surface coal haulage system which will carry the waste to the primary crusher building.

The surface coal haulage system and preparation plant have been designed to facilitate waste handling. The stacking tube at the run-of-mine coal stockpile can be emptied by a direct feed chute in its base allowing waste to bypass the coal stockpile and feed directly to Conveyor SC-1. In the primary crusher building a flop-gate and diversion chute will allow mine waste to bypass the primary crusher and feed directly to the mine waste temporary stockpile. From this stockpile Cyprus will use a wheel loader and rear dump trucks to load and haul the mine waste to the existing permitted Schoolhouse Canyon refuse stockpile. In the refuse stockpile area, mine waste will be handled and placed in essentially the same way as coal refuse material as discussed in the subsequent subsection titled Coal Processing Waste Handling and Disposal.

The Operator proposes to dispose of coal mine waste in sites already permitted for this activity. To avoid confusion the Operator should show that the Schoolhouse Canyon refuse stockpile has been permitted to accept material from the Willow Creek Mine.

On September 15, 1995, the Division approved a permit revision to the existing approved Castle Gate Mine Permit involving placement of materials from the Willow Creek area in the existing Schoolhouse Canyon Refuse Facility.

Refuse Piles

Refuse will be stored at the existing and permitted Schoolhouse Canyon facility.

TECHNICAL ANALYSIS

Impounding Structures

The Operator's designs for pond construction are:

Pond construction will follow the regulatory guidelines as outlined in R645-301-533. The initial step in embankment construction is the removal of all organic materials from the foundation area. This will occur in conjunction with topsoil recovery operations as described in Section 4, Engineering Design and Operation Plans. Foundation areas will be graded to achieve maximum 1:1 slopes.

On-site borrow materials will be utilized for fill for the construction of pond embankments. Fill material shall be selectively handled to exclude organic material, frozen soils, and other unsuitable materials. Coal processing wasters may be used as embankment fill material

Fill materials for pond embankment construction will be placed in horizontally continuous lifts beginning at the base of the structure. In using fin-grained soils, lift thickness should not exceed 12 inches. Material should be compacted to at least 95% of the maximum dry density as defined by the standard Proctor test, with the placement of water content not exceeding the range of -2 to +3% of optimum.

At a minimum, the top width of each pond will not be less than 20% of the sum of the height, in feet of the embankment measured at the upstream toe plus 10 feet. The embankment cross sections are shown on the Sedimentation Pond Designs Maps 24, 25 and 26.

Design specifications for embankment height provide for a minimum of 1.0 feet freeboard between the top of the embankment and the emergency spillway flow level, and an additional 5% factor of safety to offset any settling which might occur. The 5% settling factor is conservative, because construction plans specify compaction of the horizontally continuous lift embankment fills. The compaction should all but eliminate settling.

Tests need to be performed during the construction of pond embankments to determine compliance with moisture-density specifications. At a minimum, one field test for every 2,000 cubic yards of compacted structural fill, with at least one test per lift; one field test for every 200 cubic yards of compacted backfill in trenches or around structures with at least one test per lift; supplementary laboratory compaction curves for at least every 20 field density tests.

Burning and Burned Waste Utilization

The Operator stated that:

In the unlikely event that any burning waste is found during regular inspection of waste stockpile areas, it will be separated and extinguished either by burying the burning material or by using water sprays from the mine water truck. Once extinguished, the material will be placed, compacted, and buried on an active waste stockpile bench. All future material placement,