


**State of Utah**  
**DEPARTMENT OF NATURAL RESOURCES**  
**Division of Oil, Gas & Mining**

1594 West North Temple, Suite 1210, PO Box 145801, Salt Lake City, UT 84114-5801  
 Telephone (801) 538-5340 facsimile (801) 359 3940 TTY (801) 538-7458  
[www.ogm.utah.gov](http://www.ogm.utah.gov)



**Quarterly Inspection Form - Refuse Disposal Areas**

(please provide to DOGM promptly after inspection is complete)

Permit Number : C/025/0005 Inspection Date : 06/28/16  
 Mine Name : Coal Hollow Project Quarter / Year : 2nd / 2016  
 Mine Operator (Permittee) : Alton Coal Development Inspector Name : Dan W. Guy  
 MSHA ID # : 42-02519 Inspector Signature :   
 Facility Name / Location / Address : 2060 South Alton Road, Alton, UT 84710

1. Describe any changes in the geometry of the structure (as well as instrumentation, if any, used to monitor changes):  
Removing spoil to Highwall Miner Trench 2. Sub Soil has been pushed to the south.

2. Lift Height / Thickness Avg 4.0' Maximum 4.0' # \_\_\_\_\_ Elevation of Active Benches : 6918 , \_\_\_\_\_ , \_\_\_\_\_

3. Vertical Angle of Outslope(s) / Location(s) where measured 3H:1V Avg. / No. Slope / So. Slope / \_\_\_\_\_ / \_\_\_\_\_

4. Total storage capacity: 8,600,000 cy Remaining storage capacity 8,211,000 cy Volume placed during year : 0

5. Describe foundation preparation (including removal of vegetation, stumps, topsoil, and all other organic material) :  
Topsoil and subsoil removed and stored on site.

6. Describe placement and compaction of fill materials (including an explanation of how compaction is confirmed) :  
Dumped by truck / Pushed by dozer / Compaction primarily from large trucks / Tested with nuclear density unit.

7. Is there any evidence of fires or burning on the structure ? (If YES, specify extent, location, and abatement/extinguishment of such fires) :  
None

8. Describe placement of under drains, protective filter systems, and final surface drainage systems (report any seepage, including location, color, flow) :  
None

9. Describe any appearances of instability, structural weakness, or other hazardous conditions :  
No instability noted.

10. Please provide any other information pertaining to the stability of the structure (attach any photos taken during the inspection)

Are there cracks or scarps in crest ?	YES <input type="checkbox"/>	NO <input checked="" type="checkbox"/>
Is there any detectable sloughing or bulging ?	YES <input type="checkbox"/>	NO <input checked="" type="checkbox"/>
Do slope erosion problems exist ?	YES <input type="checkbox"/>	NO <input checked="" type="checkbox"/>
Cracks or scarps in slope ?	YES <input type="checkbox"/>	NO <input checked="" type="checkbox"/>
Surface movements? (valley bottom, hillsides)	YES <input type="checkbox"/>	NO <input checked="" type="checkbox"/>
Erosion of Toe ?	YES <input type="checkbox"/>	NO <input checked="" type="checkbox"/>
Water impounded by structure ?	YES <input type="checkbox"/>	NO <input checked="" type="checkbox"/>
Are diversion ditches stable?	YES <input checked="" type="checkbox"/>	NO <input type="checkbox"/>
Is drainage positive ?	YES <input checked="" type="checkbox"/>	NO <input type="checkbox"/>

Could failure of structure create an impoundment (provide description) ? Possible small impoundment in swale below. Any impoundment would not present a major safety hazard due to location.

Are design standards established within the mining and reclamation plan for the disposal facility being met ?  
Yes

Proctor Determination : 88% minimum - 98% maximum compaction as determined by nuclear density tests on 5/13/13.

I hereby certify that: I am experienced in the construction of earth and rock fills; I am qualified and authorized in the State of Utah to inspect and certify the condition and appearance of earth and rock fills in accordance with structure; that the fill structure has been maintained in accordance with the approved design and meets or exceeds the minimum design requirements under all applicable federal, state, and local regulations; and, that inspections and inspection reports are made by myself or under my direction and include any appearances of instability, structural weakness or other hazardous conditions of the structure affecting stability.

(place P.E. certification below)



**State of Utah**  
**DEPARTMENT OF NATURAL RESOURCES**  
**Division of Oil, Gas & Mining**

1594 West North Temple, Suite 1210, PO Box 145801, Salt Lake City, UT 84114-5801  
 Telephone (801) 538-5340 facsimile (801) 359 3940 TTY (801) 538-7458  
[www.ogm.utah.gov](http://www.ogm.utah.gov)



**Quarterly Inspection Form - Refuse Disposal Areas**

(please provide to DOGM promptly after inspection is complete)

Permit Number : C/025/0005 Inspection Date : 06/28/16  
 Mine Name : Temporary Spoil Pile - North Private Leas Quarter / Year : 2nd / 2016  
 Mine Operator (Permittee) : Coal Hollow Project - Alton Coal Develo Inspector Name : Dan W. Guy  
 MSHA ID # : 42-02519 Inspector Signature : *[Signature]*  
 Facility Name / Location / Address : 2060 South Alton Road, Alton, UT 84710

1. Describe any changes in the geometry of the structure (as well as instrumentation, if any, used to monitor changes):  
Pile started in 1st quarter of 2016. Approximately 274,300 cubic yards in place.

2. Lift Height / Thickness Avg 4.0' Maximum 4.0' # \_\_\_\_\_ Elevation of Active Benches : 6900 , \_\_\_\_\_ , \_\_\_\_\_  
 3. Vertical Angle of Outslope(s) / Location(s) where measured N/A Not Graded / \_\_\_\_\_ / \_\_\_\_\_  
 4. Total storage capacity: 506,000 cy Remaining storage capacity 231,700 cy Volume placed during year : 274,300 cy  
 5. Describe foundation preparation (including removal of vegetation, stumps, topsoil, and all other organic material) :  
Vegetation removed. Topsoil and subsoil removed and stored on site. Orange marker placed beneath active pile area as required.

6. Describe placement and compaction of fill materials (including an explanation of how compaction is confirmed) :  
Dumped by truck. Graded and pushed by dozer. Compaction primarily from large truck.s, and tested with nuclear density unit.

7. Is there any evidence of fires or burning on the structure ? (If YES, specify extent, location, and abatement/extinguishment of such fires) :  
None

8. Describe placement of under drains, protective filter systems, and final surface drainage systems (report any seepage, including location, color, flow) :  
None

9. Describe any appearances of instability, structural weakness, or other hazardous conditions :  
No instability noted.

10. Please provide any other information pertaining to the stability of the structure (attach any photos taken during the inspection)

Are there cracks or scarps in crest ?	YES <input type="checkbox"/>	NO <input checked="" type="checkbox"/>	_____
Is there any detectable sloughing or bulging ?	YES <input type="checkbox"/>	NO <input checked="" type="checkbox"/>	_____
Do slope erosion problems exist ?	YES <input type="checkbox"/>	NO <input checked="" type="checkbox"/>	_____
Cracks or scarps in slope ?	YES <input type="checkbox"/>	NO <input checked="" type="checkbox"/>	_____
Surface movements? (valley bottom, hillsides)	YES <input type="checkbox"/>	NO <input checked="" type="checkbox"/>	_____
Erosion of Toe ?	YES <input type="checkbox"/>	NO <input checked="" type="checkbox"/>	_____
Water impounded by structure ?	YES <input type="checkbox"/>	NO <input checked="" type="checkbox"/>	_____
Are diversion ditches stable?	YES <input checked="" type="checkbox"/>	NO <input type="checkbox"/>	_____
Is drainage positive ?	YES <input checked="" type="checkbox"/>	NO <input type="checkbox"/>	_____

Could failure of structure create an impoundment (provide description) ? No

Are design standards established within the mining and reclamation plan for the disposal facility being met ?  
Yes

Proctor Determination : 4 Compaction Tests on 6/22/16. Results range from 90% to 94% Compaction.

I hereby certify that: I am experienced in the construction of earth and rock fills; I am qualified and authorized in the State of Utah to inspect and certify the condition and appearance of earth and rock fills in accordance with structure; that the fill structure has been maintained in accordance with the approved design and meets or exceeds the minimum design requirements under all applicable federal, state, and local regulations; and, that inspections and inspection reports are made by myself or under my direction and include any appearances of instability, structural weakness or other hazardous conditions of the structure affecting stability.

(place P.E. certification below)

IMPOUNDMENT INSPECTION AND REPORT		
Permit Number	C/025/0005	6/17/2016
Mine Name	Coal Hollow Mine	
Company Name	Alton Coal Development, LLC	
Impoundment Identification	Impoundment Name	Pond 1
	Impoundment Number	Pond 1
	MSHA Mine ID Number	42-02519
IMPOUNDMENT INSPECTION		
Inspection Date	16-Jun-16	
Inspected By	K. Nicholes	
Reason for Inspection (Annual, Quarterly or Other Periodic Inspections, Critical Installation, or Completion of Construction)	Quarterly Inspection.	
1. Describe any appearance of any instability, structural weakness, or any other hazardous condition. N/A - None Noted.		
Required for an impoundment which functions as a SEDIMENTATION POND.	2. Sediment storage capacity, including elevation of 60% and 100% sediment storage volumes, and estimated average elevation of existing sediment. Sediment Storage Capacity: 60 % Elevation: 6913 (1.26') 100% Elevation: 6912 (2.03')  The pond contained approximately 0.5' of water. The sediment marker is in place, and field observation shows the sediment level to be well below the cleanout elevation. The sediment level is estimated to be at approximately elevation 6912.5.	
	3. Principle and emergency spillway elevations. Principle and Emergency Spillway Elevation: <b>6920 feet</b> (The outlet structure for Pond 1 serves as both the Principle and Emergency Spillways) Total volume of pond at Spillway: <b>3.1 Acre-Feet</b> (Elev. 6920.00') Required runoff storage: <b>2.57 Acre-Feet</b>	

4. **Field Information.** Provide current water elevation, whether pond is discharging, type and number of samples taken, monitoring/instrumentation information, inlet/outlet conditions or other related activities associated with the pond decanting, embankment erosion/repairs, monitoring information, vegetation on outlooses of embankments, etc.

The water level is approximately at elevation 6913. The pond is not discharging. Embankments are stable and well vegetated.

5. **Field Evaluation.** Describe any changes in the geometry of the structure, average and maximum depths and elevations of impounded water, estimated sediment or slurry volume and remaining storage capacity, estimated volume of water impounded, and any other aspect of the impounding structure affecting its stability or function which has occurred during the reporting period.

The only noted changes in the structure during the 2nd quarter, was a decrease in the depth of the water.

**Certification Statement**

I hereby certify that: I am experienced in the construction of impoundments; I am qualified and authorized under the direction of a Registered Professional Engineer to inspect the condition and appearance of impoundments in accordance with the certified and approved designs for this structure; that the impoundment has been maintained in accordance with approved design and meet or exceed the minimum design requirements under all applicable federal, state and local regulations: and, that inspections and inspection reports are made by myself, or under my direction and include any appearances of instability, structural weakness or other hazardous conditions of the structure affecting stability.

**By:**

(Full Name and Title)

Signature: *R. K. Whish*

Date: 06/17/2016

IMPOUNDMENT INSPECTION AND REPORT			
Permit Number	C/025/0005	Report Date	06/17/2016
Mine Name	Coal Hollow Mine		
Company Name	Alton Coal Development, LLC		
Impoundment Identification	Impoundment Name	Pond 1B	
	Impoundment Number	Pond 1B	
	MSHA Mine ID Number	42-02519	
IMPOUNDMENT INSPECTION			
Inspection Date	16-Jun-16		
Inspected By	B. K. Nicholes		
Reason for Inspection (Annual, Quarterly or Other Periodic Inspections, Critical Installation, or Completion of Construction)	Quarterly Inspection.		
<p>1. Describe any appearance of any instability, structural weakness, or any other hazardous condition.</p> <p>N/A - No appearance of any instability, structural weakness or other hazardous condition was noted.</p>			
Required for an impoundment which functions as a SEDIMENTATION POND.	<p>2. Sediment storage capacity, including elevation of 60% and 100% sediment storage volumes, and estimated average elevation of existing sediment.</p> <p>Sediment Storage Capacity:  60 % Elevation: 6900.00 (6.00')  100% Elevation: 6902.08 (8.08')</p> <p>The pond was dry at the time of inspection. The sediment marker is in place. Field observation shows the sediment level to be well below the cleanout elevation. The approximate sediment elevation is 6898.0. Inlets have been cleaned.</p>		
	<p>3. Principle and emergency spillway elevations.</p> <p>Principle and Emergency Spillway Elevation: 6906 feet (The outlet structure for Pond 1B serves as both the Principle and Emergency Spillways)</p> <p>Total volume of pond at Spillway: 0.894 Acre-Feet (Elev. 6906.45)</p> <p>Required runoff storage: 0.50 Acre-Feet</p>		

4. **Field Information.** Provide current water elevation, whether pond is discharging, type and number of samples taken, monitoring/instrumentation information, inlet/outlet conditions or other related activities associated with the pond decanting, embankment erosion/repairs, monitoring information, vegetation on outslopes of embankments, etc.

There was no water at the time of inspection. There are 2 inlets to the pond - both have been rip-rapped. Both inlets appear stable and are functioning properly. Both inlets have been cleaned. The outlet is also open and functional.

5. **Field Evaluation.** Describe any changes in the geometry of the structure, average and maximum depths and elevations of impounded water, estimated sediment or slurry volume and remaining storage capacity, estimated volume of water impounded, and any other aspect of the impounding structure affecting its stability or function which has occurred during the reporting period.

The only change to the pond since the last inspection is the pond is dry.

**Certification Statement**

I hereby certify that: I am experienced in the construction of impoundments; I am qualified and authorized under the direction of a Registered Professional Engineer to inspect the condition and appearance of impoundments in accordance with the certified and approved designs for this structure; that the impoundment has been maintained in accordance with approved design and meet or exceed the minimum design requirements under all applicable federal, state and local regulations: and, that inspections and inspection reports are made by myself, or under my direction and include any appearances of instability, structural weakness or other hazardous conditions of the structure affecting stability.

**By:**

(Full Name and Title)

Signature: B. Keith White Date: 06/17/2018

IMPOUNDMENT INSPECTION AND REPORT		
Permit Number	C/025/0005	6/17/2016
Mine Name	Coal Hollow Mine	
Company Name	Alton Coal Development, LLC	
Impoundment Identification	Impoundment Name	Pond 2
	Impoundment Number	Pond 2
	MSHA Mine ID Number	42-02519
IMPOUNDMENT INSPECTION		
Inspection Date	16-Jun-16	
Inspected By	B. K.Nicholes	
Reason for Inspection (Annual, Quarterly or Other Periodic Inspections, Critical Installation, or Completion of Construction)	Quarterly Inspection.	
<p>1. Describe any appearance of any instability, structural weakness, or any other hazardous condition.</p> <p>N/A - No appearance of any instability, structural weakness or other hazardous condition was noted.</p>		
Required for an impoundment which functions as a SEDIMENTATION POND.	<p>2. Sediment storage capacity, including elevation of 60% and 100% sediment storage volumes, and estimated average elevation of existing sediment.</p> <p>Sediment Storage Capacity:</p> <p>60 % Elevation: 6894.07 (3.07')</p> <p>100% Elevation: 6895.72 (4.72')</p> <p>The pond contained approximately 1.0' of water. The sediment marker is in place, and field observation shows the sediment level to be well below the cleanout elevation. The approximate sediment elevation is 6891.5.</p>	
	<p>3. Principle and emergency spillway elevations.</p> <p>Principle and Emergency Spillway Elevation: 6900 feet (The outlet structure for Pond 2 serves as both the Principle and Emergency Spillways)</p> <p>Total volume of pond at Spillway: 2.675 Acre-Feet (Elev. 6901.09')</p> <p>Required runoff storage: 1.70 Acre-Feet</p>	

4. **Field Information.** Provide current water elevation, whether pond is discharging, type and number of samples taken, monitoring/instrumentation information, inlet/outlet conditions or other related activities associated with the pond decanting, embankment erosion/repairs, monitoring information, vegetation on outslopes of embankments, etc.

The water level is approximately at elevation 6892.5. The single pond inlet is rip-rapped and has some sediment accumulation.

5. **Field Evaluation.** Describe any changes in the geometry of the structure, average and maximum depths and elevations of impounded water, estimated sediment or slurry volume and remaining storage capacity, estimated volume of water impounded, and any other aspect of the impounding structure affecting its stability or function which has occurred during the reporting period.

The only changes in the pond since the last inspection was the decrease in water level and repair of the leak at the outlet pipe.

**Certification Statement**

I hereby certify that: I am experienced in the construction of impoundments; I am qualified and authorized under the direction of a Registered Professional Engineer to inspect the condition and appearance of impoundments in accordance with the certified and approved designs for this structure; that the impoundment has been maintained in accordance with approved design and meet or exceed the minimum design requirements under all applicable federal, state and local regulations: and, that inspections and inspection reports are made by myself, or under my direction and include any appearances of instability, structural weakness or other hazardous conditions of the structure affecting stability.

**By:**

(Full Name and Title)

Signature: *D. K. [Signature]* Date: 06/17/2016

IMPOUNDMENT INSPECTION AND REPORT		
Permit Number	C/025/0005	6/17/2016
Mine Name	Coal Hollow Mine	
Company Name	Alton Coal Development, LLC	
Impoundment Identification	Impoundment Name	Pond 3
	Impoundment Number	Pond 3
	MSHA Mine ID Number	42-02519
IMPOUNDMENT INSPECTION		
Inspection Date	16-Jun-16	
Inspected By	B.K. Nicholes	
Reason for Inspection (Annual, Quarterly or Other Periodic Inspections, Critical Installation, or Completion of Construction)	Quarterly Inspection.	
<p>1. Describe any appearance of any instability, structural weakness, or any other hazardous condition.</p> <p>No instability or hazardous conditions were noted.</p>		
Required for an impoundment which functions as a SEDIMENTATION POND.	<p>2. Sediment storage capacity, including elevation of 60% and 100% sediment storage volumes, and estimated average elevation of existing sediment.</p> <p>Sediment Storage Capacity:  60 % Elevation: 6807.80 (7.74')  100% Elevation: 6808.50 (8.44')</p> <p>The pond contained approximately 0.6' of water. The sediment marker is in place, and field observation shows the sediment level to be well below the cleanout elevation. The approximate average sediment elevation is 6803. An additional mine water discharge pipe has been added at the upper edge of the pond.</p>	
	<p>3. Principle and emergency spillway elevations.</p> <p>Principle and Emergency Spillway Elevation: 6811 feet (The outlet structure for Pond 3 serves as both the Principle and Emergency Spillways)  Total volume of pond at Spillway: 12.96 Acre-Feet (Elev. 6811.00')  Required runoff storage: 6.72 Acre-Feet  Decant Elevation: 6808.0</p>	

4. **Field Information.** Provide current water elevation, whether pond is discharging, type and number of samples taken, monitoring/instrumentation information, inlet/outlet conditions or other related activities associated with the pond decanting, embankment erosion/repairs, monitoring information, vegetation on outlopes of embankments, etc.

The water level is approximately at elevation 6803.6'. A decant has been installed at elevation 6808.0.

5. **Field Evaluation.** Describe any changes in the geometry of the structure, average and maximum depths and elevations of impounded water, estimated sediment or slurry volume and remaining storage capacity, estimated volume of water impounded, and any other aspect of the impounding structure affecting its stability or function which has occurred during the reporting period.

The only change since the last inspection is the decrease in the water level and some of the sediment has been removed from the inlet of ditch 4.

**Certification Statement**

I hereby certify that: I am experienced in the construction of impoundments; I am qualified and authorized under the direction of a Registered Professional Engineer to inspect the condition and appearance of impoundments in accordance with the certified and approved designs for this structure; that the impoundment has been maintained in accordance with approved design and meet or exceed the minimum design requirements under all applicable federal, state and local regulations: and, that inspections and inspection reports are made by myself, or under my direction and include any appearances of instability, structural weakness or other hazardous conditions of the structure affecting stability.

**By:**

(Full Name and Title)

Signature: B. K. Whelan Date: 06/17/06

IMPOUNDMENT INSPECTION AND REPORT			
Permit Number	C/025/0005	Report Date	06/17/2016
Mine Name	Coal Hollow Mine		
Company Name	Alton Coal Development, LLC		
Impoundment Identification	Impoundment Name	Pond 4	
	Impoundment Number	Pond 4	
	MSHA Mine ID Number	42-02519	
IMPOUNDMENT INSPECTION			
Inspection Date	16-Jun-16		
Inspected By	B.K. Nicholes		
Reason for Inspection (Annual, Quarterly or Other Periodic Inspections, Critical Installation, or Completion of Construction)	Quarterly Inspection.		
<p>1. Describe any appearance of any instability, structural weakness, or any other hazardous condition.</p> <p>No instability of the embankment or hazardous condition was noted during the inspection.</p>			
Required for an impoundment which functions as a SEDIMENTATION POND.	<p>2. Sediment storage capacity, including elevation of 60% and 100% sediment storage volumes, and estimated average elevation of existing sediment.</p> <p>Sediment Storage Capacity:  60 % Elevation: 6832.0 (3.78')  100% Elevation: 6833.0 (4.82')</p> <p>The pond contained approximately 0.5' of water . The sediment marker is in place, and field observation shows the sediment level to be well below the cleanout elevation. The bottom of pond and approximate sediment elevation is 6828.7.</p>		
	<p>3. Principle and emergency spillway elevations.</p> <p>Principle and Emergency Spillway Elevation: 6834 feet (The outlet structure for Pond 4 serves as both the Principle and Emergency Spillways)</p> <p>Total volume of pond at Spillway: 5.50 Acre-Feet (Elev. 6834.00')</p> <p>Required runoff storage: 2.10 Acre-Feet</p>		

4. **Field Information.** Provide current water elevation, whether pond is discharging, type and number of samples taken, monitoring/instrumentation information, inlet/outlet conditions or other related activities associated with the pond decanting, embankment erosion/repairs, monitoring information, vegetation on outlopes of embankments, etc.

The average water elevation is approximately 6829.0. The open-channel spillway is in place and riprapped. No discharge.

5. **Field Evaluation.** Describe any changes in the geometry of the structure, average and maximum depths and elevations of impounded water, estimated sediment or slurry volume and remaining storage capacity, estimated volume of water impounded, and any other aspect of the impounding structure affecting its stability or function which has occurred during the reporting period.

The only change since the last inspection is the water elevation has decreased.

**Certification Statement**

I hereby certify that: I am experienced in the construction of impoundments; I am qualified and authorized under the direction of a Registered Professional Engineer to inspect the condition and appearance of impoundments in accordance with the certified and approved designs for this structure; that the impoundment has been maintained in accordance with approved design and meet or exceed the minimum design requirements under all applicable federal, state and local regulations: and, that inspections and inspection reports are made by myself, or under my direction and include any appearances of instability, structural weakness or other hazardous conditions of the structure affecting stability.

**By: Dan W. Guy, P.E.**

(Full Name and Title)

Signature:  Date: 06/17/2016

IMPOUNDMENT INSPECTION AND REPORT		
Permit Number	C/025/0005	6/17/2016
Mine Name	Coal Hollow Mine	
Company Name	Alton Coal Development, LLC	
Impoundment Identification	Impoundment Name	Pond 5
	Impoundment Number	Pond 5
	MSHA Mine ID Number	42-02519
IMPOUNDMENT INSPECTION		
Inspection Date	16-Jun-16	
Inspected By	B.K.Nicholes	
Reason for Inspection (Annual, Quarterly or Other Periodic Inspections, Critical Installation, or Completion of Construction)	Quarterly Inspection.	
<p>1. Describe any appearance of any instability, structural weakness, or any other hazardous condition.</p> <p>No instability of the embankment or hazardous condition was noted during the inspection.</p>		
Required for an impoundment which functions as a SEDIMENTATION POND.	<p>2. Sediment storage capacity, including elevation of 60% and 100% sediment storage volumes, and estimated average elevation of existing sediment.</p> <p>Sediment Storage Capacity:  60 % Elevation: 6842.0 (2.00')  100% Elevation: 6843.0 (3.00')</p> <p>The pond was dry at the time of inspection . The sediment marker is in place, and field observation shows the sediment level to be well below the cleanout elevation. The bottom of pond and approximate sediment elevation is 6840.0.</p>	
	<p>3. Principle and emergency spillway elevations.</p> <p>Principle Spillway Elevation: 6848 feet  Emergency Spillway Elevation: 6849 feet  Total volume of pond at Spillway: 1.55 Acre-Feet (Elev. 6848.00')  Required runoff storage: 1.28 Acre-Feet</p>	

4. **Field Information.** Provide current water elevation, whether pond is discharging, type and number of samples taken, monitoring/instrumentation information, inlet/outlet conditions or other related activities associated with the pond decanting, embankment erosion/repairs, monitoring information, vegetation on outlopes of embankments, etc.

The pond was dry at the time of inspection.

5. **Field Evaluation.** Describe any changes in the geometry of the structure, average and maximum depths and elevations of impounded water, estimated sediment or slurry volume and remaining storage capacity, estimated volume of water impounded, and any other aspect of the impounding structure affecting its stability or function which has occurred during the reporting period.

There have been no changes since last inspection

**Certification Statement**

I hereby certify that: I am experienced in the construction of impoundments; I am qualified and authorized under the direction of a Registered Professional Engineer to inspect the condition and appearance of impoundments in accordance with the certified and approved designs for this structure; that the impoundment has been maintained in accordance with approved design and meet or exceed the minimum design requirements under all applicable federal, state and local regulations; and, that inspections and inspection reports are made by myself, or under my direction and include any appearances of instability, structural weakness or other hazardous conditions of the structure affecting stability.

**By:**

(Full Name and Title)

Signature: *R. K. Chhab* Date: 06/17/2016

**IMPOUNDMENT INSPECTION AND REPORT**

Permit Number	C/025/0005	Report Date	06/17/2016
Mine Name	Coal Hollow Mine		
Company Name	Alton Coal Development, LLC		
Impoundment Identification	Impoundment Name	Pond 6	
	Impoundment Number	Pond 6	
	MSHA Mine ID Number	42-02519	

**IMPOUNDMENT INSPECTION**

Inspection Date	16-Jun-16
Inspected By	B.K.Nicholes

Reason for Inspection (Annual, Quarterly or Other Periodic Inspections, Critical Installation, or Completion of Construction)	Quarterly Inspection.
--	-----------------------

1. Describe any appearance of any instability, structural weakness, or any other hazardous condition.  
 No instability of the embankment or hazardous condition was noted during the inspection.

Required for an impoundment which functions as a SEDIMENTATION POND.

2. Sediment storage capacity, including elevation of 60% and 100% sediment storage volumes, and estimated average elevation of existing sediment.  
 Sediment Storage Capacity:  
 60 % Elevation: 6860.0 (2.00')  
 100% Elevation: 6861.0 (3.00')  
 The pond was dry at the time of inspection . The sediment marker is in place, and field observation shows the sediment level to be well below the cleanout elevation. The bottom of pond and approximate sediment elevation is 6858.0.

3. Principle and emergency spillway elevations.  
 Principle Spillway Elevation: 6866 feet  
 Emergency Spillway Elevation: 6867 feet  
 Total volume of pond at Spillway: 3.14 Acre-Feet (Elev. 6866.00')  
 Required runoff storage: 1.43 Acre-Feet

4. **Field Information.** Provide current water elevation, whether pond is discharging, type and number of samples taken, monitoring/instrumentation information, inlet/outlet conditions or other related activities associated with the pond decanting, embankment erosion/repairs, monitoring information, vegetation on outlopes of embankments, etc.

The pond was dry at the time of inspection.

5. **Field Evaluation.** Describe any changes in the geometry of the structure, average and maximum depths and elevations of impounded water, estimated sediment or slurry volume and remaining storage capacity, estimated volume of water impounded, and any other aspect of the impounding structure affecting its stability or function which has occurred during the reporting period.

There have been no changes since last inspection

**Certification Statement**

I hereby certify that: I am experienced in the construction of impoundments; I am qualified and authorized under the direction of a Registered Professional Engineer to inspect the condition and appearance of impoundments in accordance with the certified and approved designs for this structure; that the impoundment has been maintained in accordance with approved design and meet or exceed the minimum design requirements under all applicable federal, state and local regulations: and, that inspections and inspection reports are made by myself, or under my direction and include any appearances of instability, structural weakness or other hazardous conditions of the structure affecting stability.

**By:**

(Full Name and Title)

Signature: B. Keith Anderson Date: 06/17/2016