APPENDIX B

Slope Stability Analysis Under Static Conditions - Computer Output

```
PROFIL
GENWAL - Proposed storage pad expansion with debris slope at base of slope
scoured
6
6
0.0 100.0 25.0 100.0 1
25.0 100.0 50.0 102.0 1
50.0 102.0 53.3 131.7 1
53.3 131.7 55.0 131.8 1
55.0 131.8 67.0 140.4 1
67.0 140.4 150.0 140.4 1
SOIL
1
120.0 130.0 700.0 46.0 0.0 0.0 1
CIRCL2
11
10
50.0 52.0
55.0 90.0
0.0
3.0
80.0
5.0
```

GEOSLOPE
Version 3.11

Supplied by GEOCOMP Corp.
342 Sudbury Rd., Concord, MA. 01742
(617) 369-8304

Portions of this software and documentation are copyrighted 1983,1984,1985 by GEOCOMP Corp. All rights are reserved

GEOSLOPE is based on the program, STABL3, developed at Purdue University under sponsorship of the Federal Highway Administration.

GEOCOMP Corp. has modified the program to run on various microcomputers and plotting devices.

GEOCOMP Corp. makes no warranties as to the fitness of this software. The user bears all responsibility for accuracy and correctness of results produced by this software. See the users manual for further warranty information.

Supplied under exclusive license to :
EARTH FAX
Midvale, UT (s/n 5080)

1
EARTH FAX
Midvale, UT (s/n 5080)

--SLOPE STABILITY ANALYSIS--
SIMPLIFIED JANBU METHOD OF SLICES
IRREGULAR FAILURE SURFACES

PROBLEM DESCRIPTION GENWAL - Proposed storage pad expansion
with debris slope at base of slope scour

BOUNDARY COORDINATES

6 TOP BOUNDARIES
6 TOTAL BOUNDARIES

BOUNDARY NO.	X-LEFT	Y-LEFT	X-RIGHT	Y-RIGHT	SOIL TYPE BELOW BND
1	.00	100.00	25.00	100.00	1
2	25.00	100.00	50.00	102.00	1
3	50.00	102.00	53.30	131.70	1
4	53.30	131.70	55.00	131.80	1
5	55.00	131.80	67.00	140.40	1
6	67.00	140.40	150.00	140.40	1

ISOTROPIC SOIL PARAMETERS

1 TYPE(S) OF SOIL

SOIL TYPE NO.	TOTAL UNIT WT.	SATURATED UNIT WT.	COHESION INTERCEPT	FRICTION ANGLE (DEG)	PORE PRESSURE PARAMETER	PRESSURE CONSTANT	PIEZOMETRIC SURFACE NO.
1	120.0	130.0	700.0	46.0	.00	.0	1

A CRITICAL FAILURE SURFACE SEARCHING METHOD, USING A RANDOM TECHNIQUE FOR GENERATING CIRCULAR SURFACES, HAS BEEN SPECIFIED.

110 TRIAL SURFACES HAVE BEEN GENERATED.

10 SURFACES INITIATE FROM EACH OF 11 POINTS EQUALLY SPACED
ALONG THE GROUND SURFACE BETWEEN X = 50.00
AND X = 52.00

EACH SURFACE TERMINATES BETWEEN X = 55.00
AND X = 90.00

UNLESS FURTHER LIMITATIONS WERE IMPOSED, THE MINIMUM ELEVATION
AT WHICH A SURFACE EXTENDS IS Y = .00

3.00 FT. LINE SEGMENTS DEFINE EACH TRIAL FAILURE SURFACE.

RESTRICTIONS HAVE BEEN IMPOSED UPON THE ANGLE OF INITIATION.
THE ANGLE HAS BEEN RESTRICTED BETWEEN THE ANGLES OF 5.0 AND 80.0 DEG.

FACTOR OF SAFETY CALCULATION HAS GONE THROUGH TEN ITERATIONS

FACTOR OF SAFETY FOR THE PRECEDING SPECIFIED SURFACE = 2.320

FOLLOWING ARE DISPLAYED THE TEN MOST CRITICAL OF THE TRIAL FAILURE SURFACES EXAMINED. THEY ARE ORDERED - MOST CRITICAL FIRST.

SAFETY FACTORS ARE CALCULATED BY THE MODIFIED BISHOP METHOD.

1
EARTH FAX
Midvale, UT (s/n 5080)

FAILURE SURFACE # 1 SPECIFIED BY 17 COORDINATE POINTS

SAFETY FACTOR = 1.583

X-CENTER = -226.27
Y-CENTER = 318.27
RADIUS = 350.85

POINT NO.	X-SURF	Y-SURF	ALPHA (DEG)
1	50.00	102.00	52.19
2	51.84	104.37	52.68
3	53.66	106.76	53.17
4	55.46	109.16	53.66
5	57.23	111.58	54.15
6	58.99	114.01	54.64
7	60.73	116.46	55.13
8	62.44	118.92	55.62
9	64.14	121.39	56.11
10	65.81	123.88	56.60
11	67.46	126.39	57.09
12	69.09	128.91	57.58
13	70.70	131.44	58.07
14	72.29	133.99	58.56
15	73.85	136.55	59.05
16	75.39	139.12	59.54
17	76.15	140.40	

SLICE NO.	X	DX	DW	DQ	DU	DN	DSr
1	50.92	1.84	1564.91	.00	.00	457.11	741.43
2	52.57	1.46	3469.14	.00	.00	2327.11	1965.03
3	53.48	.36	1083.11	.00	.00	776.80	950.61
4	54.33	1.34	3880.66	.00	.00	2749.57	2241.46
5	55.23	.46	1266.32	.00	.00	887.29	1022.91
6	56.35	1.78	4777.27	.00	.00	3312.08	2609.54

7	58.11	1.76	4477.53	.00	.00	3048.24	2436.90
8	59.86	1.74	4176.98	.00	.00	2782.24	2262.84
9	61.59	1.72	3875.97	.00	.00	2514.29	2087.51
10	63.29	1.69	3574.77	.00	.00	2244.58	1911.04
11	64.97	1.67	3273.69	.00	.00	1973.31	1733.53
12	66.40	1.19	2169.54	.00	.00	1250.00	1260.24
13	67.23	.46	794.36	.00	.00	442.35	731.77
14	68.28	1.63	2494.25	.00	.00	1263.20	1268.88
15	69.90	1.61	1973.77	.00	.00	784.25	955.48
16	71.49	1.59	1463.65	.00	.00	311.26	645.99
17	73.07	1.56	964.15	.00	.00	-155.57	340.53
18	74.62	1.54	475.51	.00	.00	-616.02	39.24
19	75.77	.75	57.98	.00	.00	-475.27	131.33

1

EARTH FAX
Midvale, UT (s/n 5080)

FAILURE SURFACE # 2 SPECIFIED BY 16 COORDINATE POINTS

SAFETY FACTOR = 1.584

X-CENTER = -13.14
Y-CENTER = 167.20
RADIUS = 89.61

POINT NO.	X-SURF	Y-SURF	ALPHA (DEG)
1	50.20	103.80	45.93
2	52.29	105.96	47.85
3	54.30	108.18	49.77
4	56.24	110.47	51.69
5	58.10	112.83	53.60
6	59.88	115.24	55.52
7	61.58	117.72	57.44
8	63.19	120.24	59.36
9	64.72	122.83	61.28
10	66.16	125.46	63.20
11	67.51	128.13	65.11
12	68.78	130.86	67.03
13	69.95	133.62	68.95
14	71.02	136.42	70.87
15	72.01	139.25	72.79
16	72.36	140.40	

1

EARTH FAX
Midvale, UT (s/n 5080)

FAILURE SURFACE # 3 SPECIFIED BY 16 COORDINATE POINTS

SAFETY FACTOR = 1.592
X-CENTER = -92.96
Y-CENTER = 199.06
RADIUS = 172.79

POINT NO.	X-SURF	Y-SURF	ALPHA (DEG)
1	50.00	102.00	56.32
2	51.66	104.50	57.32
3	53.28	107.03	58.31
4	54.86	109.58	59.31
5	56.39	112.16	60.30
6	57.88	114.76	61.30
7	59.32	117.40	62.29
8	60.71	120.05	63.29
9	62.06	122.73	64.28
10	63.36	125.43	65.28
11	64.62	128.16	66.27
12	65.83	130.91	67.27
13	66.98	133.67	68.26
14	68.10	136.46	69.26
15	69.16	139.26	70.25
16	69.57	140.40	

1

EARTH FAX
Midvale, UT (s/n 5080)

FAILURE SURFACE # 4 SPECIFIED BY 15 COORDINATE POINTS

SAFETY FACTOR = 1.639

X-CENTER = 2.42
Y-CENTER = 157.34
RADIUS = 70.56

POINT NO.	X-SURF	Y-SURF	ALPHA (DEG)
1	50.40	105.60	44.06
2	52.56	107.69	46.50
3	54.62	109.87	48.93
4	56.59	112.13	51.37
5	58.46	114.47	53.81
6	60.24	116.89	56.24
7	61.90	119.39	58.68
8	63.46	121.95	61.12
9	64.91	124.58	63.55
10	66.25	127.26	65.99
11	67.47	130.00	68.42
12	68.57	132.79	70.86
13	69.56	135.63	73.30
14	70.42	138.50	75.73
15	70.90	140.40	

1

EARTH FAX
Midvale, UT (s/n 5080)

FAILURE SURFACE # 5 SPECIFIED BY 16 COORDINATE POINTS

SAFETY FACTOR = 1.694

X-CENTER = -1430.94
Y-CENTER = 1028.77
RADIUS = 1746.23

POINT NO.	X-SURF	Y-SURF	ALPHA (DEG)
1	50.20	103.80	58.06
2	51.79	106.35	58.16
3	53.37	108.90	58.26
4	54.95	111.45	58.36
5	56.52	114.00	58.46
6	58.09	116.56	58.56
7	59.66	119.12	58.65
8	61.22	121.68	58.75
9	62.77	124.25	58.85
10	64.32	126.82	58.95
11	65.87	129.39	59.05
12	67.41	131.96	59.15
13	68.95	134.53	59.24
14	70.49	137.11	59.34
15	72.02	139.69	59.44
16	72.44	140.40	

1
EARTH FAX
Midvale, UT (s/n 5080)

FAILURE SURFACE # 6 SPECIFIED BY 17 COORDINATE POINTS

SAFETY FACTOR = 1.703

X-CENTER = -68.42
Y-CENTER = 234.85
RADIUS = 176.76

POINT NO.	X-SURF	Y-SURF	ALPHA (DEG)
1	50.20	103.80	42.64
2	52.41	105.84	43.61
3	54.58	107.91	44.58
4	56.72	110.01	45.55
5	58.82	112.15	46.53
6	60.88	114.33	47.50
7	62.91	116.54	48.47
8	64.90	118.79	49.44
9	66.85	121.07	50.42
10	68.76	123.38	51.39
11	70.63	125.72	52.36
12	72.46	128.10	53.33

13	74.25	130.51	54.31
14	76.00	132.94	55.28
15	77.71	135.41	56.25
16	79.38	137.90	57.22
17	80.99	140.40	

1

EARTH FAX
Midvale, UT (s/n 5080)

FAILURE SURFACE # 7 SPECIFIED BY 19 COORDINATE POINTS

SAFETY FACTOR = 1.704

X-CENTER = -648.15
Y-CENTER = 764.60
RADIUS = 962.53

POINT NO.	X-SURF	Y-SURF	ALPHA (DEG)
1	50.00	102.00	46.59
2	52.06	104.18	46.76
3	54.12	106.37	46.94
4	56.17	108.56	47.12
5	58.21	110.76	47.30
6	60.24	112.96	47.48
7	62.27	115.18	47.66
8	64.29	117.39	47.84
9	66.30	119.62	48.01
10	68.31	121.85	48.19
11	70.31	124.08	48.37
12	72.30	126.33	48.55
13	74.29	128.57	48.73
14	76.27	130.83	48.91
15	78.24	133.09	49.09
16	80.20	135.36	49.26
17	82.16	137.63	49.44
18	84.11	139.91	49.62
19	84.53	140.40	

1

EARTH FAX
Midvale, UT (s/n 5080)

FAILURE SURFACE # 8 SPECIFIED BY 17 COORDINATE POINTS

SAFETY FACTOR = 1.758

X-CENTER = -126.92
Y-CENTER = 285.45
RADIUS = 252.56

FAILURE SURFACE #10 SPECIFIED BY 19 COORDINATE POINTS

SAFETY FACTOR = 1.850

X-CENTER = 20.10
Y-CENTER = 163.40
RADIUS = 68.29

POINT NO.	X-SURF	Y-SURF	ALPHA (DEG)
1	50.00	102.00	27.22
2	52.67	103.38	29.74
3	55.27	104.86	32.26
4	57.81	106.47	34.77
5	60.27	108.18	37.29
6	62.66	109.99	39.81
7	64.97	111.92	42.33
8	67.18	113.94	44.84
9	69.31	116.05	47.36
10	71.34	118.26	49.88
11	73.28	120.55	52.39
12	75.11	122.93	54.91
13	76.83	125.38	57.43
14	78.45	127.91	59.95
15	79.95	130.51	62.46
16	81.34	133.17	64.98
17	82.60	135.89	67.50
18	83.75	138.66	70.02
19	84.39	140.40	

1
EARTH FAX
Midvale, UT (s/n 5080)

POINT NO.	X-SURF	Y-SURF	ALPHA (DEG)
1	50.40	105.60	44.94
2	52.52	107.72	45.62
3	54.62	109.87	46.30
4	56.70	112.04	46.98
5	58.74	114.23	47.66
6	60.76	116.45	48.34
7	62.76	118.69	49.02
8	64.72	120.95	49.70
9	66.66	123.24	50.38
10	68.58	125.55	51.06
11	70.46	127.89	51.74
12	72.32	130.24	52.42
13	74.15	132.62	53.10
14	75.95	135.02	53.78
15	77.72	137.44	54.46
16	79.47	139.88	55.14
17	79.83	140.40	

1

EARTH FAX
Midvale, UT (s/n 5080)

FAILURE SURFACE # 9 SPECIFIED BY 13 COORDINATE POINTS

SAFETY FACTOR = 1.812

X-CENTER = -15.12
Y-CENTER = 156.97
RADIUS = 82.31

POINT NO.	X-SURF	Y-SURF	ALPHA (DEG)
1	50.60	107.40	54.02
2	52.36	109.83	56.11
3	54.04	112.32	58.20
4	55.62	114.87	60.29
5	57.10	117.48	62.37
6	58.49	120.14	64.46
7	59.79	122.84	66.55
8	60.98	125.59	68.64
9	62.07	128.39	70.73
10	63.06	131.22	72.82
11	63.95	134.09	74.90
12	64.73	136.98	76.99
13	65.23	139.13	

1

EARTH FAX
Midvale, UT (s/n 5080)

```
          Y            A     X     I     S

         100.00    118.75    137.50    156.25    175.00    193.75

X          .00 *----------+----------+----------+----------+----------+
               -
               -
               -
               -
               -
       18.75 +
               -
               *
               -
               -
               -
A      37.50 +
               -
               -
               -
               -*249...
               -.1214.9..... .  *
X      56.25 +..0.11599..... .*.
               - ..0.6121539.......
               - ...0..72123539 99..
               -  ...00.76121233 3 99*
               -   .....0..67112423.33
               -    .....00..668112522
I      75.00 +     ......0..76861 11
               -      .......00..7668.
               -         ......0.077.6
               -           .........77
               -              ........
               -                   ...
S      93.75 +
               -
               -
               -
               -
               -
      112.50 +
               -
               -
               -
               -
               -
      131.25 +
               -
               -
               -
               -
               -
      150.00 +                    *
```